Homologation

LiveWire Tool

Type: Cleco-17BPYPB13QL

Serial no.: 737457

Apex Tool Group GmbH
Industriestraße 1, 73463 Westhausen, Germany
Tel.: +49 7363 81-0
Fax: +49 7363 81-222
E-Mail: info@apexpowertools.eu
www.apexpowertools.eu

Contents

Homologation: Cleco-17BPYPB13QL SN: 737457

		Page
Cover sheet		1
Contents		2
Test sheet no. 2 (torque determination 30 %)		3
Machine Capability Study, Tool System	30 % hard	4
Machine Capability Study, Control System	30 % hard	7
Curves of the 1st and 100th measurement	30 % hard	10
Machine Capability Study, Tool System	30 % soft	11
Machine Capability Study, Control System	30 % soft	14
Curves of the 1st and 100th measurement	30 % soft	17
Test sheet no. 3 (torque determination 80 %)		18
Machine Capability Study, Tool System	80 % hard	19
Machine Capability Study, Control System	80 % hard	22
Curves of the 1st and 100th measurement	80 % hard	25
Machine Capability Study, Tool System	80 % soft	26
Machine Capability Study, Control System	80 % soft	29
Curves of the 1st and 100th measurement	80 % soft	32
Test sheet no. 4 (torque determination 100 %)		33
Machine Capability Study, Tool System	100 % hard	34
Machine Capability Study, Control System	100 % hard	37
Curves of the 1st and 100th measurement	100 % hard	40
Machine Capability Study, Tool System	100 % soft	41
Machine Capability Study, Control System	100 % soft	44
Curves of the 1st and 100th measurement	100 % soft	47
Annex 3 (ability contemplation at 40° / 60 %)	**without angle correction**	48
Graphical representation	40° / 60 %	50
Machine Capability Study, Tool System	40° / 60 %	51
Machine Capability Study, Control System	40° / 60 %	54
Curves of the 1st and 100th measurement	40° / 60 %	57
Annex 3 (ability contemplation at 180° / 80 %)	**without angle correction**	58
Graphical representation	180° / 80 %	60
Machine Capability Study, Tool System	180° / 80 %	61
Machine Capability Study, Control System	180° / 80 %	64
Curves of the 1st and 100th measurement	180° / 80 %	67

Investigation no.: 010/2017
Date: 25.09.2017

Test sheet no. 2

Machine Capability Study 30 %

Multi-stage tightening system	☑	Speed 50 rpm	5.38 %
Single-stage tightening system	☐	Speed 100 %	629 rpm

Manufacturer: Apex Tool Group GmbH Serial no: **737457**

Test torque: Tq min. + 0.3 (Tq max. - Tq min.) 6.00 Nm with 26 volt battery

Hard joint (H)	36.09 Nm / Revolution	Angle degree	30°
Soft joint (L)	2.93 Nm / Revolution	Angle degree	360°

		H	L
a)	Tolerance down / up	5.58 - 6.42 Nm	5.58 - 6.42 Nm
	Tolerance down / up	7 %	7 %
	Average torque	6.02 Nm	5.87 Nm
	Standard deviation	0.05 Nm	0.02 Nm
	Torque scatter (99,73%)	0.28 Nm	0.14 Nm
	C_m	3.04	5.96
	C_{mk}	2.93	4.10

b)	Min. C_m hard/soft (lowest value)	3.04
	Min. C_{mk} hard/soft (lowest value)	2.93

Capability is reached if minimum C_{mk} value ≥1.67

Note:

Machine Capability Study
Control System

Cleco Production Tools

Plant	ATG Westhausen	Operator Name	Anton Czapla
Date	20.09.2017		

Ord. No.	17BPYPB13QL	Part type	17BPYPB13QL	Contr.item	yes
Serial No.	737457d	Char.Descr.	VM1698-4	Inspection Val. 6,00 0,42	USL 6,42
		Serial No.	1024210	Unit Nm -0,42	LSL 5,58
Char.Type	variable			Tolerance value 7 %	Decimal Pl. 2
Cust.Name	Homologation	Reference System	VM1698-4	Test Electronic	MPRO400SE
Contr.No.	816N2152	Reference Transducer	10 / 1029292	nges.	100

Evaluation from 20.09.2017 13:20:05 to 20.09.2017 13:38:45

Rem. Tq. 30% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.274 Nm/A





Drawing Values		Collected Values		Statistics	
T_m	6.00			$\bar{x}$	6.0150
LSL	5.58	x_{min}	5.90	$\bar{x}$-3s	5.8769
USL	6.42	x_{max}	6.12	$\bar{x}$+3s	6.1531
T	0.84	R	0.22	6s	0.2761
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1 1.4 $\hat{\sigma} = s_{tot}$
Potential Capability index	=	C_m	3.04
Critical capability index	=	C_{mk}	2.93

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457d	Characteristic			
Type	17BPYPB13QL	Char.Descr.	VM1698-4	Inspection Val.	6,00
Ord. No.	17BPYPB13QL	Ser.No.	1024210	LSL	5,58
				USL	6,42
Remark	Tq. 30% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.274 Nm/A				

Char.No	Char.Descr.	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
1024210	VM1698-4	6,10	6,12	6,07	6,05	6,05	6,06	6,07	6,10	6,04	6,02
1024210	VM1698-4	30,00	30,75	30,00	29,75	29,50	29,25	29,25	30,25	30,25	29,50

Char.No	Char.Descr.	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
1024210	VM1698-4	6,06	6,05	6,12	6,07	6,11	6,04	6,06	6,06	6,06	6,01
1024210	VM1698-4	29,75	29,00	29,50	29,75	30,75	30,00	30,75	30,25	29,75	30,50

Char.No	Char.Descr.	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
1024210	VM1698-4	6,02	6,12	6,06	6,11	6,07	6,01	6,03	6,02	6,05	6,01
1024210	VM1698-4	29,75	30,25	30,50	30,75	30,25	30,00	30,00	30,00	29,50	29,25

Char.No	Char.Descr.	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
1024210	VM1698-4	5,99	6,02	6,03	6,03	5,98	5,97	6,04	6,00	5,97	6,02
1024210	VM1698-4	29,25	30,25	30,00	29,50	29,50	29,25	29,50	30,50	30,25	30,25

Char.No	Char.Descr.	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
1024210	VM1698-4	5,99	6,05	5,97	5,96	6,05	6,00	5,98	6,04	6,01	5,98
1024210	VM1698-4	30,25	30,25	30,25	30,25	31,00	30,25	30,00	30,25	30,25	30,50

Char.No	Char.Descr.	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
1024210	VM1698-4	6,01	6,00	6,01	5,97	5,99	6,06	6,01	6,01	6,00	5,97
1024210	VM1698-4	30,00	30,25	29,75	29,50	30,50	31,00	30,75	30,25	29,50	31,00

Char.No	Char.Descr.	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
1024210	VM1698-4	6,03	6,05	6,01	5,97	6,01	5,99	5,98	5,96	5,97	6,00
1024210	VM1698-4	30,50	31,00	30,75	31,00	30,50	29,75	29,75	30,25	51,75	29,50

Char.No	Char.Descr.	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
1024210	VM1698-4	6,03	5,98	6,03	5,97	6,03	5,97	6,06	6,01	6,05	5,95
1024210	VM1698-4	29,50	29,25	29,25	29,00	30,50	30,00	30,00	30,00	30,00	28,75

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457d	Characteristic			
Type	17BPYPB13QL	Char.Descr.	VM1698-4	Inspection Val.	6,00
Ord. No.	17BPYPB13QL	Ser.No.	1024210	LSL	5,58
				USL	6,42
Remark	Tq. 30% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.274 Nm/A				

Char.No	Char.Descr.	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
1024210	VM1698-4	6,04	6,00	6,01	5,97	6,00	6,05	5,98	5,99	6,00	6,01
1024210	VM1698-4	29,50	30,00	30,00	30,25	29,75	29,50	29,25	29,75	30,00	30,00

Char.No	Char.Descr.	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
1024210	VM1698-4	5,95	6,02	5,94	5,96	5,96	5,90	5,92	5,91	5,94	5,97
1024210	VM1698-4	28,50	29,75	29,25	30,25	30,50	29,75	29,50	30,25	29,75	29,00

Machine Capability Study
Tool System

Page 1 / 1

Plant ATG Westhausen		Operator Name Anton Czapla	Date 20.09.2017

Ord. No. 17BPYPB13QL	Part type 17BPYPB13QL				Contr.item yes
Serial No. 737457d	Char.Descr. 936522PT	Inspection Val.	6,00	0,42	USL 6,42
	Serial No. 154244	Unit	Nm	-0,42	LSL 5,58
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2
Cust.Name Homologation	Reference System VM1698-4	Test Electronic MPRO400SE			
Contr.No. 816N2152	Reference Transducer 10 / 1029292	nges. 100			

Evaluation from 20.09.2017 13:20:08 to 20.09.2017 13:38:48

Rem. Tq. 30% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.274 Nm/A





Drawing Values		Collected Values		Statistics	
T_m	6.00			$\bar{x}$	6.0549
LSL	5.58	x_{min}	6.01	$\bar{x}$-3s	5.9449
USL	6.42	x_{max}	6.14	$\bar{x}$+3s	6.1649
T	0.84	R	0.13	6s	0.2200
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			$M1_{1.4}$ $\hat{\sigma} = s_{tot}$
Potential Capability index	=	C_m	3.82
Critical capability index	=	C_{mk}	3.32

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457d	Characteristic			
Type	17BPYPB13QL	Char.Descr.	936522PT	Inspection Val.	6,00
Ord. No.	17BPYPB13QL	Ser.No.	154244	LSL	5,58
				USL	6,42
Remark	Tq. 30% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.274 Nm/A				

Char.No	Char.Descr.	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
154244	936522PT	6,09	6,06	6,01	6,01	6,01	6,04	6,06	6,09	6,09	6,04
154244	936522PT	31,00	30,00	31,00	30,00	30,00	29,00	30,00	31,00	31,00	30,00

Char.No	Char.Descr.	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
154244	936522PT	6,09	6,04	6,14	6,04	6,09	6,04	6,09	6,04	6,04	6,04
154244	936522PT	31,00	30,00	30,00	30,00	31,00	31,00	31,00	31,00	30,00	31,00

Char.No	Char.Descr.	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
154244	936522PT	6,04	6,14	6,04	6,14	6,04	6,01	6,06	6,01	6,06	6,06
154244	936522PT	30,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	30,00	30,00

Char.No	Char.Descr.	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
154244	936522PT	6,01	6,06	6,06	6,06	6,01	6,01	6,06	6,01	6,06	6,01
154244	936522PT	30,00	31,00	31,00	30,00	30,00	30,00	30,00	31,00	31,00	31,00

Char.No	Char.Descr.	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
154244	936522PT	6,01	6,11	6,01	6,01	6,06	6,01	6,01	6,06	6,01	6,04
154244	936522PT	31,00	31,00	31,00	31,00	31,00	31,00	30,00	31,00	31,00	31,00

Char.No	Char.Descr.	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
154244	936522PT	6,01	6,09	6,01	6,04	6,04	6,06	6,09	6,04	6,04	6,04
154244	936522PT	31,00	31,00	30,00	30,00	31,00	31,00	32,00	31,00	30,00	31,00

Char.No	Char.Descr.	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
154244	936522PT	6,09	6,09	6,09	6,04	6,09	6,04	6,04	6,04	6,09	6,09
154244	936522PT	31,00	31,00	31,00	31,00	31,00	30,00	30,00	31,00	30,00	30,00

Char.No	Char.Descr.	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
154244	936522PT	6,09	6,09	6,04	6,04	6,09	6,06	6,14	6,09	6,09	6,01
154244	936522PT	30,00	30,00	30,00	30,00	31,00	31,00	31,00	31,00	31,00	30,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457d	Characteristic			
Type	17BPYPB13QL	Char.Descr.	936522PT	Inspection Val.	6,00
Ord. No.	17BPYPB13QL	Ser.No.	154244	LSL	5,58
				USL	6,42
Remark	Tq. 30% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.274 Nm/A				

Char.No	Char.Descr.	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
154244	936522PT	6,09	6,14	6,04	6,04	6,09	6,14	6,04	6,09	6,04	6,09
154244	936522PT	30,00	30,00	30,00	31,00	30,00	30,00	29,00	31,00	31,00	30,00

Char.No	Char.Descr.	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
154244	936522PT	6,01	6,11	6,01	6,06	6,04	6,01	6,01	6,04	6,01	6,06
154244	936522PT	30,00	31,00	30,00	31,00	31,00	31,00	31,00	31,00	31,00	30,00

Torque graphs

Machine Capability Study 30 %

Model: **17BPYPB13QL**
Serial no: **737457**

Angle degree: **30°**
Test torque: **6.0 Nm**



Value no. 1
Graph
Torque / Angle



Value no. 1
Graph
Torque / Time



Value no. 100
Graph
Torque / Angle



Value no. 100
Graph
Torque / Time

Machine Capability Study
Control System

Page 1 / 1

Plant ATG Westhausen		Operator Name Anton Czapla	Date 20.09.2017

Ord. No. 17BPYPB13QL	Part type 17BPYPB13QL				Contr.item yes
Serial No. 737457c	Char.Descr. VM1698-4	Inspection Val.	6,00	0,42	USL 6,42
	Serial No. 1024210	Unit	Nm	-0,42	LSL 5,58
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2

Cust.Name Homologation	Reference System VM1698-4	Test Electronic MPRO400SE
Contr.No. 816N2152	Reference Transducer 10 / 1029292	nges. 100

Evaluation from 20.09.2017 13:43:10 to 20.09.2017 14:05:20

Rem. Tq. 30% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.274 Nm/A





Drawing Values		Collected Values		Statistics	
T_m	6.00			$\bar{x}$	5.8686
LSL	5.58	x_{min}	5.82	$\bar{x}$-3s	5.7981
USL	6.42	x_{max}	5.95	$\bar{x}$+3s	5.9391
T	0.84	R	0.13	6s	0.1409
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			$M1_{1,4}$ $\hat{\sigma} = s_{tot}$
Potential Capability index	=	C_m	5.96
Critical capability index	=	C_{mk}	4.10

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\AppData\QW\QWE\MessWert\2017\737457cM.DFD

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457c	Characteristic			
Type	17BPYPB13QL	Char.Descr.	VM1698-4	Inspection Val.	6,00
Ord. No.	17BPYPB13QL	Ser.No.	1024210	LSL	5,58
				USL	6,42
Remark	Tq. 30% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.274 Nm/A				

Char.No	Char.Descr.	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
1024210	VM1698-4	5,94	5,89	5,89	5,93	5,89	5,88	5,86	5,89	5,90	5,84
1024210	VM1698-4	366,25	362,50	362,50	366,00	363,00	355,75	360,00	363,50	360,50	354,00

Char.No	Char.Descr.	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
1024210	VM1698-4	5,85	5,89	5,86	5,95	5,86	5,88	5,85	5,85	5,87	5,86
1024210	VM1698-4	357,50	361,00	357,25	366,75	360,00	358,25	353,25	356,25	359,50	355,25

Char.No	Char.Descr.	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
1024210	VM1698-4	5,85	5,89	5,85	5,90	5,88	5,84	5,86	5,86	5,89	5,84
1024210	VM1698-4	358,00	359,25	356,75	360,50	359,50	356,00	357,25	358,75	358,00	357,25

Char.No	Char.Descr.	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
1024210	VM1698-4	5,86	5,87	5,86	5,86	5,88	5,86	5,84	5,85	5,85	5,85
1024210	VM1698-4	357,00	359,50	358,00	358,50	359,00	358,25	356,25	357,75	357,25	356,25

Char.No	Char.Descr.	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
1024210	VM1698-4	5,90	5,86	5,89	5,90	5,91	5,89	5,88	5,88	5,82	5,86
1024210	VM1698-4	360,50	357,25	359,75	361,75	362,75	360,50	360,50	357,50	349,00	355,50

Char.No	Char.Descr.	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
1024210	VM1698-4	5,89	5,85	5,86	5,86	5,86	5,89	5,85	5,86	5,86	5,86
1024210	VM1698-4	359,75	353,00	361,50	358,25	358,75	361,00	354,25	357,75	358,50	358,50

Char.No	Char.Descr.	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
1024210	VM1698-4	5,87	5,85	5,85	5,86	5,86	5,90	5,83	5,86	5,85	5,85
1024210	VM1698-4	358,00	357,00	356,25	359,00	358,25	361,25	349,75	352,50	355,00	354,25

Char.No	Char.Descr.	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
1024210	VM1698-4	5,84	5,86	5,84	5,85	5,89	5,83	5,86	5,88	5,89	5,87
1024210	VM1698-4	352,50	356,75	352,00	356,50	360,75	348,25	355,50	360,00	359,75	358,00

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457c	Characteristic			
Type	17BPYPB13QL	Char.Descr.	VM1698-4	Inspection Val.	6,00
Ord. No.	17BPYPB13QL	Ser.No.	1024210	LSL	5,58
				USL	6,42
Remark	Tq. 30% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.274 Nm/A				

Char.No	Char.Descr.	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
1024210	VM1698-4	5,88	5,85	5,90	5,85	5,87	5,85	5,85	5,84	5,87	5,88
1024210	VM1698-4	359,75	350,50	357,00	351,25	353,50	354,75	354,25	352,00	359,25	359,00

Char.No	Char.Descr.	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
1024210	VM1698-4	5,86	5,84	5,89	5,85	5,89	5,91	5,87	5,90	5,86	5,86
1024210	VM1698-4	353,50	355,00	358,50	357,00	361,00	361,25	359,25	359,50	357,75	358,00

Machine Capability Study
Tool System

Page 1 / 1

Plant ATG Westhausen		Operator Name Anton Czapla	Date 20.09.2017

Ord. No. 17BPYPB13QL	Part type 17BPYPB13QL				Contr.item yes
Serial No. 737457c	Char.Descr. 936522PT	Inspection Val.	6,00	0,42	USL 6,42
	Serial No. 154244	Unit	Nm	-0,42	LSL 5,58
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2
Cust.Name Homologation	Reference System VM1698-4	Test Electronic MPRO400SE			
Contr.No. 816N2152	Reference Transducer 10 / 1029292	nges. 100			

Evaluation from 20.09.2017 13:43:14 to 20.09.2017 14:05:24

Rem. Tq. 30% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.274 Nm/A





Drawing Values		Collected Values		Statistics	
T_m	6.00			$\bar{x}$	6.0163
LSL	5.58	x_{min}	6.01	$\bar{x}$-3s	5.9795
USL	6.42	x_{max}	6.04	$\bar{x}$+3s	6.0531
T	0.84	R	0.03	6s	0.0737
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			$M1_{1.4}$ $\hat{\sigma} = s_{tot}$
Potential Capability index	=	C_m	11.40
Critical capability index	=	C_{mk}	10.96

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\AppData\QW\QWE\MessWert\2017\737457c1.DFD

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457c	Characteristic			
Type	17BPYPB13QL	Char.Descr.	936522PT	Inspection Val.	6,00
Ord. No.	17BPYPB13QL	Ser.No.	154244	LSL	5,58
				USL	6,42
Remark	Tq. 30% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.274 Nm/A				

Char.No	Char.Descr.	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
154244	936522PT	6,04	6,04	6,04	6,04	6,04	6,01	6,01	6,04	6,01	6,01
154244	936522PT	363,00	365,00	365,00	366,00	366,00	364,00	365,00	367,00	364,00	364,00

Char.No	Char.Descr.	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
154244	936522PT	6,01	6,01	6,01	6,04	6,04	6,01	6,01	6,01	6,01	6,01
154244	936522PT	368,00	366,00	367,00	364,00	369,00	362,00	365,00	364,00	363,00	367,00

Char.No	Char.Descr.	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
154244	936522PT	6,01	6,01	6,01	6,01	6,01	6,01	6,01	6,01	6,01	6,01
154244	936522PT	367,00	363,00	367,00	367,00	363,00	365,00	363,00	368,00	364,00	366,00

Char.No	Char.Descr.	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
154244	936522PT	6,01	6,01	6,01	6,01	6,01	6,01	6,01	6,01	6,01	6,01
154244	936522PT	368,00	363,00	364,00	366,00	363,00	367,00	365,00	365,00	362,00	364,00

Char.No	Char.Descr.	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
154244	936522PT	6,01	6,01	6,01	6,01	6,01	6,01	6,01	6,01	6,01	6,01
154244	936522PT	362,00	365,00	363,00	366,00	367,00	365,00	367,00	360,00	360,00	361,00

Char.No	Char.Descr.	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
154244	936522PT	6,01	6,01	6,04	6,01	6,01	6,01	6,04	6,01	6,01	6,01
154244	936522PT	362,00	362,00	369,00	363,00	364,00	367,00	362,00	362,00	367,00	368,00

Char.No	Char.Descr.	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
154244	936522PT	6,01	6,01	6,01	6,01	6,01	6,01	6,01	6,01	6,01	6,01
154244	936522PT	366,00	364,00	365,00	368,00	366,00	366,00	360,00	360,00	362,00	360,00

Char.No	Char.Descr.	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
154244	936522PT	6,01	6,04	6,01	6,01	6,01	6,01	6,04	6,04	6,01	6,01
154244	936522PT	362,00	364,00	361,00	364,00	362,00	357,00	363,00	365,00	361,00	362,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457c	Characteristic			
Type	17BPYPB13QL	Char.Descr.	936522PT	Inspection Val.	6,00
Ord. No.	17BPYPB13QL	Ser.No.	154244	LSL	5,58
				USL	6,42
Remark	Tq. 30% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.274 Nm/A				

Char.No	Char.Descr.	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
154244	936522PT	6,01	6,04	6,01	6,01	6,01	6,01	6,01	6,01	6,01	6,01
154244	936522PT	367,00	362,00	360,00	359,00	360,00	362,00	364,00	361,00	368,00	361,00

Char.No	Char.Descr.	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
154244	936522PT	6,01	6,04	6,04	6,04	6,04	6,04	6,04	6,01	6,04	6,01
154244	936522PT	365,00	362,00	362,00	363,00	364,00	364,00	365,00	363,00	365,00	362,00

Torque graphs

Machine Capability Study 30 %

Model: **17BPYPB13QL**
Serial no: **737457**

Angle degree: **360°**
Test torque: **6.0 Nm**



Value no. 1
Graph
Torque / Angle



Value no. 1
Graph
Torque / Time



Value no. 100
Graph
Torque / Angle



Value no. 100
Graph
Torque / Time

Investigation no.: 010/2017
Date: 25.09.2017

Test sheet no. 3

Machine Capability Study 80 %

Multi-stage tightening system	☑	Speed 50 rpm	5.4 %
Single-stage tightening system	☐	Speed 100 %	629 rpm

Manufacturer: Apex Tool Group GmbH Serial no: **737457**

Test torque: Tq min. + 0.8 (Tq max. - Tq min.) 11.00 Nm with 26 volt battery

Hard joint (H)	66.18 Nm / Revolution	Angle degree	30°
Soft joint (L)	5.44 Nm / Revolution	Angle degree	360°

		H	L
a)	Tolerance down / up	10.23 - 11.77 Nm	10.23 - 11.77 Nm
	Tolerance down / up	7 %	7 %
	Average torque	11.03 Nm	10.89 Nm
	Standard deviation	0.03 Nm	0.02 Nm
	Torque scatter (99,73%)	0.17 Nm	0.11 Nm
	C_m	8.99	14.17
	C_{mk}	8.64	12.05

b)	Min. C_m hard/soft (lowest value)	8.99
	Min. C_{mk} hard/soft (lowest value)	8.64

Capability is reached if minimum C_{mk} value ≥1.67

Note:

Machine Capability Study
Control System

Page 1 / 1

Plant ATG Westhausen		Operator Name Anton Czapla	Date 20.09.2017

Ord. No. 17BPYPB13QL	Part type 17BPYPB13QL				Contr.item yes
Serial No. 737457h	Char.Descr. VM1698-4	Inspection Val.	11,00	0,77	USL 11,77
	Serial No. 1024210	Unit	Nm	-0,77	LSL 10,23
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2

Cust.Name Homologation	Reference System VM1698-4	Test Electronic MPRO400SE
Contr.No. 816N2152	Reference Transducer 50 / 1024729	nges. 100

Evaluation from 20.09.2017 07:25:02 to 20.09.2017 07:46:52

Rem. Tq. 80% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.267 Nm/A







Drawing Values		Collected Values		Statistics	
T_m	11.00			$\bar{x}$	11.0297
LSL	10.23	x_{min}	10.96	$\bar{x}$-3s	10.9441
USL	11.77	x_{max}	11.10	$\bar{x}$+3s	11.1153
T	1.54	R	0.14	6s	0.1713
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			$M1_{1,4}$ $\hat{\sigma} = s_{tot}$
Potential Capability index	=	C_m	8.99
Critical capability index	=	C_{mk}	8.64

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457h	Characteristic			
Type	17BPYPB13QL	Char.Descr.	VM1698-4	Inspection Val.	11,00
Ord. No.	17BPYPB13QL	Ser.No.	1024210	LSL	10,23
				USL	11,77
Remark	Tq. 80% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.267 Nm/A				

Char.No	Char.Descr.	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
1024210	VM1698-4	11,02	11,03	11,01	11,08	11,06	11,02	11,02	11,06	11,03	11,00
1024210	VM1698-4	30,25	30,75	29,75	30,00	31,00	29,75	30,00	31,00	29,50	29,00

Char.No	Char.Descr.	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
1024210	VM1698-4	11,01	11,03	11,02	11,02	11,03	11,04	11,02	11,04	11,08	11,00
1024210	VM1698-4	29,00	28,50	28,75	29,25	29,75	29,75	29,50	29,25	31,25	30,75

Char.No	Char.Descr.	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
1024210	VM1698-4	11,01	11,10	11,02	11,02	11,06	11,05	11,05	11,07	11,01	11,04
1024210	VM1698-4	29,25	31,25	29,50	30,75	31,25	31,50	30,25	30,50	31,00	31,25

Char.No	Char.Descr.	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
1024210	VM1698-4	11,05	11,00	11,04	10,97	11,03	11,03	11,01	11,02	11,09	11,05
1024210	VM1698-4	29,25	31,00	30,00	30,00	31,25	30,25	30,25	31,00	29,00	30,00

Char.No	Char.Descr.	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
1024210	VM1698-4	11,07	11,03	11,05	10,99	10,97	11,02	11,01	11,01	11,05	11,04
1024210	VM1698-4	28,50	29,75	28,75	30,00	29,00	31,25	30,00	31,00	29,50	30,50

Char.No	Char.Descr.	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
1024210	VM1698-4	11,02	10,96	11,02	11,03	11,03	11,04	11,03	11,03	11,06	11,00
1024210	VM1698-4	31,25	30,00	30,75	30,75	30,00	31,00	31,75	29,75	29,25	30,00

Char.No	Char.Descr.	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
1024210	VM1698-4	11,00	11,02	11,08	11,04	11,04	11,05	11,01	11,04	11,00	11,01
1024210	VM1698-4	29,50	31,00	30,75	30,75	29,50	31,00	31,00	29,50	31,00	31,00

Char.No	Char.Descr.	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
1024210	VM1698-4	11,08	11,08	11,00	11,05	11,00	11,06	11,04	11,06	11,07	11,00
1024210	VM1698-4	30,00	29,00	29,25	30,00	29,50	30,50	30,50	28,75	29,25	30,25

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457h	Characteristic			
Type	17BPYPB13QL	Char.Descr.	VM1698-4	Inspection Val.	11,00
Ord. No.	17BPYPB13QL	Ser.No.	1024210	LSL	10,23
				USL	11,77
Remark	Tq. 80% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.267 Nm/A				

Char.No	Char.Descr.	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
1024210	VM1698-4	11,03	11,01	11,04	10,98	11,01	10,97	11,04	11,00	11,04	10,98
1024210	VM1698-4	29,50	31,00	29,75	31,00	29,50	30,75	31,50	30,00	31,25	29,00

Char.No	Char.Descr.	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
1024210	VM1698-4	11,05	11,05	10,97	11,04	11,03	11,00	11,03	11,06	11,07	11,04
1024210	VM1698-4	30,50	29,50	29,75	29,25	30,75	28,50	30,75	31,00	29,75	29,50

Machine Capability Study
Tool System

Page 1 / 1

Plant ATG Westhausen		Operator Name Anton Czapla	Date 20.09.2017

Ord. No. 17BPYPB13QL	Part type 17BPYPB13QL				Contr.item yes
Serial No. 737457h	Char.Descr. 936522PT	Inspection Val.	11,00	0,77	USL 11,77
	Serial No. 154244	Unit	Nm	-0,77	LSL 10,23
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2

Cust.Name Homologation	Reference System VM1698-4	Test Electronic MPRO400SE
Contr.No. 816N2152	Reference Transducer 50 / 1024729	nges. 100

Evaluation from 20.09.2017 07:25:05 to 20.09.2017 07:46:56

Rem. Tq. 80% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.267 Nm/A







Drawing Values		Collected Values		Statistics	
T_m	11.00			$\bar{x}$	11.1261
LSL	10.23	x_{min}	11.06	$\bar{x}$-3s	11.0294
USL	11.77	x_{max}	11.19	$\bar{x}$+3s	11.2228
T	1.54	R	0.13	6s	0.1933
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			$M1_{1.4}$ $\hat{\sigma} = s_{tot}$
Potential Capability index	=	C_m	7.97
Critical capability index	=	C_{mk}	6.66

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\AppData\QW\QWE\MessWert\2017\737457h1.DFD

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457h	Characteristic			
Type	17BPYPB13QL	Char.Descr.	936522PT	Inspection Val.	11,00
Ord. No.	17BPYPB13QL	Ser.No.	154244	LSL	10,23
				USL	11,77
Remark	Tq. 80% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.267 Nm/A				

Char.No	Char.Descr.	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
154244	936522PT	11,14	11,10	11,10	11,10	11,10	11,10	11,10	11,14	11,10	11,14
154244	936522PT	31,00	32,00	31,00	31,00	32,00	31,00	31,00	33,00	31,00	30,00

Char.No	Char.Descr.	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
154244	936522PT	11,10	11,14	11,10	11,14	11,10	11,14	11,10	11,10	11,14	11,14
154244	936522PT	30,00	30,00	30,00	31,00	31,00	31,00	31,00	31,00	32,00	32,00

Char.No	Char.Descr.	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
154244	936522PT	11,10	11,10	11,10	11,14	11,10	11,10	11,09	11,15	11,10	11,10
154244	936522PT	31,00	32,00	31,00	32,00	33,00	33,00	32,00	32,00	32,00	32,00

Char.No	Char.Descr.	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
154244	936522PT	11,10	11,14	11,10	11,06	11,10	11,14	11,06	11,09	11,15	11,10
154244	936522PT	31,00	32,00	31,00	31,00	32,00	31,00	32,00	32,00	30,00	31,00

Char.No	Char.Descr.	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
154244	936522PT	11,10	11,10	11,14	11,06	11,10	11,15	11,10	11,14	11,14	11,14
154244	936522PT	30,00	31,00	30,00	31,00	30,00	33,00	31,00	32,00	31,00	32,00

Char.No	Char.Descr.	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
154244	936522PT	11,14	11,06	11,14	11,10	11,14	11,14	11,09	11,14	11,14	11,14
154244	936522PT	32,00	31,00	33,00	32,00	31,00	33,00	34,00	31,00	31,00	31,00

Char.No	Char.Descr.	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
154244	936522PT	11,14	11,14	11,14	11,14	11,19	11,14	11,09	11,14	11,14	11,14
154244	936522PT	31,00	32,00	32,00	32,00	31,00	33,00	32,00	31,00	32,00	33,00

Char.No	Char.Descr.	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
154244	936522PT	11,19	11,19	11,14	11,19	11,14	11,14	11,19	11,19	11,19	11,14
154244	936522PT	31,00	30,00	30,00	31,00	31,00	32,00	32,00	30,00	31,00	32,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457h	Characteristic			
Type	17BPYPB13QL	Char.Descr.	936522PT	Inspection Val.	11,00
Ord. No.	17BPYPB13QL	Ser.No.	154244	LSL	10,23
				USL	11,77
Remark	Tq. 80% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.267 Nm/A				

Char.No	Char.Descr.	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
154244	936522PT	11,19	11,14	11,19	11,09	11,14	11,09	11,14	11,14	11,14	11,09
154244	936522PT	30,00	32,00	31,00	32,00	30,00	32,00	34,00	31,00	33,00	31,00

Char.No	Char.Descr.	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
154244	936522PT	11,14	11,14	11,06	11,14	11,09	11,14	11,19	11,14	11,14	11,14
154244	936522PT	32,00	31,00	31,00	31,00	32,00	30,00	32,00	32,00	31,00	31,00

Torque graphs

Model: **17BPYPB13QL**
Serial no: **737457**

Machine Capability Study 80 %

Angle degree: **30°**
Test torque: **11.0 Nm**



Value no. 1
Graph
Torque / Angle



Value no. 1
Graph
Torque / Time



Value no. 100
Graph
Torque / Angle



Value no. 100
Graph
Torque / Time

Machine Capability Study
Control System

Page 1 / 1

Plant ATG Westhausen		Operator Name Anton Czapla	Date 20.09.2017

Ord. No. 17BPYPB13QL	Part type 17BPYPB13QL				Contr.item yes
Serial No. 737457g	Char.Descr. VM1698-4	Inspection Val.	11,00	0,77	USL 11,77
	Serial No. 1024210	Unit	Nm	-0,77	LSL 10,23
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2

Cust.Name Homologation	Reference System VM1698-4	Test Electronic MPRO400SE
Contr.No. 816N2152	Reference Transducer 50 / 1024729	nges. 100

Evaluation from 20.09.2017 07:50:26 to 20.09.2017 08:28:01

Rem. Tq. 80% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.267 Nm/A





Drawing Values		Collected Values		Statistics	
T_m	11.00			$\bar{x}$	10.8852
LSL	10.23	x_{min}	10.84	$\bar{x}$-3s	10.8308
USL	11.77	x_{max}	10.94	$\bar{x}$+3s	10.9396
T	1.54	R	0.10	6s	0.1087
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			$M1_{1.4}$ $\hat{\sigma} = s_{tot}$
Potential Capability index	=	C_m	14.17
Critical capability index	=	C_{mk}	12.05

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457g	Characteristic			
Type	17BPYPB13QL	Char.Descr.	VM1698-4	Inspection Val.	11,00
Ord. No.	17BPYPB13QL	Ser.No.	1024210	LSL	10,23
				USL	11,77
Remark	Tq. 80% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.267 Nm/A				

Char.No	Char.Descr.	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
1024210	VM1698-4	10,87	10,88	10,88	10,90	10,89	10,89	10,93	10,89	10,87	10,86
1024210	VM1698-4	387,50	388,00	381,75	376,75	367,75	386,50	363,25	369,25	353,75	413,75

Char.No	Char.Descr.	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
1024210	VM1698-4	10,89	10,90	10,88	10,90	10,87	10,90	10,89	10,88	10,90	10,90
1024210	VM1698-4	384,25	357,50	360,00	358,25	364,75	340,00	363,75	369,00	365,25	368,50

Char.No	Char.Descr.	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
1024210	VM1698-4	10,87	10,89	10,88	10,91	10,89	10,88	10,86	10,89	10,87	10,94
1024210	VM1698-4	379,50	363,25	354,00	358,00	358,00	354,25	355,25	350,00	357,50	363,00

Char.No	Char.Descr.	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
1024210	VM1698-4	10,88	10,87	10,87	10,90	10,88	10,87	10,90	10,86	10,87	10,91
1024210	VM1698-4	348,25	353,00	363,25	355,00	356,50	379,75	352,75	352,00	332,50	373,75

Char.No	Char.Descr.	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
1024210	VM1698-4	10,88	10,88	10,90	10,89	10,89	10,85	10,86	10,92	10,88	10,88
1024210	VM1698-4	353,50	363,25	348,00	361,00	352,00	375,00	372,00	383,50	354,75	345,00

Char.No	Char.Descr.	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
1024210	VM1698-4	10,88	10,90	10,93	10,89	10,90	10,89	10,91	10,89	10,91	10,91
1024210	VM1698-4	379,50	356,25	348,75	345,50	352,25	350,50	347,75	356,25	354,50	371,25

Char.No	Char.Descr.	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
1024210	VM1698-4	10,89	10,85	10,87	10,90	10,88	10,86	10,84	10,87	10,86	10,88
1024210	VM1698-4	355,25	351,00	360,50	353,00	351,75	357,00	372,50	357,50	364,25	363,25

Char.No	Char.Descr.	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
1024210	VM1698-4	10,87	10,89	10,88	10,88	10,87	10,91	10,88	10,87	10,87	10,88
1024210	VM1698-4	355,00	356,50	361,00	358,25	357,75	356,25	349,00	366,00	364,50	362,25

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457g	Characteristic			
Type	17BPYPB13QL	Char.Descr.	VM1698-4	Inspection Val.	11,00
Ord. No.	17BPYPB13QL	Ser.No.	1024210	LSL	10,23
				USL	11,77
Remark	Tq. 80% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.267 Nm/A				

Char.No	Char.Descr.	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
1024210	VM1698-4	10,89	10,89	10,89	10,92	10,90	10,89	10,86	10,88	10,86	10,88
1024210	VM1698-4	368,75	341,00	343,25	379,75	380,00	362,25	338,50	357,50	345,75	379,75

Char.No	Char.Descr.	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
1024210	VM1698-4	10,88	10,87	10,86	10,89	10,87	10,89	10,91	10,89	10,91	10,89
1024210	VM1698-4	360,25	350,75	375,25	361,00	364,00	375,25	373,75	377,50	372,75	384,25

Machine Capability Study
Tool System

Page 1 / 1

Plant ATG Westhausen		Operator Name Anton Czapla	Date 20.09.2017

Ord. No. 17BPYPB13QL	Part type 17BPYPB13QL				Contr.item yes
Serial No. 737457g	Char.Descr. 936522PT	Inspection Val.	11,00	0,77	USL 11,77
	Serial No. 154244	Unit	Nm	-0,77	LSL 10,23
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2

Cust.Name Homologation	Reference System VM1698-4	Test Electronic MPRO400SE
Contr.No. 816N2152	Reference Transducer 50 / 1024729	nges. 100

Evaluation from 20.09.2017 07:50:30 to 20.09.2017 08:28:05

Rem. Tq. 80% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.267 Nm/A





Drawing Values		Collected Values		Statistics	
T_m	11.00			$\bar{x}$	11.0291
LSL	10.23	x_{min}	11.01	$\bar{x}$-3s	10.9846
USL	11.77	x_{max}	11.06	$\bar{x}$+3s	11.0736
T	1.54	R	0.05	6s	0.0891
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			$M1_{1.4}$ $\hat{\sigma} = s_{tot}$
Potential Capability index	=	C_m	17.29
Critical capability index	=	C_{mk}	16.64

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\AppData\QW\QWE\MessWert\2017\737457g1.DFD

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457g	Characteristic			
Type	17BPYPB13QL	Char.Descr.	936522PT	Inspection Val.	11,00
Ord. No.	17BPYPB13QL	Ser.No.	154244	LSL	10,23
				USL	11,77
Remark	Tq. 80% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.267 Nm/A				

Char.No	Char.Descr.	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
154244	936522PT	11,04	11,04	11,04	11,01	11,04	11,04	11,04	11,04	11,04	11,04
154244	936522PT	389,00	389,00	384,00	379,00	369,00	387,00	365,00	371,00	356,00	417,00

Char.No	Char.Descr.	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
154244	936522PT	11,01	11,04	11,01	11,04	11,04	11,04	11,04	11,04	11,04	11,04
154244	936522PT	387,00	359,00	360,00	360,00	364,00	340,00	365,00	371,00	367,00	370,00

Char.No	Char.Descr.	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
154244	936522PT	11,04	11,04	11,04	11,04	11,04	11,04	11,04	11,04	11,04	11,04
154244	936522PT	381,00	366,00	356,00	360,00	360,00	356,00	356,00	353,00	359,00	365,00

Char.No	Char.Descr.	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
154244	936522PT	11,04	11,04	11,04	11,04	11,04	11,04	11,04	11,04	11,04	11,04
154244	936522PT	349,00	355,00	366,00	357,00	358,00	382,00	355,00	354,00	334,00	373,00

Char.No	Char.Descr.	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
154244	936522PT	11,04	11,04	11,01	11,01	11,01	11,01	11,01	11,04	11,04	11,04
154244	936522PT	355,00	364,00	349,00	362,00	355,00	377,00	374,00	384,00	357,00	346,00

Char.No	Char.Descr.	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
154244	936522PT	11,06	11,01	11,04	11,04	11,04	11,04	11,04	11,04	11,04	11,01
154244	936522PT	380,00	358,00	353,00	347,00	356,00	354,00	348,00	358,00	355,00	372,00

Char.No	Char.Descr.	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
154244	936522PT	11,01	11,04	11,01	11,01	11,01	11,04	11,04	11,04	11,01	11,04
154244	936522PT	356,00	353,00	362,00	355,00	353,00	360,00	373,00	359,00	366,00	365,00

Char.No	Char.Descr.	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
154244	936522PT	11,01	11,04	11,04	11,01	11,01	11,04	11,01	11,01	11,01	11,04
154244	936522PT	358,00	357,00	363,00	360,00	360,00	358,00	351,00	367,00	366,00	364,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457g	Characteristic			
Type	17BPYPB13QL	Char.Descr.	936522PT	Inspection Val.	11,00
Ord. No.	17BPYPB13QL	Ser.No.	154244	LSL	10,23
				USL	11,77
Remark	Tq. 80% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.267 Nm/A				

Char.No	Char.Descr.	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
154244	936522PT	11,04	11,01	11,01	11,01	11,01	11,04	11,01	11,01	11,01	11,01
154244	936522PT	370,00	342,00	344,00	382,00	382,00	364,00	342,00	359,00	347,00	380,00

Char.No	Char.Descr.	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
154244	936522PT	11,04	11,01	11,01	11,01	11,01	11,01	11,01	11,01	11,04	11,01
154244	936522PT	361,00	354,00	377,00	363,00	365,00	377,00	376,00	380,00	375,00	387,00

Torque graphs

Model: **17BPYPB13QL**
Serial no: **737457**

Machine Capability Study 80 %
Angle degree: **360°**
Test torque: **11.0 Nm**



Value no. 1
Graph
Torque / Angle



Value no. 1
Graph
Torque / Time



Value no. 100
Graph
Torque / Angle



Value no. 100
Graph
Torque / Time

Investigation no.: 010/2017
Date: 25.09.2017

Test sheet no. 4

Machine Capability Study 100 %

Multi-stage tightening system	☑	Speed 50 rpm	5.4 %
Single-stage tightening system	☐	Speed 100 %	629 rpm

Manufacturer: Apex Tool Group GmbH Serial no: **737457**

Test torque: Tq max. 13.00 Nm with 26 volt battery

Hard joint (H)	78.31 Nm / Revolution	Angle degree	30°
Soft joint (L)	6.42 Nm / Revolution	Angle degree	360°

		H	L
a)	Tolerance down / up	12.09 - 13.91 Nm	12.09 - 13.91 Nm
	Tolerance down / up	7 %	7 %
	Average torque	13.05 Nm	12.84 Nm
	Standard deviation	0.07 Nm	0.03 Nm
	Torque scatter (99,73%)	0.43 Nm	0.18 Nm
	C_m	4.25	10.28
	C_{mk}	4.01	8.47

b)	Min. C_m hard/soft (lowest value)	4.25
	Min. C_{mk} hard/soft (lowest value)	4.01

Capability is reached if minimum C_{mk} value ≥1.67

Note:

Machine Capability Study
Control System

Page 1 / 1

Plant ATG Westhausen		Operator Name Anton Czapla	Date 20.09.2017

Ord. No. 17BPYPB13QL	Part type 17BPYPB13QL				Contr.item yes
Serial No. 737457b	Char.Descr. VM1698-4	Inspection Val.	13,00	0,91	USL 13,91
	Serial No. 1024210	Unit	Nm	-0,91	LSL 12,09
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2

Cust.Name Homologation	Reference System VM1698-4	Test Electronic MPRO400SE
Contr.No. 816N2152	Reference Transducer 50 / 1024729	nges. 100

Evaluation from 20.09.2017 07:05:49 to 20.09.2017 07:22:35

Rem. Tq. 100% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.269 Nm/A





Drawing Values		Collected Values		Statistics	
T_m	13.00			$\bar{x}$	13.0517
LSL	12.09	x_{min}	12.93	$\bar{x}$-3s	12.8376
USL	13.91	x_{max}	13.29	$\bar{x}$+3s	13.2658
T	1.82	R	0.36	6s	0.4282
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1 1.4 $\hat{\sigma} = s_{tot}$
Potential Capability index	=	C_m	4.25
Critical capability index	=	C_{mk}	4.01

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457b	Characteristic			
Type	17BPYPB13QL	Char.Descr.	VM1698-4	Inspection Val.	13,00
Ord. No.	17BPYPB13QL	Ser.No.	1024210	LSL	12,09
				USL	13,91
Remark	Tq. 100% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.269 Nm/A				

Char.No	Char.Descr.	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
1024210	VM1698-4	13,23	13,23	13,24	13,22	13,19	13,13	13,19	13,29	13,11	13,15
1024210	VM1698-4	30,50	30,50	29,25	29,25	29,00	29,25	30,50	30,75	29,50	29,00

Char.No	Char.Descr.	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
1024210	VM1698-4	13,17	13,13	13,15	13,16	13,12	13,15	13,12	13,10	13,10	13,08
1024210	VM1698-4	30,00	30,50	29,75	30,25	28,50	30,25	28,75	31,00	29,50	31,00

Char.No	Char.Descr.	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
1024210	VM1698-4	13,06	13,09	13,04	13,10	13,05	13,08	13,06	13,11	13,09	13,05
1024210	VM1698-4	29,25	30,25	29,25	30,75	30,50	31,00	30,50	30,75	31,00	28,75

Char.No	Char.Descr.	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
1024210	VM1698-4	13,11	13,10	13,14	13,08	13,07	13,01	13,01	13,03	13,05	13,03
1024210	VM1698-4	30,00	28,75	30,50	30,00	29,25	29,50	29,75	29,75	30,00	29,25

Char.No	Char.Descr.	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
1024210	VM1698-4	13,07	13,02	13,03	13,03	13,01	12,98	12,97	13,04	13,01	13,04
1024210	VM1698-4	30,25	29,50	29,75	30,50	29,25	29,00	29,25	29,75	29,25	30,25

Char.No	Char.Descr.	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
1024210	VM1698-4	13,03	13,03	12,97	13,03	13,05	13,01	13,05	13,01	13,04	13,00
1024210	VM1698-4	29,25	30,50	29,00	29,25	30,25	29,25	31,00	29,25	30,50	29,25

Char.No	Char.Descr.	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
1024210	VM1698-4	13,01	13,05	12,99	13,01	13,00	13,03	12,97	13,05	13,05	12,99
1024210	VM1698-4	30,50	30,00	30,25	29,50	30,50	30,75	29,25	30,75	30,50	29,50

Char.No	Char.Descr.	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
1024210	VM1698-4	13,05	12,98	12,97	13,03	12,99	13,04	12,97	13,01	13,05	13,00
1024210	VM1698-4	30,75	30,00	29,75	30,75	29,50	29,50	29,75	30,25	30,75	29,75

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457b	Characteristic			
Type	17BPYPB13QL	Char.Descr.	VM1698-4	Inspection Val.	13,00
Ord. No.	17BPYPB13QL	Ser.No.	1024210	LSL	12,09
				USL	13,91
Remark	Tq. 100% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.269 Nm/A				

Char.No	Char.Descr.	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
1024210	VM1698-4	13,05	12,97	13,03	13,01	12,99	13,04	13,01	13,04	13,02	12,99
1024210	VM1698-4	29,25	30,25	29,75	29,25	30,25	30,75	30,25	29,50	30,00	30,50

Char.No	Char.Descr.	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
1024210	VM1698-4	12,97	13,03	13,01	12,95	12,97	12,96	12,96	12,98	12,98	12,93
1024210	VM1698-4	30,00	30,50	30,75	30,25	29,50	29,25	30,25	30,75	30,50	30,50

Machine Capability Study
Tool System

Page 1 / 1

Plant ATG Westhausen		Operator Name Anton Czapla	Date 20.09.2017

Ord. No. 17BPYPB13QL	Part type 17BPYPB13QL				Contr.item yes
Serial No. 737457b	Char.Descr. 936522PT	Inspection Val.	13,00	0,91	USL 13,91
	Serial No. 154244	Unit	Nm	-0,91	LSL 12,09
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2

Cust.Name Homologation	Reference System VM1698-4	Test Electronic MPRO400SE
Contr.No. 816N2152	Reference Transducer 50 / 1024729	nges. 100

Evaluation from 20.09.2017 07:05:52 to 20.09.2017 07:22:39

Rem. Tq. 100% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.269 Nm/A





Drawing Values		Collected Values		Statistics	
T_m	13.00			$\bar{x}$	13.1499
LSL	12.09	x_{min}	13.07	$\bar{x}$-3s	13.0669
USL	13.91	x_{max}	13.22	$\bar{x}$+3s	13.2329
T	1.82	R	0.15	6s	0.1659
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			$M1_{1.4}$ $\hat{\sigma} = s_{tot}$
Potential Capability index	=	C_m	10.97
Critical capability index	=	C_{mk}	9.16

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\AppData\QW\QWE\MessWert\2017\737457b1.DFD

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457b	Characteristic			
Type	17BPYPB13QL	Char.Descr.	936522PT	Inspection Val.	13,00
Ord. No.	17BPYPB13QL	Ser.No.	154244	LSL	12,09
				USL	13,91
Remark	Tq. 100% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.269 Nm/A				

Char.No	Char.Descr.	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
154244	936522PT	13,07	13,17	13,17	13,12	13,17	13,16	13,16	13,17	13,11	13,11
154244	936522PT	32,00	32,00	31,00	31,00	31,00	31,00	32,00	32,00	31,00	31,00

Char.No	Char.Descr.	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
154244	936522PT	13,16	13,11	13,16	13,17	13,16	13,16	13,16	13,17	13,17	13,12
154244	936522PT	32,00	32,00	31,00	32,00	30,00	32,00	30,00	33,00	31,00	33,00

Char.No	Char.Descr.	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
154244	936522PT	13,12	13,17	13,12	13,17	13,12	13,17	13,12	13,17	13,12	13,17
154244	936522PT	31,00	32,00	31,00	32,00	32,00	32,00	33,00	32,00	33,00	30,00

Char.No	Char.Descr.	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
154244	936522PT	13,17	13,17	13,17	13,16	13,16	13,11	13,11	13,11	13,21	13,11
154244	936522PT	32,00	30,00	32,00	32,00	31,00	31,00	31,00	32,00	31,00	31,00

Char.No	Char.Descr.	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
154244	936522PT	13,16	13,16	13,16	13,16	13,11	13,16	13,11	13,16	13,17	13,11
154244	936522PT	32,00	31,00	32,00	32,00	31,00	31,00	31,00	32,00	30,00	32,00

Char.No	Char.Descr.	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
154244	936522PT	13,16	13,17	13,11	13,12	13,17	13,12	13,16	13,16	13,17	13,17
154244	936522PT	31,00	32,00	31,00	31,00	32,00	31,00	33,00	31,00	32,00	31,00

Char.No	Char.Descr.	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
154244	936522PT	13,22	13,17	13,12	13,17	13,12	13,12	13,12	13,17	13,17	13,12
154244	936522PT	32,00	32,00	32,00	31,00	32,00	32,00	31,00	32,00	32,00	31,00

Char.No	Char.Descr.	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
154244	936522PT	13,17	13,12	13,12	13,17	13,12	13,17	13,17	13,12	13,17	13,12
154244	936522PT	32,00	32,00	31,00	32,00	31,00	31,00	32,00	33,00	32,00	32,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457b	Characteristic			
Type	17BPYPB13QL	Char.Descr.	936522PT	Inspection Val.	13,00
Ord. No.	17BPYPB13QL	Ser.No.	154244	LSL	12,09
				USL	13,91
Remark	Tq. 100% hard * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.269 Nm/A				

Char.No	Char.Descr.	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
154244	936522PT	13,17	13,12	13,17	13,17	13,17	13,17	13,17	13,17	13,17	13,12
154244	936522PT	31,00	32,00	31,00	31,00	32,00	32,00	32,00	31,00	32,00	32,00

Char.No	Char.Descr.	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
154244	936522PT	13,17	13,17	13,17	13,12	13,16	13,16	13,11	13,21	13,16	13,16
154244	936522PT	32,00	32,00	32,00	32,00	31,00	31,00	32,00	32,00	32,00	32,00

Torque graphs

Machine Capability Study 100 %

Model: **17BPYPB13QL**
Serial no: **737457**

Angle degree: **30°**
Test torque: **13.0 Nm**



Value no. 1
Graph
Torque / Angle



Value no. 1
Graph
Torque / Time



Value no. 100
Graph
Torque / Angle



Value no. 100
Graph
Torque / Time

Machine Capability Study
Control System

Page 1 / 1

Plant ATG Westhausen		Operator Name Anton Czapla	Date 19.09.2017

Ord. No. 17BPYPB13QL	Part type 17BPYPB13QL				Contr.item yes
Serial No. 737457a	Char.Descr. VM1698-4	Inspection Val.	13,00	0,91	USL 13,91
	Serial No. 1024210	Unit	Nm	-0,91	LSL 12,09
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2

Cust.Name Homologation	Reference System VM1698-4	Test Electronic MPRO400SE
Contr.No. 816N2152	Reference Transducer 50 / 1024729	nges. 100

Evaluation from 19.09.2017 15:56:31 to 19.09.2017 16:58:16

Rem. Tq. 100% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.269 Nm/A





Drawing Values		Collected Values		Statistics	
T_m	13.00			$\bar{x}$	12.8398
LSL	12.09	x_{min}	12.78	$\bar{x}$-3s	12.7513
USL	13.91	x_{max}	12.92	$\bar{x}$+3s	12.9283
T	1.82	R	0.14	6s	0.1770
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			$M1_{1.4}$ $\hat{\sigma} = s_{tot}$
Potential Capability index	=	C_m	10.28
Critical capability index	=	C_{mk}	8.47

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 19.09.2017

Ser.No.	737457a	Characteristic			
Type	17BPYPB13QL	Char.Descr.	VM1698-4	Inspection Val.	13,00
Ord. No.	17BPYPB13QL	Ser.No.	1024210	LSL	12,09
				USL	13,91
Remark	Tq. 100% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.269 Nm/A				

Char.No	Char.Descr.	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
1024210	VM1698-4	12,92	12,88	12,92	12,90	12,85	12,90	12,92	12,86	12,87	12,87
1024210	VM1698-4	363,50	342,25	369,00	343,75	335,50	349,00	347,00	357,00	344,75	339,50

Char.No	Char.Descr.	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
1024210	VM1698-4	12,90	12,85	12,90	12,86	12,87	12,91	12,85	12,83	12,81	12,85
1024210	VM1698-4	357,00	339,75	366,75	332,75	356,00	344,25	356,25	342,50	355,50	370,75

Char.No	Char.Descr.	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
1024210	VM1698-4	12,82	12,82	12,86	12,83	12,86	12,83	12,84	12,81	12,85	12,87
1024210	VM1698-4	356,25	357,00	369,50	349,25	366,00	348,50	350,75	350,50	373,00	366,75

Char.No	Char.Descr.	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
1024210	VM1698-4	12,84	12,84	12,84	12,83	12,83	12,83	12,86	12,84	12,81	12,85
1024210	VM1698-4	373,75	358,50	366,25	371,00	358,25	346,00	358,25	358,50	379,00	358,75

Char.No	Char.Descr.	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
1024210	VM1698-4	12,82	12,81	12,82	12,87	12,83	12,84	12,83	12,83	12,80	12,86
1024210	VM1698-4	363,75	349,00	359,25	349,00	362,75	349,50	358,75	345,25	358,50	381,75

Char.No	Char.Descr.	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
1024210	VM1698-4	12,85	12,84	12,82	12,86	12,82	12,85	12,82	12,81	12,81	12,85
1024210	VM1698-4	363,00	358,00	360,50	365,75	360,50	374,75	374,50	357,00	369,50	375,00

Char.No	Char.Descr.	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
1024210	VM1698-4	12,84	12,83	12,86	12,81	12,83	12,83	12,80	12,79	12,82	12,82
1024210	VM1698-4	354,50	363,75	379,50	360,75	378,75	363,75	348,25	341,75	351,25	342,50

Char.No	Char.Descr.	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
1024210	VM1698-4	12,85	12,82	12,80	12,84	12,83	12,80	12,80	12,82	12,85	12,87
1024210	VM1698-4	373,00	370,00	373,25	377,50	358,25	350,00	375,75	352,00	355,25	393,50

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 19.09.2017

Ser.No.	737457a	Characteristic			
Type	17BPYPB13QL	Char.Descr.	VM1698-4	Inspection Val.	13,00
Ord. No.	17BPYPB13QL	Ser.No.	1024210	LSL	12,09
				USL	13,91
Remark	Tq. 100% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.269 Nm/A				

Char.No	Char.Descr.	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
1024210	VM1698-4	12,82	12,85	12,82	12,80	12,81	12,85	12,80	12,82	12,86	12,82
1024210	VM1698-4	351,00	358,75	355,75	359,25	352,00	356,25	352,25	353,50	376,75	344,50

Char.No	Char.Descr.	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
1024210	VM1698-4	12,78	12,80	12,82	12,84	12,86	12,82	12,86	12,86	12,84	12,82
1024210	VM1698-4	352,75	335,00	368,00	350,25	353,75	358,00	371,75	377,00	378,75	365,75

Machine Capability Study
Tool System

Page 1 / 1

Plant ATG Westhausen		Operator Name Anton Czapla	Date 19.09.2017

Ord. No. 17BPYPB13QL	Part type 17BPYPB13QL				Contr.item yes
Serial No. 737457a	Char.Descr. 936522PT	Inspection Val.	13,00	0,91	USL 13,91
	Serial No. 154244	Unit	Nm	-0,91	LSL 12,09
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2

Cust.Name Homologation	Reference System VM1698-4	Test Electronic MPRO400SE
Contr.No. 816N2152	Reference Transducer 50 / 1024729	nges. 100

Evaluation from 19.09.2017 15:56:35 to 19.09.2017 16:58:20

Rem. Tq. 100% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.269 Nm/A





Drawing Values		Collected Values		Statistics	
T_m	13.00			$\bar{x}$	13.0163
LSL	12.09	x_{min}	13.01	$\bar{x}$-3s	12.9778
USL	13.91	x_{max}	13.07	$\bar{x}$+3s	13.0548
T	1.82	R	0.06	6s	0.0771
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			$M1_{1.4}$ $\hat{\sigma} = s_{tot}$
Potential Capability index	=	C_m	23.62
Critical capability index	=	C_{mk}	23.19

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 19.09.2017

Ser.No.	737457a	Characteristic			
Type	17BPYPB13QL	Char.Descr.	936522PT	Inspection Val.	13,00
Ord. No.	17BPYPB13QL	Ser.No.	154244	LSL	12,09
				USL	13,91
Remark	Tq. 100% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.269 Nm/A				

Char.No	Char.Descr.	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
154244	936522PT	13,01	13,01	13,01	13,01	13,01	13,01	13,02	13,02	13,02	13,02
154244	936522PT	368,00	345,00	375,00	346,00	339,00	351,00	349,00	359,00	349,00	341,00

Char.No	Char.Descr.	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
154244	936522PT	13,02	13,02	13,02	13,02	13,02	13,02	13,01	13,01	13,01	13,01
154244	936522PT	358,00	341,00	368,00	334,00	358,00	346,00	360,00	347,00	360,00	376,00

Char.No	Char.Descr.	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
154244	936522PT	13,01	13,01	13,01	13,01	13,01	13,01	13,01	13,01	13,01	13,01
154244	936522PT	362,00	360,00	376,00	353,00	370,00	351,00	357,00	356,00	378,00	371,00

Char.No	Char.Descr.	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
154244	936522PT	13,01	13,01	13,01	13,01	13,01	13,01	13,01	13,02	13,02	13,06
154244	936522PT	379,00	367,00	371,00	379,00	362,00	351,00	363,00	364,00	384,00	364,00

Char.No	Char.Descr.	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
154244	936522PT	13,01	13,01	13,01	13,02	13,01	13,01	13,06	13,01	13,02	13,02
154244	936522PT	370,00	356,00	365,00	354,00	367,00	354,00	365,00	350,00	364,00	387,00

Char.No	Char.Descr.	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
154244	936522PT	13,02	13,01	13,01	13,02	13,02	13,01	13,01	13,01	13,01	13,02
154244	936522PT	368,00	361,00	365,00	370,00	367,00	380,00	380,00	361,00	376,00	378,00

Char.No	Char.Descr.	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
154244	936522PT	13,02	13,01	13,01	13,02	13,01	13,01	13,01	13,01	13,01	13,01
154244	936522PT	359,00	368,00	384,00	365,00	383,00	369,00	354,00	346,00	356,00	346,00

Char.No	Char.Descr.	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
154244	936522PT	13,07	13,01	13,01	13,07	13,01	13,02	13,01	13,01	13,01	13,06
154244	936522PT	381,00	376,00	377,00	383,00	367,00	355,00	381,00	359,00	359,00	399,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 19.09.2017

Ser.No.	737457a	Characteristic			
Type	17BPYPB13QL	Char.Descr.	936522PT	Inspection Val.	13,00
Ord. No.	17BPYPB13QL	Ser.No.	154244	LSL	12,09
				USL	13,91
Remark	Tq. 100% soft * +/-7% * Tq-Cal.: 17.75 Nm * Cur.-Cal.: 0.269 Nm/A				

Char.No	Char.Descr.	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
154244	936522PT	13,01	13,01	13,01	13,01	13,02	13,02	13,01	13,02	13,02	13,02
154244	936522PT	357,00	361,00	361,00	367,00	359,00	361,00	357,00	359,00	381,00	353,00

Char.No	Char.Descr.	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
154244	936522PT	13,02	13,02	13,06	13,01	13,01	13,01	13,02	13,01	13,01	13,02
154244	936522PT	357,00	340,00	371,00	358,00	358,00	362,00	378,00	381,00	386,00	373,00

Torque graphs

Model: **17BPYPB13QL**
Serial no: **737457**

Machine Capability Study 100 %
Angle degree: **360°**
Test torque: **13.0 Nm**



Value no. 1
Graph
Torque / Angle



Value no. 1
Graph
Torque / Time



Value no. 100
Graph
Torque / Angle



Value no. 100
Graph
Torque / Time

Investigation no.: 010/2017
Date: 25.09.2017

General Specifications

Manufacturer: Apex Tool Group GmbH **Tool type:** LiveWire Tool

Model: 17BPYPB13QL **Serial no:** 737457

Torque range: **3 Nm to 13 Nm**

Difference evaluation: Reference/Tool at 40° / 60 %

Capability examination

Snugfit value: 2.6 Nm **Torque tolerance ±** 7 %

Target torque: 7.8 Nm Tolerance: 3.28 % ± **1.64 %**

Angle degree: 40° Tolerance: 2.4° ± **1.2°**

Formula derivation: $C_m = \frac{T}{6\,s}$ $T = C_m * 6\,s$

Tool without angle correction

Measurement	Tool data		Control data		Difference	
No.	Torque	Angle	Torque	Angle	Torque	Angle
1	7.84	40.00	7.72	38.75	0.12	1.25
2	7.89	40.00	7.73	38.50	0.16	1.50
3	7.89	40.00	7.78	38.50	0.11	1.50
4	7.84	40.00	7.73	38.75	0.11	1.25
5	7.89	40.00	7.74	38.75	0.15	1.25
6	7.93	40.00	7.80	38.75	0.13	1.25
7	7.89	40.00	7.80	38.75	0.09	1.25
8	7.89	40.00	7.77	39.00	0.12	1.00
9	7.89	40.00	7.81	38.75	0.08	1.25
10	7.93	40.00	7.77	38.75	0.16	1.25
11	7.89	40.00	7.80	38.75	0.09	1.25
12	7.89	40.00	7.79	39.00	0.10	1.00
13	7.89	40.00	7.77	38.50	0.12	1.50
14	7.89	40.00	7.78	38.75	0.11	1.25
15	7.89	40.00	7.71	38.75	0.18	1.25
16	7.89	40.00	7.77	38.75	0.12	1.25
17	7.89	40.00	7.77	38.50	0.12	1.50
18	7.98	40.00	7.94	39.00	0.04	1.00
19	7.84	40.00	7.76	38.75	0.08	1.25
20	7.89	40.00	7.74	38.75	0.15	1.25
21	7.89	40.00	7.77	38.75	0.12	1.25
22	7.98	40.00	7.86	39.25	0.12	0.75
23	7.89	40.00	7.77	38.50	0.12	1.50
24	7.89	40.00	7.79	38.75	0.10	1.25
25	7.89	40.00	7.82	38.75	0.07	1.25
26	7.93	40.00	7.83	38.75	0.10	1.25
27	7.84	40.00	7.74	38.75	0.10	1.25
28	7.84	40.00	7.68	38.25	0.16	1.75
29	7.89	40.00	7.72	38.75	0.17	1.25
30	7.84	40.00	7.74	38.50	0.10	1.50
31	7.89	40.00	7.80	38.75	0.09	1.25
32	7.93	40.00	7.86	39.25	0.07	0.75
33	7.98	40.00	7.85	39.00	0.13	1.00
34	7.79	40.00	7.73	38.50	0.06	1.50
35	7.93	40.00	7.84	39.50	0.09	0.50
36	7.89	40.00	7.80	39.00	0.09	1.00
37	7.89	40.00	7.77	38.75	0.12	1.25
38	7.84	40.00	7.76	38.75	0.08	1.25
39	7.89	40.00	7.78	38.50	0.11	1.50
40	7.93	40.00	7.83	39.25	0.10	0.75
41	7.89	40.00	7.80	39.00	0.09	1.00
42	7.89	40.00	7.79	38.75	0.10	1.25
43	7.89	40.00	7.78	38.75	0.11	1.25
44	7.89	40.00	7.81	39.25	0.08	0.75
45	7.84	40.00	7.73	38.50	0.11	1.50
46	7.84	40.00	7.71	38.75	0.13	1.25
47	7.84	40.00	7.70	38.25	0.14	1.75
48	7.84	40.00	7.70	38.75	0.14	1.25
49	7.93	40.00	7.78	39.00	0.15	1.00
50	7.84	40.00	7.75	38.75	0.09	1.25
51	7.93	40.00	7.80	39.00	0.13	1.00
52	7.89	40.00	7.77	39.25	0.12	0.75
53	7.89	40.00	7.78	38.75	0.11	1.25
54	7.93	40.00	7.85	38.75	0.08	1.25
55	7.89	40.00	7.77	38.75	0.12	1.25
56	7.93	40.00	7.80	39.00	0.13	1.00
57	7.84	40.00	7.72	38.75	0.12	1.25
58	7.84	40.00	7.73	38.25	0.11	1.75
59	7.84	40.00	7.72	38.25	0.12	1.75
60	7.89	40.00	7.78	39.00	0.11	1.00
61	7.89	40.00	7.82	38.75	0.07	1.25
62	7.89	40.00	7.79	39.00	0.10	1.00
63	7.84	40.00	7.73	39.00	0.11	1.00
64	7.89	40.00	7.79	38.75	0.10	1.25
65	7.89	40.00	7.80	38.75	0.09	1.25
66	7.84	40.00	7.72	38.25	0.12	1.75
67	7.84	40.00	7.72	38.75	0.12	1.25
68	7.89	40.00	7.75	39.00	0.14	1.00
69	7.89	40.00	7.76	39.00	0.13	1.00
70	7.84	40.00	7.74	38.50	0.10	1.50
71	7.84	40.00	7.74	38.75	0.10	1.25
72	7.89	40.00	7.77	38.75	0.12	1.25
73	7.89	40.00	7.74	38.75	0.15	1.25
74	7.89	40.00	7.74	38.75	0.15	1.25
75	7.79	40.00	7.67	38.50	0.12	1.50
76	7.84	40.00	7.72	39.00	0.12	1.00
77	7.84	40.00	7.75	39.00	0.09	1.00
78	7.89	40.00	7.81	39.25	0.08	0.75
79	7.84	40.00	7.71	38.75	0.13	1.25
80	7.84	40.00	7.71	38.50	0.13	1.50
81	7.89	40.00	7.78	39.00	0.11	1.00
82	7.89	40.00	7.79	39.25	0.10	0.75
83	7.84	40.00	7.71	38.75	0.13	1.25
84	7.79	40.00	7.64	38.50	0.15	1.50
85	7.91	40.00	7.77	39.00	0.14	1.00
86	7.89	40.00	7.80	39.00	0.09	1.00
87	7.89	40.00	7.79	39.00	0.10	1.00
88	7.84	40.00	7.76	39.00	0.08	1.00
89	7.89	40.00	7.80	38.75	0.09	1.25
90	7.84	40.00	7.75	38.75	0.09	1.25
91	7.79	40.00	7.69	38.75	0.10	1.25
92	7.89	40.00	7.78	39.00	0.11	1.00
93	7.84	40.00	7.76	38.75	0.08	1.25
94	7.84	40.00	7.72	39.00	0.12	1.00
95	7.84	40.00	7.72	38.75	0.12	1.25
96	7.79	40.00	7.70	38.75	0.09	1.25
97	7.89	40.00	7.79	38.75	0.10	1.25
98	7.79	40.00	7.72	38.75	0.07	1.25
99	7.84	40.00	7.77	39.00	0.07	1.00
100	7.89	40.00	7.76	38.50	0.13	1.50
				Standard deviation:	**0.026**	**0.241**

Graphical representation

Model:	**17BPYPB13QL**	Serial no:	**737457**
Target torque:	**7.8 Nm**	60 % of max. torque	
Angle degree:	**40°**	Tool without angle correction	





Machine Capability Study
Control System

Cleco Production Tools

Plant	ATG Westhausen	Operator Name	Anton Czapla
Date	20.09.2017		

Ord. No.	17BPYPB13QL	Part type	17BPYPB13QL	Contr.item	yes
Serial No.	737457k	Char.Descr.	VM1698-4	Inspection Val. 40,00 5,00	USL 45,00
		Serial No.	1024210	Unit Grad -5,00	LSL 35,00
Char.Type	variable			Tolerance value 12 %	Decimal Pl. 2
Cust.Name	Homologation	Reference System	VM1698-4	Test Electronic	MPRO400SE
Contr.No.	816N2152	Reference Transducer	10 / 1029292	nges.	100

Evaluation from 20.09.2017 15:02:12 to 20.09.2017 15:15:57

Rem. Tq. 60% Angle 40° * +/-5° * Tq-Cal.: 17.65 Nm * Cur.-Cal.: 0.264 Nm/A





Drawing Values		Collected Values		Statistics	
T_m	40.00			$\bar{x}$	38.7925
LSL	35.00	x_{min}	38.25	$\bar{x}$-3s	38.0691
USL	45.00	x_{max}	39.50	$\bar{x}$+3s	39.5159
T	10.00	R	1.25	6s	1.4469
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			$M1_{1.4}$ $\hat{\sigma} = s_{tot}$
Potential Capability index	=	C_m	6.91
Critical capability index	=	C_{mk}	5.24

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457k	Characteristic			
Type	17BPYPB13QL	Char.Descr.	VM1698-4	Inspection Val.	7,90
Ord. No.	17BPYPB13QL	Ser.No.	1024210	LSL	6,12
				USL	9,79
Remark	Tq. 60% Angle 40° * +/-5°* Tq-Cal.: 17.65 N m * Cur.-Cal.: 0.264 Nm/A				

Char.No	Char.Descr.	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
1024210	VM1698-4	7,72	7,73	7,78	7,73	7,74	7,80	7,80	7,77	7,81	7,77
1024210	VM1698-4	38,75	38,50	38,50	38,75	38,75	38,75	38,75	39,00	38,75	38,75

Char.No	Char.Descr.	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
1024210	VM1698-4	7,80	7,79	7,77	7,78	7,71	7,77	7,77	7,94	7,76	7,74
1024210	VM1698-4	38,75	39,00	38,50	38,75	38,75	38,75	38,50	39,00	38,75	38,75

Char.No	Char.Descr.	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
1024210	VM1698-4	7,77	7,86	7,77	7,79	7,82	7,83	7,74	7,68	7,72	7,74
1024210	VM1698-4	38,75	39,25	38,50	38,75	38,75	38,75	38,75	38,25	38,75	38,50

Char.No	Char.Descr.	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
1024210	VM1698-4	7,80	7,86	7,85	7,73	7,84	7,80	7,77	7,76	7,78	7,83
1024210	VM1698-4	38,75	39,25	39,00	38,50	39,50	39,00	38,75	38,75	38,50	39,25

Char.No	Char.Descr.	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
1024210	VM1698-4	7,80	7,79	7,78	7,81	7,73	7,71	7,70	7,70	7,78	7,75
1024210	VM1698-4	39,00	38,75	38,75	39,25	38,50	38,75	38,25	38,75	39,00	38,75

Char.No	Char.Descr.	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
1024210	VM1698-4	7,80	7,77	7,78	7,85	7,77	7,80	7,72	7,73	7,72	7,78
1024210	VM1698-4	39,00	39,25	38,75	38,75	38,75	39,00	38,75	38,25	38,25	39,00

Char.No	Char.Descr.	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
1024210	VM1698-4	7,82	7,79	7,73	7,79	7,80	7,72	7,72	7,75	7,76	7,74
1024210	VM1698-4	38,75	39,00	39,00	38,75	38,75	38,25	38,75	39,00	39,00	38,50

Char.No	Char.Descr.	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
1024210	VM1698-4	7,74	7,77	7,74	7,74	7,67	7,72	7,75	7,81	7,71	7,71
1024210	VM1698-4	38,75	38,75	38,75	38,75	38,50	39,00	39,00	39,25	38,75	38,50

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457k	Characteristic			
Type	17BPYPB13QL	Char.Descr.	VM1698-4	Inspection Val.	7,90
Ord. No.	17BPYPB13QL	Ser.No.	1024210	LSL	6,12
				USL	9,79
Remark	Tq. 60% Angle 40° * +/-5°* Tq-Cal.: 17.65 N m * Cur.-Cal.: 0.264 Nm/A				

Char.No	Char.Descr.	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
1024210	VM1698-4	7,78	7,79	7,71	7,64	7,77	7,80	7,79	7,76	7,80	7,75
1024210	VM1698-4	39,00	39,25	38,75	38,50	39,00	39,00	39,00	39,00	38,75	38,75

Char.No	Char.Descr.	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
1024210	VM1698-4	7,69	7,78	7,76	7,72	7,72	7,70	7,79	7,72	7,77	7,76
1024210	VM1698-4	38,75	39,00	38,75	39,00	38,75	38,75	38,75	38,75	39,00	38,50

Machine Capability Study
Tool System

Page 1 / 1

Plant ATG Westhausen		Operator Name Anton Czapla	Date 20.09.2017

Ord. No. 17BPYPB13QL	Part type 17BPYPB13QL				Contr.item yes
Serial No. 737457k	Char.Descr. 936522PT	Inspection Val.	40,00	5,00	USL 45,00
	Serial No. 154244	Unit	Grad	-5,00	LSL 35,00
Char.Type variable		Tolerance value	12 %		Decimal Pl. 2
Cust.Name Homologation	Reference System VM1698-4	Test Electronic MPRO400SE			
Contr.No. 816N2152	Reference Transducer 10 / 1029292	nges. 100			

Evaluation from 20.09.2017 15:02:13 to 20.09.2017 15:15:57

Rem. Tq. 60% Angle 40° * +/-5° * Tq-Cal.: 17.65 Nm * Cur.-Cal.: 0.264 Nm/A







Drawing Values		Collected Values		Statistics	
T_m	40.00			$\bar{x}$	40.0000
LSL	35.00	x_{min}	40.00		
USL	45.00	x_{max}	40.00		
T	10.00	R	0.00		
		$n_{<T>}$	100		
		$n_{>USL}$	0		
		$n_{<LSL}$	0		
		n_{eff}	100		
		n_{tot}	100		

--- R = 0 ---

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\AppData\QW\QWE\MessWert\2017\737457k1.DFD

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457k	Characteristic			
Type	17BPYPB13QL	Char.Descr.	936522PT	Inspection Val.	4,08
Ord. No.	17BPYPB13QL	Ser.No.	154244	LSL	0,00
				USL	9,79
Remark	Tq. 60% Angle 40° * +/-5°* Tq-Cal.: 17.65 N m * Cur.-Cal.: 0.264 Nm/A				

Char.No	Char.Descr.	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
154244	936522PT	7,84	7,89	7,89	7,84	7,89	7,93	7,89	7,89	7,89	7,93
154244	936522PT	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No	Char.Descr.	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
154244	936522PT	7,89	7,89	7,89	7,89	7,89	7,89	7,89	7,98	7,84	7,89
154244	936522PT	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No	Char.Descr.	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
154244	936522PT	7,89	7,98	7,89	7,89	7,89	7,93	7,84	7,84	7,89	7,84
154244	936522PT	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No	Char.Descr.	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
154244	936522PT	7,89	7,93	7,98	7,79	7,93	7,89	7,89	7,84	7,89	7,93
154244	936522PT	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No	Char.Descr.	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
154244	936522PT	7,89	7,89	7,89	7,89	7,84	7,84	7,84	7,84	7,93	7,84
154244	936522PT	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No	Char.Descr.	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
154244	936522PT	7,93	7,89	7,89	7,93	7,89	7,93	7,84	7,84	7,84	7,89
154244	936522PT	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No	Char.Descr.	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
154244	936522PT	7,89	7,89	7,84	7,89	7,89	7,84	7,84	7,89	7,89	7,84
154244	936522PT	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No	Char.Descr.	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
154244	936522PT	7,84	7,89	7,89	7,89	7,79	7,84	7,84	7,89	7,84	7,84
154244	936522PT	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457k	Characteristic			
Type	17BPYPB13QL	Char.Descr.	936522PT	Inspection Val.	4,08
Ord. No.	17BPYPB13QL	Ser.No.	154244	LSL	0,00
				USL	9,79
Remark	Tq. 60% Angle 40° * +/-5°* Tq-Cal.: 17.65 N m * Cur.-Cal.: 0.264 Nm/A				

Char.No	Char.Descr.	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
154244	936522PT	7,89	7,89	7,84	7,79	7,91	7,89	7,89	7,84	7,89	7,84
154244	936522PT	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No	Char.Descr.	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
154244	936522PT	7,79	7,89	7,84	7,84	7,84	7,79	7,89	7,79	7,84	7,89
154244	936522PT	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Torque graphs

Model:	**17BPYPB13QL**	Serial no:	**737457**
Target torque:	**7.8 Nm**	60 % of max. torque	
Angle degree:	**40°**	Tool without angle correction	



Value no. 1
Graph
Torque / Angle



Value no. 1
Graph
Torque / Time



Value no. 100
Graph
Torque / Angle



Value no. 100
Graph
Torque / Time

Investigation no.: 010/2017
Date: 25.09.2017

General Specifications

Manufacturer: Apex Tool Group GmbH **Tool type:** LiveWire Tool

Model: 17BPYPB13QL **Serial no:** 737457

Torque range: **3 Nm to 13 Nm**

Difference evaluation: Reference/Tool at 180° / 80 %

Capability examination

Snugfit value: 2.6 Nm **Torque tolerance ±** 7 %

Target torque: 10.4 Nm Tolerance: 2.62 % ± **1.31 %**

Angle degree: 180° Tolerance: 4.0° ± **2.0°**

Formula derivation: $C_m = \frac{T}{6\,s}$ $T = C_m * 6\,s$

Tool without angle correction

Measurement	Tool data		Control data		Difference	
No.	Torque	Angle	Torque	Angle	Torque	Angle
1	10.48	180.00	10.36	177.50	0.12	2.50
2	10.50	180.00	10.39	178.50	0.11	1.50
3	10.53	180.00	10.39	177.50	0.14	2.50
4	10.48	180.00	10.34	178.25	0.14	1.75
5	10.35	180.00	10.27	177.75	0.08	2.25
6	10.45	180.00	10.35	177.50	0.10	2.50
7	10.45	180.00	10.31	177.25	0.14	2.75
8	10.43	180.00	10.27	178.00	0.16	2.00
9	10.38	180.00	10.27	177.50	0.11	2.50
10	10.40	180.00	10.34	177.75	0.06	2.25
11	10.53	180.00	10.37	178.25	0.16	1.75
12	10.45	180.00	10.34	178.00	0.11	2.00
13	10.34	180.00	10.22	177.50	0.12	2.50
14	10.40	180.00	10.30	177.50	0.10	2.50
15	10.48	180.00	10.37	178.00	0.11	2.00
16	10.48	180.00	10.35	178.25	0.13	1.75
17	10.35	180.00	10.24	178.25	0.11	1.75
18	10.35	180.00	10.27	177.25	0.08	2.75
19	10.40	180.00	10.32	177.50	0.08	2.50
20	10.45	180.00	10.34	177.75	0.11	2.25
21	10.40	180.00	10.27	178.00	0.13	2.00
22	10.38	180.00	10.26	178.25	0.12	1.75
23	10.43	180.00	10.32	177.50	0.11	2.50
24	10.40	180.00	10.34	178.00	0.06	2.00
25	10.40	180.00	10.28	178.25	0.12	1.75
26	10.38	180.00	10.23	178.50	0.15	1.50
27	10.34	180.00	10.25	177.25	0.09	2.75
28	10.45	180.00	10.35	177.00	0.10	3.00
29	10.43	180.00	10.34	178.25	0.09	1.75
30	10.43	180.00	10.27	178.50	0.16	1.50
31	10.34	180.00	10.21	177.50	0.13	2.50
32	10.38	180.00	10.24	177.50	0.14	2.50
33	10.38	180.00	10.27	177.75	0.11	2.25
34	10.48	180.00	10.36	177.25	0.12	2.75
35	10.53	180.00	10.35	178.25	0.18	1.75
36	10.35	180.00	10.24	178.75	0.11	1.25
37	10.34	180.00	10.23	177.25	0.11	2.75
38	10.40	180.00	10.29	177.75	0.11	2.25
39	10.40	180.00	10.26	177.00	0.14	3.00
40	10.48	180.00	10.35	178.00	0.13	2.00
41	10.43	180.00	10.28	178.00	0.15	2.00
42	10.43	180.00	10.30	177.75	0.13	2.25
43	10.43	180.00	10.28	177.50	0.15	2.50
44	10.43	180.00	10.27	178.25	0.16	1.75
45	10.34	180.00	10.21	178.00	0.13	2.00
46	10.38	180.00	10.26	177.25	0.12	2.75
47	10.48	180.00	10.35	178.00	0.13	2.00
48	10.38	180.00	10.23	178.00	0.15	2.00
49	10.38	180.00	10.26	177.75	0.12	2.25
50	10.48	180.00	10.32	177.75	0.16	2.25
51	10.43	180.00	10.26	178.00	0.17	2.00
52	10.34	180.00	10.20	177.50	0.14	2.50
53	10.48	180.00	10.31	177.75	0.17	2.25
54	10.48	180.00	10.31	178.25	0.17	1.75
55	10.34	180.00	10.21	177.75	0.13	2.25
56	10.38	180.00	10.28	177.25	0.10	2.75
57	10.48	180.00	10.34	178.00	0.14	2.00
58	10.43	180.00	10.32	178.25	0.11	1.75
59	10.34	180.00	10.21	178.00	0.13	2.00
60	10.34	180.00	10.22	178.00	0.12	2.00
61	10.43	180.00	10.32	178.00	0.11	2.00
62	10.43	180.00	10.33	177.50	0.10	2.50
63	10.48	180.00	10.31	178.25	0.17	1.75
64	10.34	180.00	10.21	177.75	0.13	2.25
65	10.38	180.00	10.29	178.00	0.09	2.00
66	10.43	180.00	10.34	177.75	0.09	2.25
67	10.48	180.00	10.33	178.25	0.15	1.75
68	10.38	180.00	10.22	178.50	0.16	1.50
69	10.38	180.00	10.29	177.00	0.09	3.00
70	10.48	180.00	10.32	177.75	0.16	2.25
71	10.48	180.00	10.34	178.25	0.14	1.75
72	10.34	180.00	10.23	178.00	0.11	2.00
73	10.38	180.00	10.26	177.75	0.12	2.25
74	10.43	180.00	10.29	177.50	0.14	2.50
75	10.48	180.00	10.35	178.00	0.13	2.00
76	10.48	180.00	10.34	178.50	0.14	1.50
77	10.43	180.00	10.26	178.50	0.17	1.50
78	10.38	180.00	10.25	178.75	0.13	1.25
79	10.38	180.00	10.28	177.50	0.10	2.50
80	10.43	180.00	10.32	177.75	0.11	2.25
81	10.43	180.00	10.36	177.75	0.07	2.25
82	10.48	180.00	10.32	178.00	0.16	2.00
83	10.38	180.00	10.24	177.75	0.14	2.25
84	10.34	180.00	10.24	178.00	0.10	2.00
85	10.43	180.00	10.34	177.75	0.09	2.25
86	10.48	180.00	10.34	178.00	0.14	2.00
87	10.43	180.00	10.25	178.25	0.18	1.75
88	10.34	180.00	10.22	178.00	0.12	2.00
89	10.43	180.00	10.31	177.75	0.12	2.25
90	10.48	180.00	10.30	178.00	0.18	2.00
91	10.34	180.00	10.19	178.00	0.15	2.00
92	10.38	180.00	10.29	177.75	0.09	2.25
93	10.48	180.00	10.34	178.00	0.14	2.00
94	10.45	180.00	10.30	177.25	0.15	2.75
95	10.38	180.00	10.24	178.75	0.14	1.25
96	10.38	180.00	10.25	178.00	0.13	2.00
97	10.43	180.00	10.33	178.25	0.10	1.75
98	10.48	180.00	10.32	178.50	0.16	1.50
99	10.34	180.00	10.22	178.25	0.12	1.75
100	10.38	180.00	10.23	178.00	0.15	2.00
				Standard deviation:	**0.027**	**0.398**

Graphical representation

Model:	**17BPYPB13QL**	Serial no:	**737457**
Target torque:	**10.4 Nm**	80 % of max. torque	
Angle degree:	**180°**	Tool without angle correction	





Machine Capability Study
Control System

Page 1 / 1

Plant ATG Westhausen		Operator Name Anton Czapla	Date 20.09.2017

Ord. No. 17BPYPB13QL	Part type 17BPYPB13QL				Contr.item yes
Serial No. 737457l	Char.Descr. VM1698-4	Inspection Val. 180,00	10,00	USL 190,00	
	Serial No. 1024210	Unit Grad	-10,00	LSL 170,00	
Char.Type variable		Tolerance value 6 %		Decimal Pl. 2	
Cust.Name Homologation	Reference System VM1698-4	Test Electronic MPRO400SE			
Contr.No. 816N2152	Reference Transducer 10 / 1029292	nges. 100			

Evaluation from 20.09.2017 15:20:13 to 20.09.2017 15:37:09

Rem. Tq. 80% Angle 180° * +/-10° * Tq-Cal.: 17.65 Nm * Cur.-Cal.: 0.264 Nm/A





Drawing Values		Collected Values		Statistics	
T_m	180.00			$\bar{x}$	177.8850
LSL	170.00	x_{min}	177.00	$\bar{x}$-3s	176.6912
USL	190.00	x_{max}	178.75	$\bar{x}$+3s	179.0788
T	20.00	R	1.75	6s	2.3877
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1 1.4 $\hat{\sigma} = s_{tot}$
Potential Capability index	=	C_m	8.38
Critical capability index	=	C_{mk}	6.60

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457l	Characteristic			
Type	17BPYPB13QL	Char.Descr.	VM1698-4	Inspection Val.	10,45
Ord. No.	17BPYPB13QL	Ser.No.	1024210	LSL	8,15
				USL	12,86
Remark	Tq. 80% Angle 180° * +/-10°* Tq-Cal.: 17.65 Nm * Cur.-Cal.: 0.264 Nm/A				

Char.No	Char.Descr.	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
1024210	VM1698-4	10,36	10,39	10,39	10,34	10,27	10,35	10,31	10,27	10,27	10,34
1024210	VM1698-4	177,50	178,50	177,50	178,25	177,75	177,50	177,25	178,00	177,50	177,75

Char.No	Char.Descr.	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
1024210	VM1698-4	10,37	10,34	10,22	10,30	10,37	10,35	10,24	10,27	10,32	10,34
1024210	VM1698-4	178,25	178,00	177,50	177,50	178,00	178,25	178,25	177,25	177,50	177,75

Char.No	Char.Descr.	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
1024210	VM1698-4	10,27	10,26	10,32	10,34	10,28	10,23	10,25	10,35	10,34	10,27
1024210	VM1698-4	178,00	178,25	177,50	178,00	178,25	178,50	177,25	177,00	178,25	178,50

Char.No	Char.Descr.	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
1024210	VM1698-4	10,21	10,24	10,27	10,36	10,35	10,24	10,23	10,29	10,26	10,35
1024210	VM1698-4	177,50	177,50	177,75	177,25	178,25	178,75	177,25	177,75	177,00	178,00

Char.No	Char.Descr.	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
1024210	VM1698-4	10,28	10,30	10,28	10,27	10,21	10,26	10,35	10,23	10,26	10,32
1024210	VM1698-4	178,00	177,75	177,50	178,25	178,00	177,25	178,00	178,00	177,75	177,75

Char.No	Char.Descr.	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
1024210	VM1698-4	10,26	10,20	10,31	10,31	10,21	10,28	10,34	10,32	10,21	10,22
1024210	VM1698-4	178,00	177,50	177,75	178,25	177,75	177,25	178,00	178,25	178,00	178,00

Char.No	Char.Descr.	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
1024210	VM1698-4	10,32	10,33	10,31	10,21	10,29	10,34	10,33	10,22	10,29	10,32
1024210	VM1698-4	178,00	177,50	178,25	177,75	178,00	177,75	178,25	178,50	177,00	177,75

Char.No	Char.Descr.	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
1024210	VM1698-4	10,34	10,23	10,26	10,29	10,35	10,34	10,26	10,25	10,28	10,32
1024210	VM1698-4	178,25	178,00	177,75	177,50	178,00	178,50	178,50	178,75	177,50	177,75

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457l	Characteristic			
Type	17BPYPB13QL	Char.Descr.	VM1698-4	Inspection Val.	10,45
Ord. No.	17BPYPB13QL	Ser.No.	1024210	LSL	8,15
				USL	12,86
Remark	Tq. 80% Angle 180° * +/-10°* Tq-Cal.: 17.65 Nm * Cur.-Cal.: 0.264 Nm/A				

Char.No	Char.Descr.	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
1024210	VM1698-4	10,36	10,32	10,24	10,24	10,34	10,34	10,25	10,22	10,31	10,30
1024210	VM1698-4	177,75	178,00	177,75	178,00	177,75	178,00	178,25	178,00	177,75	178,00

Char.No	Char.Descr.	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
1024210	VM1698-4	10,19	10,29	10,34	10,30	10,24	10,25	10,33	10,32	10,22	10,23
1024210	VM1698-4	178,00	177,75	178,00	177,25	178,75	178,00	178,25	178,50	178,25	178,00

Machine Capability Study
Tool System

Plant	ATG Westhausen	Operator Name	Anton Czapla
Date	20.09.2017		

Ord. No.	17BPYPB13QL	Part type	17BPYPB13QL	Contr.item	yes
Serial No.	737457l	Char.Descr.	936522PT	Inspection Val. 180,00 10,00	USL 190,00
		Serial No.	154244	Unit Grad -10,00	LSL 170,00
Char.Type	variable			Tolerance value 6 %	Decimal Pl. 2
Cust.Name	Homologation	Reference System	VM1698-4	Test Electronic	MPRO400SE
Contr.No.	816N2152	Reference Transducer	10 / 1029292	nges.	100

Evaluation from 20.09.2017 15:20:15 to 20.09.2017 15:37:10

Rem. Tq. 80% Angle 180° * +/-10° * Tq-Cal.: 17.65 Nm * Cur.-Cal.: 0.264 Nm/A







Drawing Values		Collected Values		Statistics	
T_m	180.00			$\bar{x}$	180.0000
LSL	170.00	x_{min}	180.00		
USL	190.00	x_{max}	180.00		
T	20.00	R	0.00		
		$n_{<T>}$	100		
		$n_{>USL}$	0		
		$n_{<LSL}$	0		
		n_{eff}	100		
		n_{tot}	100		

--- R = 0 ---

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457l	Characteristic			
Type	17BPYPB13QL	Char.Descr.	936522PT	Inspection Val.	5,36
Ord. No.	17BPYPB13QL	Ser.No.	154244	LSL	0,00
				USL	12,86
Remark	Tq. 80% Angle 180° * +/-10°* Tq-Cal.: 17.65 Nm * Cur.-Cal.: 0.264 Nm/A				

Char.No	Char.Descr.	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
154244	936522PT	10,48	10,50	10,53	10,48	10,35	10,45	10,45	10,43	10,38	10,40
154244	936522PT	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No	Char.Descr.	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
154244	936522PT	10,53	10,45	10,34	10,40	10,48	10,48	10,35	10,35	10,40	10,45
154244	936522PT	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No	Char.Descr.	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
154244	936522PT	10,40	10,38	10,43	10,40	10,40	10,38	10,34	10,45	10,43	10,43
154244	936522PT	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No	Char.Descr.	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
154244	936522PT	10,34	10,38	10,38	10,48	10,53	10,35	10,34	10,40	10,40	10,48
154244	936522PT	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No	Char.Descr.	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
154244	936522PT	10,43	10,43	10,43	10,43	10,34	10,38	10,48	10,38	10,38	10,48
154244	936522PT	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No	Char.Descr.	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
154244	936522PT	10,43	10,34	10,48	10,48	10,34	10,38	10,48	10,43	10,34	10,34
154244	936522PT	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No	Char.Descr.	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
154244	936522PT	10,43	10,43	10,48	10,34	10,38	10,43	10,48	10,38	10,38	10,48
154244	936522PT	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No	Char.Descr.	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
154244	936522PT	10,48	10,34	10,38	10,43	10,48	10,48	10,43	10,38	10,38	10,43
154244	936522PT	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Anton Czapla	Date 20.09.2017

Ser.No.	737457l	Characteristic			
Type	17BPYPB13QL	Char.Descr.	936522PT	Inspection Val.	5,36
Ord. No.	17BPYPB13QL	Ser.No.	154244	LSL	0,00
				USL	12,86
Remark	Tq. 80% Angle 180° * +/-10°* Tq-Cal.: 17.65 Nm * Cur.-Cal.: 0.264 Nm/A				

Char.No	Char.Descr.	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
154244	936522PT	10,43	10,48	10,38	10,34	10,43	10,48	10,43	10,34	10,43	10,48
154244	936522PT	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No	Char.Descr.	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
154244	936522PT	10,34	10,38	10,48	10,45	10,38	10,38	10,43	10,48	10,34	10,38
154244	936522PT	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Torque graphs

Model:	**17BPYPB13QL**	Serial no:	**737457**
Target torque:	**10.4 Nm**	80 % of max. torque	
Angle degree:	**180°**	Tool without angle correction	



Value no. 1
Graph
Torque / Angle



Value no. 1
Graph
Torque / Time



Value no. 100
Graph
Torque / Angle



Value no. 100
Graph
Torque / Time