Homologation

Fixtured Spindle

Model: 1BD-1B012A-1K3D-1VK3D

Serial no.: 755949

Contents

Homologation: 1BD-1B012A-1K3D-1VK3D SN: 755949

		Page
Cover sheet		1
Contents		2
Test sheet no. 2 (torque determination 30 %)		3
Machine Capability Study, Tool System	30 % hard	4
Machine Capability Study, Control System	30 % hard	10
Curves of the 1st and 100th measurement	30 % hard	13
Machine Capability Study, Tool System	30 % soft	14
Machine Capability Study, Control System	30 % soft	20
Curves of the 1st and 100th measurement	30 % soft	23
Test sheet no. 3 (torque determination 80 %)		24
Machine Capability Study, Tool System	80 % hard	25
Machine Capability Study, Control System	80 % hard	31
Curves of the 1st and 100th measurement	80 % hard	34
Machine Capability Study, Tool System	80 % soft	35
Machine Capability Study, Control System	80 % soft	41
Curves of the 1st and 100th measurement	80 % soft	44
Test sheet no. 4 (torque determination 100 %)		45
Machine Capability Study, Tool System	100 % hard	46
Machine Capability Study, Control System	100 % hard	52
Curves of the 1st and 100th measurement	100 % hard	55
Machine Capability Study, Tool System	100 % soft	56
Machine Capability Study, Control System	100 % soft	62
Curves of the 1st and 100th measurement	100 % soft	65
Annex 3 (ability contemplation at 40° / 60 %)	**without angle correction**	66
Graphical representation	40° / 60 %	68
Machine Capability Study, Tool System	40° / 60 %	69
Machine Capability Study, Control System	40° / 60 %	75
Curves of the 1st and 100th measurement	40° / 60 %	78
Annex 3 (ability contemplation at 180° / 80 %)	**without angle correction**	79
Graphical representation	180° / 80 %	81
Machine Capability Study, Tool System	180° / 80 %	82
Machine Capability Study, Control System	180° / 80 %	88
Curves of the 1st and 100th measurement	180° / 80 %	91

Test sheet no. 2

Machine Capability Study 30 %

Multi-stage tightening system	☑	Speed 50 rpm	1,6 %
Single-stage tightening system	☐	Speed 100 %	3152 rpm

Manufacturer: Apex Tool Group Serial no: **755949**

Test torque: Tq min. + 0.3 (Tq max. - Tq min.) 5,00 Nm

Hard joint (H)	29,58	Nm / Revolution	Angle degree	30°
Soft joint (L)	2,45	Nm / Revolution	Angle degree	360°

		H	L
a)	Tolerance down / up	4,65 - 5,35 Nm	4,65 - 5,35 Nm
	Tolerance down / up	7 %	7 %
	Average torque	4,93 Nm	4,89 Nm
	Standard deviation	0,02 Nm	0,02 Nm
	Torque scatter (99,73%)	0,13 Nm	0,12 Nm
	C_m	5,28	5,72
	C_{mk}	4,24	3,94

b)	Min. C_m hard/soft (lowest value)	5,28
	Min. C_{mk} hard/soft (lowest value)	3,94

Capability is reached if minimum C_{mk} value ≥1.67

Note:

Machine Capability Study
Control System

Page 1 / 1

Plant ATG Westhausen		Operator Name Sünder	Date 10.06.2022

Ord. No. 1BD12T2O-A	Part type 1BD-1B012A-1K3D-1ZB				Contr.item yes
Serial No. 755949_d	Char.Descr. VM1698-4	Nom.val.	5,00	0,35	USL 5,35
	Serial No. 1024210	Unit	Nm	-0,35	LSL 4,65
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2

Cust.Name Cleco	Reference System VM1698-4	Test Electronic MPRO400GCD-P
Contr.No. Homologation	Reference Transducer 10 / 1026388	nges. 100

Evaluation from 10.06.2022 10:50:38 to 10.06.2022 11:04:44

Rem. TQ 30% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;





Drawing Values		Collected Values		Statistics	
T_m	5.00			x̄	4.9308
LSL	4.65	x_{min}	4.89	x̄-3s	4.8645
USL	5.35	x_{max}	5.01	x̄+3s	4.9971
T	0.70	R	0.12	6s	0.1326
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1.1.4 $\hat{\sigma} = S_{tot}$
Potential Capability index	=	C_m	5.28
Critical capability index	=	C_{mk}	4.24

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_d	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	VM1698-4	Nom.val.	5,00
Ord. No.	1BD12T2O-A	Serial No.	1024210	LSL	4,65
				USL	5,35
Remark	TQ 30% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
1024210	VM1698-4	Nm	4,94	4,95	4,94	4,93	4,91	4,92	4,92	4,91	4,90	4,92
1024210	VM1698-4	Grad	30,25	30,75	30,50	30,25	30,25	30,25	30,75	30,00	30,50	30,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
1024210	VM1698-4	Nm	4,93	4,94	4,95	4,91	4,92	4,93	4,93	4,92	4,96	4,92
1024210	VM1698-4	Grad	30,50	30,75	30,50	30,50	30,00	30,75	30,50	30,00	30,25	30,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
1024210	VM1698-4	Nm	4,94	4,91	4,93	4,94	4,92	4,90	4,92	4,92	4,95	4,94
1024210	VM1698-4	Grad	30,25	30,75	30,25	31,50	30,50	30,25	30,50	30,25	30,50	30,25

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
1024210	VM1698-4	Nm	4,95	4,90	4,92	4,97	4,93	4,93	4,92	4,94	4,90	4,93
1024210	VM1698-4	Grad	31,00	30,00	30,50	31,00	30,50	30,50	30,50	30,50	30,50	30,25

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
1024210	VM1698-4	Nm	4,93	4,92	4,93	4,94	4,93	4,92	4,91	4,93	4,92	4,93
1024210	VM1698-4	Grad	30,25	30,25	30,50	30,25	30,00	30,25	30,25	30,25	30,00	29,75

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
1024210	VM1698-4	Nm	4,93	4,93	4,95	4,93	4,93	4,92	5,01	4,92	4,92	4,95
1024210	VM1698-4	Grad	30,25	30,75	30,50	29,75	30,25	30,25	31,25	30,50	30,25	30,50

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
1024210	VM1698-4	Nm	4,93	4,91	5,01	4,93	4,93	4,92	4,92	5,01	4,95	4,91
1024210	VM1698-4	Grad	30,75	29,25	31,25	30,25	30,00	30,50	30,00	31,00	30,00	30,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
1024210	VM1698-4	Nm	4,93	4,94	4,93	4,94	4,92	4,91	4,93	4,94	4,93	4,95
1024210	VM1698-4	Grad	30,25	30,25	30,25	30,25	30,00	30,25	30,00	30,75	30,75	31,25

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_d	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	VM1698-4	Nom.val.	5,00
Ord. No.	1BD12T2O-A	Serial No.	1024210	LSL	4,65
				USL	5,35
Remark	TQ 30% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
1024210	VM1698-4	Nm	4,91	4,89	4,93	4,93	4,94	4,91	4,94	4,92	4,93	4,90
1024210	VM1698-4	Grad	30,00	30,00	30,50	30,50	30,50	30,75	30,75	30,50	29,75	30,25

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
1024210	VM1698-4	Nm	4,99	4,91	4,94	4,91	4,92	4,99	4,92	4,90	4,95	4,95
1024210	VM1698-4	Grad	31,25	30,25	30,00	30,25	30,25	31,50	30,50	30,00	30,75	30,25

Machine Capability Study
Tool System

Page 1 / 1

Plant ATG Westhausen		Operator Name Sünder	Date 10.06.2022

Ord. No. 1BD12T2O-A	Part type 1BD-1B012A-1K3D-1ZB				Contr.item yes
Serial No. 755949_d	Char.Descr. 1VK3D	Nom.val.	5,00	0,35	USL 5,35
	Serial No. 198080	Unit	Nm	-0,35	LSL 4,65
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2
Cust.Name Cleco	Reference System VM1698-4				Test Electronic MPRO400GCD-P
Contr.No. Homologation	Reference Transducer 10 / 1026388				nges. 100

Evaluation from 10.06.2022 10:50:39 to 10.06.2022 11:04:45

Rem. TQ 30% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;







Drawing Values		Collected Values		Statistics	
T_m	5.00			$\bar{x}$	5.0359
LSL	4.65	x_{min}	5.00	$\bar{x}$-3s	4.9932
USL	5.35	x_{max}	5.07	$\bar{x}$+3s	5.0786
T	0.70	R	0.07	6s	0.0853
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1 1.4 $\hat{\sigma}$ = S_{tot}
Potential Capability index	=	C_m	8.20
Critical capability index	=	C_{mk}	7.36

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_d	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1VK3D	Nom.val.	5,00
Ord. No.	1BD12T2O-A	Serial No.	198080	LSL	4,65
				USL	5,35
Remark	TQ 30% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
198080	1VK3D	Nm	5,03	5,07	5,05	5,05	5,03	5,05	5,03	5,02	5,02	5,04
198080	1VK3D	Grad	31,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
198080	1VK3D	Nm	5,03	5,06	5,07	5,03	5,03	5,04	5,05	5,04	5,05	5,06
198080	1VK3D	Grad	31,00	31,00	31,00	31,00	31,00	32,00	31,00	31,00	31,00	31,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
198080	1VK3D	Nm	5,03	5,03	5,02	5,03	5,03	5,00	5,03	5,03	5,03	5,03
198080	1VK3D	Grad	31,00	31,00	31,00	32,00	31,00	31,00	31,00	31,00	31,00	31,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
198080	1VK3D	Nm	5,04	5,01	5,05	5,01	5,03	5,06	5,04	5,04	5,01	5,03
198080	1VK3D	Grad	32,00	31,00	31,00	31,00	32,00	31,00	31,00	31,00	31,00	31,00

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
198080	1VK3D	Nm	5,03	5,03	5,05	5,06	5,02	5,03	5,03	5,04	5,04	5,03
198080	1VK3D	Grad	31,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	30,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
198080	1VK3D	Nm	5,04	5,03	5,04	5,05	5,05	5,03	5,04	5,03	5,04	5,05
198080	1VK3D	Grad	31,00	31,00	31,00	30,00	31,00	31,00	32,00	31,00	31,00	31,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
198080	1VK3D	Nm	5,03	5,01	5,04	5,01	5,04	5,02	5,04	5,05	5,05	5,03
198080	1VK3D	Grad	32,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
198080	1VK3D	Nm	5,04	5,05	5,03	5,05	5,02	5,04	5,07	5,06	5,05	5,03
198080	1VK3D	Grad	31,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	32,00	32,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_d	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1VK3D	Nom.val.	5,00
Ord. No.	1BD12T2O-A	Serial No.	198080	LSL	4,65
				USL	5,35
Remark	TQ 30% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
198080	1VK3D	Nm	5,03	5,01	5,03	5,04	5,06	5,02	5,03	5,03	5,04	5,02
198080	1VK3D	Grad	31,00	31,00	31,00	31,00	31,00	31,00	32,00	31,00	30,00	31,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
198080	1VK3D	Nm	5,03	5,02	5,04	5,02	5,04	5,03	5,03	5,02	5,05	5,05
198080	1VK3D	Grad	31,00	31,00	31,00	31,00	31,00	32,00	31,00	31,00	32,00	31,00

Machine Capability Study
Tool System

Page 1 / 1

Plant ATG Westhausen		Operator Name Sünder	Date 10.06.2022

Ord. No. 1BD12T2O-A	Part type 1BD-1B012A-1K3D-1ZB				Contr.item yes
Serial No. 755949_d	Char.Descr. 1K3D	Nom.val.	5,00	0,35	USL 5,35
	Serial No. 205495	Unit	Nm	-0,35	LSL 4,65
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2
Cust.Name Cleco	Reference System VM1698-4				Test Electronic MPRO400GCD-P
Contr.No. Homologation	Reference Transducer 10 / 1026388				nges. 100

Evaluation from 10.06.2022 10:50:39 to 10.06.2022 11:04:45

Rem. TQ 30% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;





Drawing Values		Collected Values		Statistics	
T_m	5.00			$\bar{x}$	5.0184
LSL	4.65	x_{min}	4.95	$\bar{x}$-3s	4.9284
USL	5.35	x_{max}	5.11	$\bar{x}$+3s	5.1084
T	0.70	R	0.16	6s	0.1800
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1 1.4 $\hat{\sigma}$ = S_{tot}
Potential Capability index	=	C_m	3.89
Critical capability index	=	C_{mk}	3.68

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\Appdata\QW\QWE\Messwert\2022\755949_d2.DFD

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_d	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1K3D	Nom.val.	5,00
Ord. No.	1BD12T2O-A	Serial No.	205495	LSL	4,65
				USL	5,35
Remark	TQ 30% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
205495	1K3D	Nm	5,03	5,05	5,01	5,02	5,02	4,99	5,02	4,98	4,98	4,99
205495	1K3D	Grad	31,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
205495	1K3D	Nm	4,99	5,03	5,06	4,95	5,02	4,99	5,05	5,02	5,07	5,04
205495	1K3D	Grad	31,00	31,00	31,00	31,00	31,00	32,00	31,00	31,00	31,00	31,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
205495	1K3D	Nm	5,02	4,99	5,01	5,02	5,02	4,99	4,98	5,01	5,01	5,02
205495	1K3D	Grad	31,00	31,00	31,00	32,00	31,00	31,00	31,00	31,00	31,00	31,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
205495	1K3D	Nm	5,03	4,96	5,01	5,03	5,01	5,06	5,00	5,04	4,97	5,01
205495	1K3D	Grad	32,00	31,00	31,00	31,00	32,00	31,00	31,00	31,00	31,00	31,00

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
205495	1K3D	Nm	5,00	4,99	5,04	5,05	5,00	5,01	4,99	5,00	5,03	4,99
205495	1K3D	Grad	31,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	30,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
205495	1K3D	Nm	5,06	5,06	5,05	5,03	5,01	5,04	5,08	5,00	5,02	5,04
205495	1K3D	Grad	31,00	31,00	31,00	30,00	31,00	31,00	32,00	31,00	31,00	31,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
205495	1K3D	Nm	4,96	5,00	5,04	5,02	5,00	4,99	5,01	5,11	5,07	5,01
205495	1K3D	Grad	32,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
205495	1K3D	Nm	4,98	5,06	5,00	5,02	4,99	5,03	5,08	5,06	5,02	5,03
205495	1K3D	Grad	31,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	32,00	32,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_d	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1K3D	Nom.val.	5,00
Ord. No.	1BD12T2O-A	Serial No.	205495	LSL	4,65
				USL	5,35
Remark	TQ 30% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
205495	1K3D	Nm	5,01	4,98	5,00	5,02	5,03	4,99	5,02	5,01	5,02	5,02
205495	1K3D	Grad	31,00	31,00	31,00	31,00	31,00	31,00	32,00	31,00	30,00	31,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
205495	1K3D	Nm	5,09	4,99	5,03	4,98	5,00	5,08	5,00	5,00	5,04	5,06
205495	1K3D	Grad	31,00	31,00	31,00	31,00	31,00	32,00	31,00	31,00	32,00	31,00

Torque graphs

Machine Capability Study 30 %

Model: **1BD-1B012A-1K3D-1VK3D**
Serial no: **755949**

Angle degree: **30°**
Test torque: **5,0 Nm**



Value no. 1
Graph
Torque / Angle / Speed



Value no. 1
Graph
Torque / Time / Speed



Value no. 100
Graph
Torque / Angle / Speed



Value no. 100
Graph
Torque / Time / Speed

Machine Capability Study
Control System

Page 1 / 1

Plant ATG Westhausen		Operator Name Sünder	Date 10.06.2022

Ord. No. 1BD12T2O-A	Part type 1BD-1B012A-1K3D-1ZB				Contr.item yes
Serial No. 755949_c	Char.Descr. VM1698-4	Nom.val.	5,00	0,35	USL 5,35
	Serial No. 1024210	Unit	Nm	-0,35	LSL 4,65
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2

Cust.Name Cleco	Reference System VM1698-4	Test Electronic MPRO400GCD-P
Contr.No. Homologation	Reference Transducer 10 / 1026388	nges. 100

Evaluation from 10.06.2022 11:15:49 to 10.06.2022 11:39:45

Rem. TQ 30% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;





Drawing Values		Collected Values		Statistics	
T_m	5.00			$\bar{x}$	4.8912
LSL	4.65	x_{min}	4.86	$\bar{x}$-3s	4.8300
USL	5.35	x_{max}	4.97	$\bar{x}$+3s	4.9524
T	0.70	R	0.11	6s	0.1225
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1.1.4 $\hat{\sigma}$ = S_{tot}
Potential Capability index	=	C_m	5.72
Critical capability index	=	C_{mk}	3.94

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_c	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	VM1698-4	Nom.val.	5,00
Ord. No.	1BD12T2O-A	Serial No.	1024210	LSL	4,65
				USL	5,35
Remark	TQ 30% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
1024210	VM1698-4	Nm	4,89	4,92	4,90	4,95	4,89	4,90	4,88	4,88	4,94	4,87
1024210	VM1698-4	Grad	370,00	364,00	374,50	368,75	351,50	360,50	361,25	357,00	382,00	362,25

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
1024210	VM1698-4	Nm	4,89	4,90	4,88	4,89	4,87	4,91	4,87	4,87	4,93	4,88
1024210	VM1698-4	Grad	367,00	365,00	368,75	362,00	360,50	366,50	350,50	363,50	374,25	361,25

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
1024210	VM1698-4	Nm	4,89	4,88	4,88	4,87	4,87	4,88	4,91	4,90	4,91	4,94
1024210	VM1698-4	Grad	360,25	366,50	363,50	359,75	364,25	359,25	365,25	363,50	367,75	374,75

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
1024210	VM1698-4	Nm	4,89	4,89	4,91	4,90	4,87	4,87	4,89	4,89	4,87	4,88
1024210	VM1698-4	Grad	368,75	359,75	362,00	371,50	363,75	357,25	363,25	374,50	357,75	370,50

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
1024210	VM1698-4	Nm	4,90	4,90	4,88	4,88	4,97	4,87	4,90	4,87	4,89	4,87
1024210	VM1698-4	Grad	365,75	371,00	359,75	361,00	377,00	363,25	367,25	360,25	365,75	360,50

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
1024210	VM1698-4	Nm	4,90	4,89	4,87	4,88	4,87	4,89	4,88	4,87	4,88	4,87
1024210	VM1698-4	Grad	361,75	361,75	361,75	359,00	363,25	363,75	360,00	361,75	359,00	360,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
1024210	VM1698-4	Nm	4,88	4,86	4,89	4,90	4,88	4,88	4,89	4,89	4,90	4,90
1024210	VM1698-4	Grad	358,00	358,00	361,50	367,25	362,50	364,25	362,50	365,50	364,75	369,25

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
1024210	VM1698-4	Nm	4,88	4,88	4,89	4,91	4,89	4,87	4,88	4,88	4,90	4,89
1024210	VM1698-4	Grad	359,25	361,75	362,50	365,25	363,00	358,00	369,25	360,50	361,75	363,00

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_c	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	VM1698-4	Nom.val.	5,00
Ord. No.	1BD12T2O-A	Serial No.	1024210	LSL	4,65
				USL	5,35
Remark	TQ 30% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
1024210	VM1698-4	Nm	4,90	4,93	4,91	4,88	4,94	4,89	4,89	4,96	4,87	4,88
1024210	VM1698-4	Grad	367,75	372,00	368,25	357,75	367,75	357,50	356,75	374,50	350,75	355,25

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
1024210	VM1698-4	Nm	4,88	4,90	4,89	4,91	4,88	4,89	4,89	4,88	4,89	4,89
1024210	VM1698-4	Grad	354,50	357,00	353,00	358,50	354,00	355,50	357,25	355,25	355,25	357,25

Machine Capability Study
Tool System

Page 1 / 1

Plant	ATG Westhausen	Operator Name	Sünder
Date	10.06.2022		

Ord. No.	1BD12T2O-A	Part type	1BD-1B012A-1K3D-1ZB	Contr.item	yes
Serial No.	755949_c	Char.Descr.	1VK3D	Nom.val.	5,00 / 0,35
		Serial No.	198080	Unit	Nm / -0,35
				USL	5,35
				LSL	4,65
Char.Type	variable			Tolerance value	7 %
				Decimal Pl.	2
Cust.Name	Cleco	Reference System	VM1698-4	Test Electronic	MPRO400GCD-P
Contr.No.	Homologation	Reference Transducer	10 / 1026388	nges.	100

Evaluation from 10.06.2022 11:15:50 to 10.06.2022 11:39:45

Rem. TQ 30% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;





Drawing Values		Collected Values		Statistics	
T_m	5.00			$\bar{x}$	5.0045
LSL	4.65	x_{min}	5.00	$\bar{x}$-3s	4.9830
USL	5.35	x_{max}	5.03	$\bar{x}$+3s	5.0260
T	0.70	R	0.03	6s	0.0430
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1 1.4 $\hat{\sigma}$ = S_{tot}
Potential Capability index	=	C_m	16.29
Critical capability index	=	C_{mk}	16.09

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\Appdata\QW\QWE\Messwert\2022\755949_c1.DFD

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_c	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1VK3D	Nom.val.	5,00
Ord. No.	1BD12T2O-A	Serial No.	198080	LSL	4,65
				USL	5,35
Remark	TQ 30% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
198080	1VK3D	Nm	5,00	5,03	5,00	5,00	5,02	5,00	5,01	5,01	5,01	5,00
198080	1VK3D	Grad	379,00	377,00	383,00	374,00	368,00	376,00	378,00	369,00	394,00	376,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
198080	1VK3D	Nm	5,01	5,01	5,00	5,01	5,00	5,00	5,00	5,00	5,02	5,00
198080	1VK3D	Grad	379,00	381,00	385,00	376,00	372,00	376,00	368,00	381,00	382,00	377,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
198080	1VK3D	Nm	5,00	5,00	5,00	5,00	5,00	5,00	5,00	5,00	5,01	5,00
198080	1VK3D	Grad	375,00	379,00	378,00	377,00	380,00	377,00	378,00	375,00	379,00	386,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
198080	1VK3D	Nm	5,00	5,00	5,00	5,00	5,00	5,00	5,02	5,01	5,00	5,01
198080	1VK3D	Grad	385,00	379,00	375,00	382,00	380,00	376,00	379,00	387,00	372,00	384,00

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
198080	1VK3D	Nm	5,00	5,03	5,00	5,00	5,00	5,00	5,01	5,00	5,01	5,00
198080	1VK3D	Grad	381,00	385,00	376,00	373,00	380,00	381,00	377,00	377,00	379,00	378,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
198080	1VK3D	Nm	5,00	5,01	5,00	5,01	5,00	5,00	5,01	5,00	5,02	5,00
198080	1VK3D	Grad	377,00	374,00	377,00	378,00	378,00	379,00	378,00	381,00	379,00	374,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
198080	1VK3D	Nm	5,01	5,00	5,01	5,01	5,00	5,00	5,00	5,00	5,00	5,00
198080	1VK3D	Grad	375,00	374,00	377,00	377,00	379,00	378,00	376,00	378,00	378,00	388,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
198080	1VK3D	Nm	5,00	5,01	5,01	5,00	5,01	5,00	5,00	5,00	5,02	5,01
198080	1VK3D	Grad	377,00	375,00	381,00	375,00	378,00	370,00	382,00	372,00	376,00	379,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_c	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1VK3D	Nom.val.	5,00
Ord. No.	1BD12T2O-A	Serial No.	198080	LSL	4,65
				USL	5,35
Remark	TQ 30% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
198080	1VK3D	Nm	5,00	5,00	5,00	5,01	5,00	5,00	5,00	5,00	5,00	5,00
198080	1VK3D	Grad	386,00	380,00	379,00	374,00	377,00	374,00	369,00	381,00	366,00	372,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
198080	1VK3D	Nm	5,00	5,01	5,00	5,02	5,00	5,01	5,00	5,00	5,01	5,02
198080	1VK3D	Grad	369,00	371,00	368,00	375,00	372,00	370,00	367,00	368,00	370,00	371,00

Machine Capability Study
Tool System

Page 1 / 1

Plant ATG Westhausen		Operator Name Sünder	Date 10.06.2022

Ord. No. 1BD12T2O-A	Part type 1BD-1B012A-1K3D-1ZB				Contr.item yes
Serial No. 755949_c	Char.Descr. 1K3D	Nom.val.	5,00	0,35	USL 5,35
	Serial No. 205495	Unit	Nm	-0,35	LSL 4,65
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2
Cust.Name Cleco	Reference System VM1698-4				Test Electronic MPRO400GCD-P
Contr.No. Homologation	Reference Transducer 10 / 1026388				nges. 100

Evaluation from 10.06.2022 11:15:50 to 10.06.2022 11:39:45

Rem. TQ 30% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;







Drawing Values		Collected Values		Statistics	
T_m	5.00			$\bar{x}$	4.9766
LSL	4.65	x_{min}	4.91	$\bar{x}$-3s	4.8759
USL	5.35	x_{max}	5.08	$\bar{x}$+3s	5.0773
T	0.70	R	0.17	6s	0.2013
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1.1.4 $\hat{\sigma}$ = S_{tot}
Potential Capability index	=	C_m	3.48
Critical capability index	=	C_{mk}	3.24

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\Appdata\QW\QWE\Messwert\2022\755949_c2.DFD

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_c	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1K3D	Nom.val.	5,00
Ord. No.	1BD12T2O-A	Serial No.	205495	LSL	4,65
				USL	5,35
Remark	TQ 30% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
205495	1K3D	Nm	4,99	5,05	5,03	5,03	5,00	4,98	4,99	4,97	5,04	5,01
205495	1K3D	Grad	379,00	377,00	383,00	374,00	368,00	376,00	378,00	369,00	394,00	376,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
205495	1K3D	Nm	5,00	5,02	4,96	4,97	4,96	4,99	4,95	4,96	5,03	4,96
205495	1K3D	Grad	379,00	381,00	385,00	376,00	372,00	376,00	368,00	381,00	382,00	377,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
205495	1K3D	Nm	4,96	4,97	4,95	4,93	4,95	4,97	4,94	4,94	5,01	5,06
205495	1K3D	Grad	375,00	379,00	378,00	377,00	380,00	377,00	378,00	375,00	379,00	386,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
205495	1K3D	Nm	4,96	4,93	4,97	4,94	4,96	4,98	4,97	5,02	4,93	4,96
205495	1K3D	Grad	385,00	379,00	375,00	382,00	380,00	376,00	379,00	387,00	372,00	384,00

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
205495	1K3D	Nm	4,96	5,04	4,96	4,97	5,08	4,99	4,99	4,94	4,92	4,96
205495	1K3D	Grad	381,00	385,00	376,00	373,00	380,00	381,00	377,00	377,00	379,00	378,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
205495	1K3D	Nm	4,98	4,96	4,96	4,97	4,95	4,96	4,93	4,93	4,99	4,94
205495	1K3D	Grad	377,00	374,00	377,00	378,00	378,00	379,00	378,00	381,00	379,00	374,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
205495	1K3D	Nm	4,99	4,95	4,99	5,01	5,03	4,97	4,96	4,95	4,98	5,01
205495	1K3D	Grad	375,00	374,00	377,00	377,00	379,00	378,00	376,00	378,00	378,00	388,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
205495	1K3D	Nm	4,96	4,93	4,98	4,99	4,99	4,93	4,96	4,93	4,98	4,96
205495	1K3D	Grad	377,00	375,00	381,00	375,00	378,00	370,00	382,00	372,00	376,00	379,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_c	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1K3D	Nom.val.	5,00
Ord. No.	1BD12T2O-A	Serial No.	205495	LSL	4,65
				USL	5,35
Remark	TQ 30% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
205495	1K3D	Nm	4,94	4,97	5,01	4,95	5,02	4,99	5,01	5,06	4,98	4,93
205495	1K3D	Grad	386,00	380,00	379,00	374,00	377,00	374,00	369,00	381,00	366,00	372,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
205495	1K3D	Nm	4,91	4,98	4,99	4,98	4,99	4,98	4,99	4,99	4,98	4,99
205495	1K3D	Grad	369,00	371,00	368,00	375,00	372,00	370,00	367,00	368,00	370,00	371,00

Torque graphs

Machine Capability Study 30 %

Model: **1BD-1B012A-1K3D-1VK3D**
Serial no: **755949**

Angle degree: **360°**
Test torque: **5,0 Nm**



Value no. 1
Graph
Torque / Angle / Speed



Value no. 1
Graph
Torque / Time / Speed



Value no. 100
Graph
Torque / Angle / Speed



Value no. 100
Graph
Torque / Time / Speed

Test sheet no. 3

Machine Capability Study 80 %

Multi-stage tightening system	☑	Speed 50 rpm	1,6 %
Single-stage tightening system	☐	Speed 100 %	3152 rpm

Manufacturer: Apex Tool Group Serial no: **755949**

Test torque: Tq min. + 0.8 (Tq max. - Tq min.) 10,00 Nm

Hard joint (H)	59,65 Nm / Revolution	Angle degree	30°
Soft joint (L)	4,98 Nm / Revolution	Angle degree	360°

		H	L
a)	Tolerance down / up	9,30 - 10,70 Nm	9,30 - 10,70 Nm
	Tolerance down / up	7 %	7 %
	Average torque	9,94 Nm	9,96 Nm
	Standard deviation	0,05 Nm	0,03 Nm
	Torque scatter (99,73%)	0,28 Nm	0,19 Nm
	C_m	4,93	7,23
	C_{mk}	4,52	6,81

b)	Min. C_m hard/soft (lowest value)	4,93
	Min. C_{mk} hard/soft (lowest value)	4,52

Capability is reached if minimum C_{mk} value ≥1.67

Note:

Machine Capability Study
Control System

Page 1 / 1

Plant ATG Westhausen		Operator Name Sünder	Date 10.06.2022

Ord. No. 1BD12T2O-A	Part type 1BD-1B012A-1K3D-1ZB				Contr.item yes
Serial No. 755949_h	Char.Descr. VM1698-4	Nom.val.	10,00	0,70	USL 10,70
	Serial No. 1024210	Unit	Nm	-0,70	LSL 9,30
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2

Cust.Name Cleco	Reference System VM1698-4	Test Electronic MPRO400GCD-P
Contr.No. Homologation	Reference Transducer 10 / 1026388	nges. 100

Evaluation from 10.06.2022 13:16:01 to 10.06.2022 13:31:45

Rem. TQ 80% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;





Drawing Values		Collected Values		Statistics	
T_m	10.00			$\bar{x}$	9.9423
LSL	9.30	x_{min}	9.85	$\bar{x}$-3s	9.8002
USL	10.70	x_{max}	10.04	$\bar{x}$+3s	10.0844
T	1.40	R	0.19	6s	0.2842
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1.1.4 $\hat{\sigma} = S_{tot}$
Potential Capability index	=	C_m	4.93
Critical capability index	=	C_{mk}	4.52

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_h	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	VM1698-4	Nom.val.	10,00
Ord. No.	1BD12T2O-A	Serial No.	1024210	LSL	9,30
				USL	10,70
Remark	TQ 80% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
1024210	VM1698-4	Nm	9,91	9,86	9,89	10,01	9,92	9,90	9,88	9,86	9,91	9,90
1024210	VM1698-4	Grad	30,00	30,50	30,00	30,75	30,75	31,00	30,50	30,75	31,50	30,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
1024210	VM1698-4	Nm	9,89	10,00	9,93	9,94	9,99	9,94	9,90	9,91	9,89	9,93
1024210	VM1698-4	Grad	31,00	31,25	31,50	30,75	31,25	31,25	30,50	31,00	29,50	30,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
1024210	VM1698-4	Nm	9,89	9,91	10,00	9,96	9,87	9,89	9,89	9,97	9,93	9,96
1024210	VM1698-4	Grad	30,50	30,00	30,50	8,75	30,50	29,50	31,00	31,25	30,50	31,75

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
1024210	VM1698-4	Nm	9,90	10,03	9,87	9,98	9,89	9,92	9,92	9,91	9,99	9,96
1024210	VM1698-4	Grad	30,50	32,50	29,50	31,50	30,75	30,50	29,50	30,50	30,50	30,25

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
1024210	VM1698-4	Nm	9,91	9,98	9,93	9,90	9,97	9,99	10,01	10,03	9,91	9,93
1024210	VM1698-4	Grad	30,75	30,00	30,50	29,75	30,75	30,75	31,00	31,75	31,00	30,75

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
1024210	VM1698-4	Nm	9,95	10,02	9,92	9,92	9,95	9,88	9,89	9,89	9,92	9,97
1024210	VM1698-4	Grad	30,50	30,25	29,50	30,00	30,50	30,00	29,75	31,50	31,50	30,50

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
1024210	VM1698-4	Nm	9,98	9,99	9,99	9,93	9,90	9,96	9,92	9,95	9,91	9,88
1024210	VM1698-4	Grad	31,25	30,25	31,00	30,50	30,25	30,25	30,50	30,25	30,00	30,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
1024210	VM1698-4	Nm	9,95	9,94	9,93	9,95	9,96	9,94	9,94	10,02	9,94	9,90
1024210	VM1698-4	Grad	31,25	30,25	32,50	30,50	30,75	29,75	29,75	30,75	30,00	29,25

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_h	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	VM1698-4	Nom.val.	10,00
Ord. No.	1BD12T2O-A	Serial No.	1024210	LSL	9,30
				USL	10,70
Remark	TQ 80% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
1024210	VM1698-4	Nm	9,92	9,88	10,02	9,99	9,85	9,99	10,00	9,98	10,04	9,91
1024210	VM1698-4	Grad	29,00	30,00	30,50	30,00	29,75	29,50	29,25	30,75	29,50	29,25

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
1024210	VM1698-4	Nm	9,98	10,02	9,98	10,01	10,00	9,99	9,98	10,01	9,90	10,03
1024210	VM1698-4	Grad	29,75	30,00	30,00	30,00	29,75	30,25	30,25	31,00	30,25	31,25

Machine Capability Study
Tool System

Page 1 / 1

Plant	ATG Westhausen	Operator Name	Sünder
Date	10.06.2022		

Ord. No.	1BD12T2O-A	Part type	1BD-1B012A-1K3D-1ZB	Contr.item	yes
Serial No.	755949_h	Char.Descr.	1VK3D	Nom.val. 10,00 / 0,70	USL 10,70
		Serial No.	198080	Unit Nm / -0,70	LSL 9,30
Char.Type	variable			Tolerance value 7 %	Decimal Pl. 2
Cust.Name	Cleco	Reference System	VM1698-4	Test Electronic	MPRO400GCD-P
Contr.No.	Homologation	Reference Transducer	10 / 1026388	nges.	100

Evaluation from 10.06.2022 13:16:02 to 10.06.2022 13:31:46

Rem. TQ 80% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;





Drawing Values		Collected Values		Statistics	
T_m	10.00			$\bar{x}$	10.0507
LSL	9.30	x_{min}	10.01	$\bar{x}$-3s	9.9928
USL	10.70	x_{max}	10.12	$\bar{x}$+3s	10.1086
T	1.40	R	0.11	6s	0.1158
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1 1.4 $\hat{\sigma}$ = S_{tot}
Potential Capability index	=	C_m	12.09
Critical capability index	=	C_{mk}	11.22

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\Appdata\QW\QWE\Messwert\2022\755949_h1.DFD

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_h	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1VK3D	Nom.val.	10,00
Ord. No.	1BD12T2O-A	Serial No.	198080	LSL	9,30
				USL	10,70
Remark	TQ 80% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
198080	1VK3D	Nm	10,05	10,03	10,05	10,08	10,05	10,03	10,04	10,04	10,05	10,06
198080	1VK3D	Grad	30,00	31,00	30,00	31,00	31,00	31,00	31,00	31,00	32,00	30,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
198080	1VK3D	Nm	10,04	10,05	10,06	10,07	10,06	10,04	10,05	10,05	10,02	10,02
198080	1VK3D	Grad	32,00	31,00	32,00	31,00	31,00	32,00	31,00	32,00	30,00	30,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
198080	1VK3D	Nm	10,02	10,09	10,06	10,05	10,03	10,06	10,06	10,06	10,01	10,07
198080	1VK3D	Grad	31,00	31,00	31,00	32,00	31,00	30,00	31,00	32,00	31,00	32,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
198080	1VK3D	Nm	10,05	10,09	10,04	10,05	10,04	10,06	10,07	10,06	10,06	10,05
198080	1VK3D	Grad	31,00	33,00	30,00	32,00	31,00	31,00	30,00	31,00	31,00	31,00

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
198080	1VK3D	Nm	10,05	10,03	10,03	10,03	10,07	10,06	10,09	10,08	10,06	10,05
198080	1VK3D	Grad	31,00	30,00	31,00	30,00	31,00	31,00	31,00	32,00	31,00	31,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
198080	1VK3D	Nm	10,05	10,10	10,06	10,07	10,07	10,04	10,05	10,06	10,05	10,02
198080	1VK3D	Grad	31,00	31,00	30,00	30,00	31,00	30,00	30,00	32,00	32,00	31,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
198080	1VK3D	Nm	10,05	10,04	10,04	10,02	10,05	10,06	10,03	10,04	10,05	10,04
198080	1VK3D	Grad	32,00	30,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	30,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
198080	1VK3D	Nm	10,08	10,03	10,04	10,05	10,05	10,05	10,07	10,06	10,05	10,04
198080	1VK3D	Grad	32,00	31,00	33,00	31,00	31,00	30,00	30,00	31,00	30,00	30,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_h	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1VK3D	Nom.val.	10,00
Ord. No.	1BD12T2O-A	Serial No.	198080	LSL	9,30
				USL	10,70
Remark	TQ 80% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
198080	1VK3D	Nm	10,05	10,02	10,07	10,04	10,01	10,05	10,04	10,04	10,07	10,03
198080	1VK3D	Grad	30,00	31,00	31,00	30,00	30,00	30,00	30,00	31,00	30,00	29,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
198080	1VK3D	Nm	10,07	10,08	10,03	10,06	10,04	10,04	10,02	10,05	10,06	10,12
198080	1VK3D	Grad	30,00	30,00	30,00	30,00	30,00	31,00	31,00	31,00	31,00	31,00

Machine Capability Study
Tool System

Page 1 / 1

Plant	ATG Westhausen	Operator Name	Sünder
Date	10.06.2022		

Ord. No.	1BD12T2O-A	Part type	1BD-1B012A-1K3D-1ZB	Contr.item	yes
Serial No.	755949_h	Char.Descr.	1K3D	Nom.val.	10,00
		Serial No.	205495	Unit	Nm
				USL	10,70
				LSL	9,30
Char.Type	variable	Tolerance value	7 %	Decimal Pl.	2
Cust.Name	Cleco	Reference System	VM1698-4	Test Electronic	MPRO400GCD-P
Contr.No.	Homologation	Reference Transducer	10 / 1026388	nges.	100

Evaluation from 10.06.2022 13:16:02 to 10.06.2022 13:31:46

Rem. TQ 80% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;





Drawing Values		Collected Values		Statistics	
T_m	10.00			$\bar{x}$	9.9971
LSL	9.30	x_{min}	9.87	$\bar{x}$-3s	9.8025
USL	10.70	x_{max}	10.15	$\bar{x}$+3s	10.1917
T	1.40	R	0.28	6s	0.3892
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1 1.4 $\hat{\sigma}$ = S_{tot}
Potential Capability index	=	C_m	3.60
Critical capability index	=	C_{mk}	3.58

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\Appdata\QW\QWE\Messwert\2022\755949_h2.DFD

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_h	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1K3D	Nom.val.	10,00
Ord. No.	1BD12T2O-A	Serial No.	205495	LSL	9,30
				USL	10,70
Remark	TQ 80% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
205495	1K3D	Nm	9,95	9,97	9,98	10,04	10,04	10,02	9,95	9,94	9,94	9,97
205495	1K3D	Grad	30,00	31,00	30,00	31,00	31,00	31,00	31,00	31,00	32,00	30,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
205495	1K3D	Nm	9,93	10,00	9,98	10,02	10,09	10,01	9,95	10,08	10,00	10,04
205495	1K3D	Grad	32,00	31,00	32,00	31,00	31,00	32,00	31,00	32,00	30,00	30,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
205495	1K3D	Nm	9,95	9,95	10,12	10,06	9,90	9,99	9,88	9,96	9,97	10,08
205495	1K3D	Grad	31,00	31,00	31,00	32,00	31,00	30,00	31,00	32,00	31,00	32,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
205495	1K3D	Nm	9,97	10,13	9,97	9,96	9,95	9,96	10,00	9,92	9,94	10,02
205495	1K3D	Grad	31,00	33,00	30,00	32,00	31,00	31,00	30,00	31,00	31,00	31,00

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
205495	1K3D	Nm	9,93	10,02	9,93	9,87	9,97	10,02	9,99	10,11	9,98	10,00
205495	1K3D	Grad	31,00	30,00	31,00	30,00	31,00	31,00	31,00	32,00	31,00	31,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
205495	1K3D	Nm	10,03	10,07	9,98	9,95	10,05	9,90	9,93	9,93	9,95	10,08
205495	1K3D	Grad	31,00	31,00	30,00	30,00	31,00	30,00	30,00	32,00	32,00	31,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
205495	1K3D	Nm	10,05	10,03	10,04	9,95	9,98	9,94	9,95	9,97	10,01	9,97
205495	1K3D	Grad	32,00	30,00	31,00	31,00	31,00	31,00	31,00	31,00	31,00	30,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
205495	1K3D	Nm	10,02	9,94	10,05	10,09	10,04	9,89	9,89	10,15	10,04	10,02
205495	1K3D	Grad	32,00	31,00	33,00	31,00	31,00	30,00	30,00	31,00	30,00	30,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_h	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1K3D	Nom.val.	10,00
Ord. No.	1BD12T2O-A	Serial No.	205495	LSL	9,30
				USL	10,70
Remark	TQ 80% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
205495	1K3D	Nm	9,91	9,89	10,08	10,00	9,87	9,98	10,06	10,01	10,10	9,90
205495	1K3D	Grad	30,00	31,00	31,00	30,00	30,00	30,00	30,00	31,00	30,00	29,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
205495	1K3D	Nm	10,05	10,07	10,06	10,15	10,08	10,04	10,07	10,09	10,01	10,00
205495	1K3D	Grad	30,00	30,00	30,00	30,00	30,00	31,00	31,00	31,00	31,00	31,00

Torque graphs

Machine Capability Study 80 %

Model: **1BD-1B012A-1K3D-1VK3D**
Serial no: **755949**

Angle degree: **30°**
Test torque: **10,0 Nm**



Value no. 1
Graph
Torque / Angle / Speed



Value no. 1
Graph
Torque / Time / Speed



Value no. 100
Graph
Torque / Angle / Speed



Value no. 100
Graph
Torque / Time / Speed

Machine Capability Study
Control System

Page 1 / 1

Plant ATG Westhausen		Operator Name Sünder	Date 10.06.2022

Ord. No. 1BD12T2O-A	Part type 1BD-1B012A-1K3D-1ZB				Contr.item yes
Serial No. 755949_g	Char.Descr. VM1698-4	Nom.val.	10,00	0,70	USL 10,70
	Serial No. 1024210	Unit	Nm	-0,70	LSL 9,30
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2

Cust.Name Cleco	Reference System VM1698-4	Test Electronic MPRO400GCD-P
Contr.No. Homologation	Reference Transducer 10 / 1026388	nges. 100

Evaluation from 10.06.2022 13:35:42 to 10.06.2022 14:03:27

Rem. TQ 80% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;





Drawing Values		Collected Values		Statistics	
T_m	10.00			$\bar{x}$	9.9598
LSL	9.30	x_{min}	9.84	$\bar{x}$-3s	9.8629
USL	10.70	x_{max}	10.02	$\bar{x}$+3s	10.0567
T	1.40	R	0.18	6s	0.1937
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1.1.4 $\hat{\sigma}$ = S_{tot}
Potential Capability index	=	C_m	7.23
Critical capability index	=	C_{mk}	6.81

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\Appdata\QW\QWE\Messwert\2022\755949_gM.DFD

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_g	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	VM1698-4	Nom.val.	10,00
Ord. No.	1BD12T2O-A	Serial No.	1024210	LSL	9,30
				USL	10,70
Remark	TQ 80% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
1024210	VM1698-4	Nm	9,98	9,95	9,98	9,97	9,98	9,96	9,98	9,94	9,96	9,99
1024210	VM1698-4	Grad	357,50	357,75	357,25	359,25	356,00	361,25	360,75	357,50	361,25	367,50

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
1024210	VM1698-4	Nm	9,90	9,98	9,94	9,95	9,99	9,90	9,97	9,98	9,98	9,96
1024210	VM1698-4	Grad	349,75	370,50	355,50	357,25	357,50	357,50	362,00	360,00	366,00	362,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
1024210	VM1698-4	Nm	9,97	9,95	9,86	9,94	9,96	9,93	9,96	9,88	9,97	9,96
1024210	VM1698-4	Grad	364,75	367,00	357,75	364,50	365,50	348,00	357,75	355,00	363,75	360,75

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
1024210	VM1698-4	Nm	9,97	9,97	9,98	10,01	9,96	9,97	9,98	9,98	9,87	9,96
1024210	VM1698-4	Grad	356,75	358,50	361,50	367,25	365,25	366,75	367,50	366,75	345,50	357,25

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
1024210	VM1698-4	Nm	9,87	9,99	9,99	9,95	9,97	10,00	9,98	9,99	9,98	9,98
1024210	VM1698-4	Grad	353,50	358,25	361,25	359,00	358,00	364,00	361,75	364,50	365,00	363,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
1024210	VM1698-4	Nm	9,95	9,92	9,95	9,97	9,95	9,98	9,96	9,99	9,97	9,95
1024210	VM1698-4	Grad	362,75	347,00	358,50	357,50	361,75	359,50	359,00	360,25	359,00	359,75

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
1024210	VM1698-4	Nm	9,91	10,00	9,84	9,96	9,96	9,97	9,91	9,98	9,98	9,98
1024210	VM1698-4	Grad	360,25	367,00	357,25	366,00	353,75	360,50	354,25	363,00	362,50	359,25

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
1024210	VM1698-4	Nm	9,98	9,96	10,00	9,99	9,91	9,98	9,93	9,99	9,92	9,95
1024210	VM1698-4	Grad	359,00	359,75	363,25	366,50	359,00	362,75	360,75	355,50	359,75	357,00

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_g	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	VM1698-4	Nom.val.	10,00
Ord. No.	1BD12T2O-A	Serial No.	1024210	LSL	9,30
				USL	10,70
Remark	TQ 80% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
1024210	VM1698-4	Nm	9,97	9,94	9,97	9,97	10,00	9,97	10,00	9,96	10,02	9,94
1024210	VM1698-4	Grad	359,50	351,50	359,50	363,25	362,25	360,75	366,00	367,25	367,75	367,25

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
1024210	VM1698-4	Nm	9,96	9,96	9,99	9,97	9,94	9,93	9,98	9,96	9,95	9,94
1024210	VM1698-4	Grad	374,25	356,50	358,75	363,00	358,00	357,75	363,25	362,00	362,00	364,00

Machine Capability Study
Tool System

Page 1 / 1

Plant	ATG Westhausen	Operator Name	Sünder
Date	10.06.2022		

Ord. No.	1BD12T2O-A	Part type	1BD-1B012A-1K3D-1ZB	Contr.item	yes
Serial No.	755949_g	Char.Descr.	1VK3D	Nom.val. 10,00 0,70	USL 10,70
		Serial No.	198080	Unit Nm -0,70	LSL 9,30
Char.Type	variable			Tolerance value 7 %	Decimal Pl. 2
Cust.Name	Cleco	Reference System	VM1698-4	Test Electronic	MPRO400GCD-P
Contr.No.	Homologation	Reference Transducer	10 / 1026388	nges.	100

Evaluation from 10.06.2022 13:35:43 to 10.06.2022 14:03:28

Rem. TQ 80% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;





Drawing Values		Collected Values		Statistics	
T_m	10.00			$\bar{x}$	10.0185
LSL	9.30	x_{min}	10.00	$\bar{x}$-3s	9.9725
USL	10.70	x_{max}	10.06	$\bar{x}$+3s	10.0645
T	1.40	R	0.06	6s	0.0920
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution		Normal Distribution	
Calculation method		M1 1.4 $\hat{\sigma}$ = S_{tot}	
Potential Capability index	=	C_m	15.22
Critical capability index	=	C_{mk}	14.82

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\Appdata\QW\QWE\Messwert\2022\755949_g1.DFD

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_g	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1VK3D	Nom.val.	10,00
Ord. No.	1BD12T2O-A	Serial No.	198080	LSL	9,30
				USL	10,70
Remark	TQ 80% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
198080	1VK3D	Nm	10,02	10,02	10,05	10,03	10,05	10,03	10,02	10,01	10,00	10,04
198080	1VK3D	Grad	359,00	359,00	359,00	361,00	358,00	367,00	362,00	361,00	365,00	369,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
198080	1VK3D	Nm	10,04	10,02	10,00	10,00	10,02	10,03	10,04	10,02	10,02	10,00
198080	1VK3D	Grad	358,00	374,00	359,00	360,00	358,00	365,00	364,00	361,00	367,00	364,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
198080	1VK3D	Nm	10,01	10,02	10,02	10,00	10,02	10,01	10,01	10,02	10,03	10,00
198080	1VK3D	Grad	366,00	371,00	368,00	368,00	372,00	351,00	360,00	362,00	365,00	362,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
198080	1VK3D	Nm	10,01	10,01	10,02	10,04	10,04	10,01	10,02	10,01	10,01	10,01
198080	1VK3D	Grad	358,00	359,00	365,00	370,00	367,00	368,00	370,00	370,00	352,00	359,00

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
198080	1VK3D	Nm	10,01	10,03	10,03	10,00	10,01	10,04	10,03	10,03	10,00	10,00
198080	1VK3D	Grad	360,00	361,00	364,00	362,00	360,00	366,00	367,00	366,00	366,00	368,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
198080	1VK3D	Nm	10,02	10,01	10,01	10,03	10,00	10,03	10,03	10,02	10,01	10,01
198080	1VK3D	Grad	367,00	352,00	360,00	360,00	366,00	361,00	361,00	361,00	361,00	362,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
198080	1VK3D	Nm	10,00	10,05	10,00	10,00	10,03	10,01	10,05	10,03	10,04	10,01
198080	1VK3D	Grad	366,00	368,00	365,00	368,00	359,00	361,00	360,00	366,00	364,00	364,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
198080	1VK3D	Nm	10,01	10,00	10,04	10,03	10,00	10,02	10,01	10,03	10,04	10,00
198080	1VK3D	Grad	360,00	362,00	364,00	368,00	364,00	365,00	364,00	358,00	367,00	358,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_g	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1VK3D	Nom.val.	10,00
Ord. No.	1BD12T2O-A	Serial No.	198080	LSL	9,30
				USL	10,70
Remark	TQ 80% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
198080	1VK3D	Nm	10,02	10,01	10,03	10,00	10,04	10,00	10,04	10,00	10,06	10,00
198080	1VK3D	Grad	365,00	357,00	361,00	365,00	368,00	362,00	368,00	368,00	370,00	370,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
198080	1VK3D	Nm	10,03	10,00	10,02	10,02	10,00	10,03	10,00	10,02	10,00	10,00
198080	1VK3D	Grad	376,00	358,00	360,00	365,00	360,00	365,00	366,00	367,00	368,00	366,00

Machine Capability Study
Tool System

Page 1 / 1

Plant ATG Westhausen		Operator Name Sünder	Date 10.06.2022

Ord. No. 1BD12T2O-A	Part type 1BD-1B012A-1K3D-1ZB				Contr.item yes
Serial No. 755949_g	Char.Descr. 1K3D	Nom.val.	10,00	0,70	USL 10,70
	Serial No. 205495	Unit	Nm	-0,70	LSL 9,30
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2

Cust.Name Cleco	Reference System VM1698-4	Test Electronic MPRO400GCD-P
Contr.No. Homologation	Reference Transducer 10 / 1026388	nges. 100

Evaluation from 10.06.2022 13:35:43 to 10.06.2022 14:03:28

Rem. TQ 80% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;





Drawing Values		Collected Values		Statistics	
T_m	10.00			$\bar{x}$	10.0253
LSL	9.30	x_{min}	9.85	$\bar{x}$-3s	9.8401
USL	10.70	x_{max}	10.13	$\bar{x}$+3s	10.2105
T	1.40	R	0.28	6s	0.3705
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1 1.4 $\hat{\sigma}$ = S_{tot}
Potential Capability index	=	C_m	3.78
Critical capability index	=	C_{mk}	3.64

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\Appdata\QW\QWE\Messwert\2022\755949_g2.DFD

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_g	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1K3D	Nom.val.	10,00
Ord. No.	1BD12T2O-A	Serial No.	205495	LSL	9,30
				USL	10,70
Remark	TQ 80% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
205495	1K3D	Nm	10,06	10,09	10,00	10,11	9,95	10,04	10,00	10,08	9,97	10,08
205495	1K3D	Grad	359,00	359,00	359,00	361,00	358,00	367,00	362,00	361,00	365,00	369,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
205495	1K3D	Nm	10,01	10,07	10,03	10,08	9,97	10,00	10,08	10,09	10,03	10,02
205495	1K3D	Grad	358,00	374,00	359,00	360,00	358,00	365,00	364,00	361,00	367,00	364,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
205495	1K3D	Nm	10,01	10,10	9,85	9,92	10,05	9,95	10,01	9,96	10,08	9,94
205495	1K3D	Grad	366,00	371,00	368,00	368,00	372,00	351,00	360,00	362,00	365,00	362,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
205495	1K3D	Nm	9,96	9,93	10,08	10,11	10,02	10,11	9,98	10,08	9,92	10,03
205495	1K3D	Grad	358,00	359,00	365,00	370,00	367,00	368,00	370,00	370,00	352,00	359,00

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
205495	1K3D	Nm	9,90	10,05	9,98	9,95	10,11	10,10	9,95	10,10	10,07	10,10
205495	1K3D	Grad	360,00	361,00	364,00	362,00	360,00	366,00	367,00	366,00	366,00	368,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
205495	1K3D	Nm	10,04	9,97	10,02	10,09	9,92	10,00	10,04	9,93	9,95	9,95
205495	1K3D	Grad	367,00	352,00	360,00	360,00	366,00	361,00	361,00	361,00	361,00	362,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
205495	1K3D	Nm	10,02	10,10	9,93	10,03	10,10	10,00	10,01	10,08	10,05	9,99
205495	1K3D	Grad	366,00	368,00	365,00	368,00	359,00	361,00	360,00	366,00	364,00	364,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
205495	1K3D	Nm	10,11	10,02	10,07	10,04	9,99	10,06	10,02	10,08	10,00	10,05
205495	1K3D	Grad	360,00	362,00	364,00	368,00	364,00	365,00	364,00	358,00	367,00	358,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_g	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1K3D	Nom.val.	10,00
Ord. No.	1BD12T2O-A	Serial No.	205495	LSL	9,30
				USL	10,70
Remark	TQ 80% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
205495	1K3D	Nm	10,01	9,88	10,13	10,08	10,13	9,92	10,06	10,04	10,02	10,07
205495	1K3D	Grad	365,00	357,00	361,00	365,00	368,00	362,00	368,00	368,00	370,00	370,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
205495	1K3D	Nm	10,04	9,98	10,11	10,01	10,01	10,01	10,00	10,10	10,04	10,07
205495	1K3D	Grad	376,00	358,00	360,00	365,00	360,00	365,00	366,00	367,00	368,00	366,00

Torque graphs

Model: **1BD-1B012A-1K3D-1VK3D**
Serial no: **755949**

Machine Capability Study 80 %
Angle degree: **360°**
Test torque: **10,0 Nm**



Value no. 1
Graph
Torque / Angle / Speed



Value no. 1
Graph
Torque / Time / Speed



Value no. 100
Graph
Torque / Angle / Speed



Value no. 100
Graph
Torque / Time / Speed

Test sheet no. 4

Machine Capability Study 100 %

Multi-stage tightening system	☑	Speed 50 rpm	1,6 %
Single-stage tightening system	☐	Speed 100 %	3152 rpm

Manufacturer: Apex Tool Group Serial no: **755949**

Test torque: Tq max. 12,00 Nm

Hard joint (H)	72,15 Nm / Revolution	Angle degree	30°
Soft joint (L)	5,97 Nm / Revolution	Angle degree	360°

		H	L
a)	Tolerance down / up	11,16 - 12,84 Nm	11,16 - 12,84 Nm
	Tolerance down / up	7 %	7 %
	Average torque	12,03 Nm	11,94 Nm
	Standard deviation	0,06 Nm	0,04 Nm
	Torque scatter (99,73%)	0,33 Nm	0,25 Nm
	C_m	5,08	6,67
	C_{mk}	4,92	6,19

b)	Min. C_m hard/soft (lowest value)	5,08
	Min. C_{mk} hard/soft (lowest value)	4,92

Capability is reached if minimum C_{mk} value ≥1.67

Note:

Machine Capability Study
Control System

Cleco Production Tools

Plant	ATG Westhausen	Operator Name	Sünder
Date	13.06.2022		

Ord. No.	1BD12T2O-A	Part type	1BD-1B012A-1K3D-1ZB	Contr.item	yes
Serial No.	755949_b	Char.Descr.	VM1698-4	Nom.val.	12,00
		Serial No.	1024210	Unit	Nm
				USL	12,84
				LSL	11,16
					0,84
					-0,84
Char.Type	variable			Tolerance value	7 %
Decimal Pl.	2				

Cust.Name	Cleco	Reference System	VM1698-4	Test Electronic	MPRO400GCD-P
Contr.No.	Homologation	Reference Transducer	50 / 1024729	nges.	100

Evaluation from 13.06.2022 07:53:22 to 13.06.2022 08:07:36

Rem. TQ 100% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;





Drawing Values		Collected Values		Statistics	
T_m	12.00			$\bar{x}$	12.0257
LSL	11.16	x_{min}	11.91	$\bar{x}$-3s	11.8602
USL	12.84	x_{max}	12.14	$\bar{x}$+3s	12.1912
T	1.68	R	0.23	6s	0.3310
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1 1.4 $\hat{\sigma}$ = S_{tot}
Potential Capability index	=	C_m	5.08
Critical capability index	=	C_{mk}	4.92

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_b	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	VM1698-4	Nom.val.	12,00
Ord. No.	1BD12T2O-A	Serial No.	1024210	LSL	11,16
				USL	12,84
Remark	TQ 100% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
1024210	VM1698-4	Nm	12,01	11,97	12,11	12,09	11,99	11,93	12,10	12,06	11,97	12,08
1024210	VM1698-4	Grad	31,00	30,00	30,50	31,00	29,75	29,75	30,00	30,75	30,50	30,50

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
1024210	VM1698-4	Nm	12,05	12,01	12,00	12,04	11,91	11,97	11,99	12,07	11,95	11,97
1024210	VM1698-4	Grad	30,00	30,25	30,25	31,00	30,25	30,00	30,50	31,00	30,50	30,25

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
1024210	VM1698-4	Nm	12,08	12,11	11,98	11,96	12,06	11,92	12,11	12,05	12,06	11,99
1024210	VM1698-4	Grad	30,50	30,50	30,00	30,00	30,50	29,75	31,00	31,00	31,25	30,50

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
1024210	VM1698-4	Nm	12,07	12,04	11,95	12,11	12,00	11,98	12,08	12,12	11,99	11,96
1024210	VM1698-4	Grad	29,75	30,25	29,75	29,75	30,25	29,75	30,50	30,25	29,75	29,75

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
1024210	VM1698-4	Nm	12,08	11,98	12,01	11,97	12,06	11,96	11,98	11,98	12,09	12,00
1024210	VM1698-4	Grad	29,75	30,00	30,00	29,75	29,25	30,00	30,00	29,75	29,75	30,25

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
1024210	VM1698-4	Nm	12,05	12,02	11,95	12,05	12,05	11,98	12,01	12,03	12,04	12,12
1024210	VM1698-4	Grad	29,75	30,00	29,25	29,50	29,75	29,50	30,00	29,25	29,75	29,50

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
1024210	VM1698-4	Nm	12,09	12,07	12,00	11,98	12,14	12,09	12,09	12,08	12,02	12,02
1024210	VM1698-4	Grad	30,25	30,50	29,75	30,50	29,75	30,25	30,00	29,25	29,75	29,50

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
1024210	VM1698-4	Nm	12,00	12,06	12,03	12,02	11,98	11,94	12,07	11,99	12,02	11,99
1024210	VM1698-4	Grad	29,75	30,00	30,00	29,25	29,50	29,50	30,00	29,75	29,50	29,75

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_b	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	VM1698-4	Nom.val.	12,00
Ord. No.	1BD12T2O-A	Serial No.	1024210	LSL	11,16
				USL	12,84
Remark	TQ 100% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
1024210	VM1698-4	Nm	12,05	12,10	12,09	11,94	12,02	12,12	11,98	12,08	11,98	12,07
1024210	VM1698-4	Grad	29,50	29,75	30,00	29,75	29,00	29,25	29,25	30,00	29,75	29,50

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
1024210	VM1698-4	Nm	11,98	12,12	12,00	11,99	11,98	11,92	12,03	12,10	12,00	12,04
1024210	VM1698-4	Grad	29,50	29,75	29,25	29,25	30,25	30,00	30,75	30,25	30,75	30,50

Machine Capability Study
Tool System

Page 1 / 1

Plant	ATG Westhausen	Operator Name	Sünder
Date	13.06.2022		

Ord. No.	1BD12T2O-A	Part type	1BD-1B012A-1K3D-1ZB	Contr.item	yes
Serial No.	755949_b	Char.Descr.	1VK3D	Nom.val. 12,00 0,84	USL 12,84
		Serial No.	198080	Unit Nm -0,84	LSL 11,16
Char.Type	variable			Tolerance value 7 %	Decimal Pl. 2
Cust.Name	Cleco	Reference System	VM1698-4	Test Electronic	MPRO400GCD-P
Contr.No.	Homologation	Reference Transducer	50 / 1024729	nges.	100

Evaluation from 13.06.2022 07:53:23 to 13.06.2022 08:07:37

Rem. TQ 100% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;





Drawing Values		Collected Values		Statistics	
T_m	12.00			$\bar{x}$	12.1150
LSL	11.16	x_{min}	12.04	$\bar{x}$-3s	12.0501
USL	12.84	x_{max}	12.17	$\bar{x}$+3s	12.1799
T	1.68	R	0.13	6s	0.1298
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1 1.4 $\hat{\sigma}$ = S_{tot}
Potential Capability index	=	C_m	12.95
Critical capability index	=	C_{mk}	11.17

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\Appdata\QW\QWE\Messwert\2022\755949_b1.DFD

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_b	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1VK3D	Nom.val.	12,00
Ord. No.	1BD12T2O-A	Serial No.	198080	LSL	11,16
				USL	12,84
Remark	TQ 100% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
198080	1VK3D	Nm	12,12	12,12	12,11	12,11	12,11	12,11	12,12	12,08	12,13	12,15
198080	1VK3D	Grad	31,00	30,00	30,00	31,00	30,00	30,00	30,00	30,00	30,00	30,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
198080	1VK3D	Nm	12,11	12,12	12,11	12,13	12,07	12,09	12,12	12,09	12,08	12,14
198080	1VK3D	Grad	30,00	30,00	30,00	31,00	30,00	30,00	30,00	31,00	31,00	30,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
198080	1VK3D	Nm	12,14	12,13	12,10	12,11	12,14	12,08	12,11	12,12	12,10	12,12
198080	1VK3D	Grad	30,00	30,00	30,00	30,00	30,00	30,00	31,00	31,00	31,00	30,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
198080	1VK3D	Nm	12,11	12,16	12,09	12,12	12,09	12,11	12,13	12,14	12,14	12,12
198080	1VK3D	Grad	29,00	30,00	30,00	30,00	30,00	30,00	30,00	30,00	29,00	30,00

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
198080	1VK3D	Nm	12,11	12,10	12,11	12,09	12,10	12,13	12,12	12,08	12,10	12,12
198080	1VK3D	Grad	30,00	30,00	30,00	29,00	29,00	30,00	30,00	30,00	30,00	30,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
198080	1VK3D	Nm	12,10	12,13	12,12	12,12	12,12	12,12	12,14	12,14	12,13	12,12
198080	1VK3D	Grad	30,00	30,00	29,00	29,00	30,00	29,00	29,00	29,00	29,00	30,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
198080	1VK3D	Nm	12,11	12,10	12,14	12,14	12,11	12,13	12,10	12,12	12,09	12,14
198080	1VK3D	Grad	30,00	30,00	29,00	30,00	30,00	30,00	30,00	29,00	29,00	30,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
198080	1VK3D	Nm	12,10	12,14	12,09	12,12	12,12	12,09	12,08	12,13	12,11	12,14
198080	1VK3D	Grad	29,00	30,00	29,00	29,00	29,00	29,00	30,00	29,00	29,00	30,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_b	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1VK3D	Nom.val.	12,00
Ord. No.	1BD12T2O-A	Serial No.	198080	LSL	11,16
				USL	12,84
Remark	TQ 100% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
198080	1VK3D	Nm	12,10	12,13	12,14	12,04	12,11	12,16	12,13	12,13	12,13	12,12
198080	1VK3D	Grad	29,00	30,00	30,00	30,00	29,00	29,00	29,00	30,00	29,00	29,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
198080	1VK3D	Nm	12,12	12,14	12,12	12,10	12,09	12,07	12,08	12,17	12,11	12,13
198080	1VK3D	Grad	29,00	30,00	29,00	29,00	30,00	30,00	30,00	30,00	31,00	30,00

Machine Capability Study
Tool System

Page 1 / 1

Plant	ATG Westhausen	Operator Name	Sünder
Date	13.06.2022		

Ord. No.	1BD12T2O-A	Part type	1BD-1B012A-1K3D-1ZB	Contr.item	yes
Serial No.	755949_b	Char.Descr.	1K3D	Nom.val. 12,00	0,84 USL 12,84
		Serial No.	205495	Unit Nm	-0,84 LSL 11,16
Char.Type	variable			Tolerance value 7 %	Decimal Pl. 2
Cust.Name	Cleco	Reference System	VM1698-4	Test Electronic	MPRO400GCD-P
Contr.No.	Homologation	Reference Transducer	50 / 1024729	nges.	100

Evaluation from 13.06.2022 07:53:23 to 13.06.2022 08:07:37

Rem. TQ 100% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;





Drawing Values		Collected Values		Statistics	
T_m	12.00			$\bar{x}$	12.0059
LSL	11.16	x_{min}	11.86	$\bar{x}$-3s	11.7643
USL	12.84	x_{max}	12.19	$\bar{x}$+3s	12.2475
T	1.68	R	0.33	6s	0.4833
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1 1.4 $\hat{\sigma}$ = S_{tot}
Potential Capability index	=	C_m	3.48
Critical capability index	=	C_{mk}	3.45

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\Appdata\QW\QWE\Messwert\2022\755949_b2.DFD

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_b	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1K3D	Nom.val.	12,00
Ord. No.	1BD12T2O-A	Serial No.	205495	LSL	11,16
				USL	12,84
Remark	TQ 100% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
205495	1K3D	Nm	11,90	11,87	12,13	11,95	11,89	11,93	12,01	11,97	11,88	12,04
205495	1K3D	Grad	31,00	30,00	30,00	31,00	30,00	30,00	30,00	30,00	30,00	30,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
205495	1K3D	Nm	12,08	12,00	11,90	12,08	11,91	12,01	11,89	11,96	11,96	11,99
205495	1K3D	Grad	30,00	30,00	30,00	31,00	30,00	30,00	30,00	31,00	31,00	30,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
205495	1K3D	Nm	12,06	11,97	11,88	11,93	11,99	12,00	12,08	12,11	12,04	12,05
205495	1K3D	Grad	30,00	30,00	30,00	30,00	30,00	30,00	31,00	31,00	31,00	30,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
205495	1K3D	Nm	12,01	12,07	11,91	12,14	11,98	11,86	12,06	12,13	11,94	11,89
205495	1K3D	Grad	29,00	30,00	30,00	30,00	30,00	30,00	30,00	30,00	29,00	30,00

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
205495	1K3D	Nm	12,15	11,88	11,94	12,01	12,06	12,00	11,88	11,94	11,99	12,02
205495	1K3D	Grad	30,00	30,00	30,00	29,00	29,00	30,00	30,00	30,00	30,00	30,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
205495	1K3D	Nm	12,06	11,91	11,93	12,06	11,99	11,94	12,03	12,02	11,95	12,15
205495	1K3D	Grad	30,00	30,00	29,00	29,00	30,00	29,00	29,00	29,00	29,00	30,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
205495	1K3D	Nm	11,96	12,06	11,98	12,02	12,02	12,03	12,08	12,13	11,99	12,10
205495	1K3D	Grad	30,00	30,00	29,00	30,00	30,00	30,00	30,00	29,00	29,00	30,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
205495	1K3D	Nm	11,95	12,14	11,97	12,07	11,91	12,05	12,01	12,01	12,07	11,98
205495	1K3D	Grad	29,00	30,00	29,00	29,00	29,00	29,00	30,00	29,00	29,00	30,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_b	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1K3D	Nom.val.	12,00
Ord. No.	1BD12T2O-A	Serial No.	205495	LSL	11,16
				USL	12,84
Remark	TQ 100% hard +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
205495	1K3D	Nm	12,05	12,14	12,19	11,92	11,91	12,06	12,00	12,19	12,04	12,05
205495	1K3D	Grad	29,00	30,00	30,00	30,00	29,00	29,00	29,00	30,00	29,00	29,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
205495	1K3D	Nm	11,99	12,19	11,96	11,93	12,01	11,89	12,06	12,10	11,99	12,03
205495	1K3D	Grad	29,00	30,00	29,00	29,00	30,00	30,00	30,00	30,00	31,00	30,00

Torque graphs

Machine Capability Study 100 %

Model: **1BD-1B012A-1K3D-1VK3D**
Serial no: **755949**

Angle degree: **30°**
Test torque: **12,0 Nm**



Value no. 1
Graph
Torque / Angle / Speed



Value no. 1
Graph
Torque / Time / Speed



Value no. 100
Graph
Torque / Angle / Speed



Value no. 100
Graph
Torque / Time / Speed

Machine Capability Study
Control System

Cleco Production Tools

Plant ATG Westhausen		Operator Name Sünder	Date 10.06.2022

Ord. No. 1BD12T2O-A	Part type 1BD-1B012A-1K3D-1ZB				Contr.item yes
Serial No. 755949_a	Char.Descr. VM1698-4	Nom.val.	12,00	0,84	USL 12,84
	Serial No. 1024210	Unit	Nm	-0,84	LSL 11,16
Char.Type variable		Tolerance value	7 %		Decimal Pl. 2
Cust.Name Cleco	Reference System VM1698-4	Test Electronic MPRO400GCD-P			
Contr.No. Homologation	Reference Transducer 50 / 1024729	nges. 100			

Evaluation from 10.06.2022 14:45:05 to 10.06.2022 15:44:04

Rem. TQ 100% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;





Drawing Values		Collected Values		Statistics	
T_m	12.00			$\bar{x}$	11.9394
LSL	11.16	x_{min}	11.87	$\bar{x}$-3s	11.8135
USL	12.84	x_{max}	12.03	$\bar{x}$+3s	12.0653
T	1.68	R	0.16	6s	0.2518
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1.1.4 $\hat{\sigma} = S_{tot}$
Potential Capability index	=	C_m	6.67
Critical capability index	=	C_{mk}	6.19

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_a	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	VM1698-4	Nom.val.	12,00
Ord. No.	1BD12T2O-A	Serial No.	1024210	LSL	11,16
				USL	12,84
Remark	TQ 100% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
1024210	VM1698-4	Nm	11,99	11,95	11,99	11,99	11,99	11,99	11,90	12,01	11,96	11,93
1024210	VM1698-4	Grad	346,00	320,25	336,00	328,50	335,50	318,00	314,25	344,00	336,25	324,25

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
1024210	VM1698-4	Nm	11,89	11,96	11,92	11,91	12,01	12,01	11,87	11,90	11,95	11,99
1024210	VM1698-4	Grad	312,75	334,00	317,00	318,25	341,25	336,25	312,75	320,75	354,00	367,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
1024210	VM1698-4	Nm	11,97	11,97	11,95	11,97	11,89	11,96	11,91	11,94	11,99	12,00
1024210	VM1698-4	Grad	349,25	359,00	358,00	353,50	313,50	328,00	337,50	359,00	372,50	369,75

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
1024210	VM1698-4	Nm	11,99	12,01	11,90	11,99	11,92	11,94	11,91	11,98	11,87	11,92
1024210	VM1698-4	Grad	363,50	363,00	347,25	353,75	345,75	362,00	337,75	367,75	330,00	359,25

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
1024210	VM1698-4	Nm	11,89	11,90	11,92	11,93	11,92	11,88	11,97	11,92	11,91	11,92
1024210	VM1698-4	Grad	336,00	350,25	357,25	361,50	357,75	362,25	365,75	359,00	359,50	365,25

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
1024210	VM1698-4	Nm	11,90	11,99	12,00	12,00	11,95	11,96	11,88	11,94	11,99	11,96
1024210	VM1698-4	Grad	356,50	375,50	379,50	368,50	365,50	361,75	337,00	373,50	397,75	367,25

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
1024210	VM1698-4	Nm	11,88	11,88	11,90	11,90	11,97	11,96	11,94	11,95	11,89	11,89
1024210	VM1698-4	Grad	344,00	354,25	356,00	357,50	367,75	366,75	368,00	368,00	353,25	373,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
1024210	VM1698-4	Nm	11,89	11,88	11,98	11,97	11,99	11,97	11,88	11,87	11,98	11,91
1024210	VM1698-4	Grad	364,00	339,25	369,75	370,50	376,50	363,25	343,50	363,00	388,25	368,50

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_a	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	VM1698-4	Nom.val.	12,00
Ord. No.	1BD12T2O-A	Serial No.	1024210	LSL	11,16
				USL	12,84
Remark	TQ 100% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
1024210	VM1698-4	Nm	12,03	11,91	11,92	11,96	11,92	11,87	11,92	11,92	11,94	11,97
1024210	VM1698-4	Grad	391,00	356,00	359,50	364,50	368,75	334,25	347,00	353,50	348,25	387,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
1024210	VM1698-4	Nm	11,94	11,91	11,95	11,89	11,96	12,00	11,90	11,94	11,89	11,90
1024210	VM1698-4	Grad	359,75	353,75	359,25	345,00	369,25	369,50	365,25	347,75	364,00	349,25

Machine Capability Study
Tool System

Page 1 / 1

Plant	ATG Westhausen	Operator Name	Sünder
Date	10.06.2022		

Ord. No.	1BD12T2O-A	Part type	1BD-1B012A-1K3D-1ZB	Contr.item	yes
Serial No.	755949_a	Char.Descr.	1VK3D	Nom.val. 12,00 0,84	USL 12,84
		Serial No.	198080	Unit Nm -0,84	LSL 11,16
Char.Type	variable			Tolerance value 7 %	Decimal Pl. 2
Cust.Name	Cleco	Reference System	VM1698-4	Test Electronic	MPRO400GCD-P
Contr.No.	Homologation	Reference Transducer	50 / 1024729	nges.	100

Evaluation from 10.06.2022 14:45:06 to 10.06.2022 15:44:05

Rem. TQ 100% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;







Drawing Values		Collected Values		Statistics	
T_m	12.00			$\bar{x}$	12.0170
LSL	11.16	x_{min}	12.00	$\bar{x}$-3s	11.9642
USL	12.84	x_{max}	12.07	$\bar{x}$+3s	12.0698
T	1.68	R	0.07	6s	0.1057
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1.1.4 $\hat{\sigma} = S_{tot}$
Potential Capability index	=	C_m	15.90
Critical capability index	=	C_{mk}	15.58

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_a	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1VK3D	Nom.val.	12,00
Ord. No.	1BD12T2O-A	Serial No.	198080	LSL	11,16
				USL	12,84
Remark	TQ 100% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
198080	1VK3D	Nm	12,00	12,02	12,01	12,00	12,00	12,02	12,00	12,04	12,03	12,04
198080	1VK3D	Grad	346,00	320,00	337,00	326,00	334,00	318,00	317,00	344,00	337,00	328,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
198080	1VK3D	Nm	12,00	12,00	12,00	12,01	12,00	12,07	12,03	12,03	12,04	12,00
198080	1VK3D	Grad	309,00	335,00	320,00	322,00	341,00	334,00	315,00	325,00	354,00	364,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
198080	1VK3D	Nm	12,02	12,01	12,00	12,00	12,02	12,00	12,01	12,01	12,00	12,05
198080	1VK3D	Grad	347,00	359,00	358,00	355,00	315,00	327,00	339,00	361,00	367,00	369,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
198080	1VK3D	Nm	12,01	12,05	12,03	12,02	12,07	12,00	12,00	12,01	12,02	12,00
198080	1VK3D	Grad	363,00	363,00	349,00	354,00	352,00	363,00	339,00	367,00	335,00	361,00

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
198080	1VK3D	Nm	12,01	12,02	12,04	12,00	12,01	12,01	12,06	12,03	12,04	12,03
198080	1VK3D	Grad	338,00	354,00	358,00	361,00	363,00	364,00	367,00	360,00	363,00	366,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
198080	1VK3D	Nm	12,02	12,04	12,02	12,02	12,03	12,00	12,03	12,00	12,03	12,01
198080	1VK3D	Grad	359,00	375,00	378,00	363,00	366,00	357,00	341,00	373,00	400,00	367,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
198080	1VK3D	Nm	12,00	12,00	12,00	12,00	12,01	12,01	12,02	12,00	12,01	12,00
198080	1VK3D	Grad	352,00	363,00	366,00	358,00	367,00	365,00	374,00	364,00	357,00	375,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
198080	1VK3D	Nm	12,00	12,03	12,02	12,03	12,01	12,01	12,01	12,00	12,01	12,03
198080	1VK3D	Grad	376,00	347,00	374,00	368,00	375,00	363,00	348,00	365,00	388,00	370,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_a	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1VK3D	Nom.val.	12,00
Ord. No.	1BD12T2O-A	Serial No.	198080	LSL	11,16
				USL	12,84
Remark	TQ 100% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
198080	1VK3D	Nm	12,05	12,02	12,02	12,00	12,00	12,01	12,03	12,00	12,00	12,05
198080	1VK3D	Grad	387,00	363,00	361,00	364,00	369,00	338,00	353,00	352,00	349,00	386,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
198080	1VK3D	Nm	12,00	12,02	12,02	12,02	12,06	12,03	12,01	12,04	12,00	12,00
198080	1VK3D	Grad	363,00	355,00	361,00	348,00	372,00	367,00	368,00	350,00	368,00	355,00

Machine Capability Study
Tool System

Page 1 / 1

Plant	ATG Westhausen	Operator Name	Sünder
Date	10.06.2022		

Ord. No.	1BD12T2O-A	Part type	1BD-1B012A-1K3D-1ZB	Contr.item	yes
Serial No.	755949_a	Char.Descr.	1K3D	Nom.val. 12,00	0,84 USL 12,84
		Serial No.	205495	Unit Nm	-0,84 LSL 11,16
Char.Type	variable			Tolerance value 7 %	Decimal Pl. 2
Cust.Name	Cleco	Reference System	VM1698-4	Test Electronic	MPRO400GCD-P
Contr.No.	Homologation	Reference Transducer	50 / 1024729	nges.	100

Evaluation from 10.06.2022 14:45:06 to 10.06.2022 15:44:05

Rem. TQ 100% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;





Drawing Values		Collected Values		Statistics	
T_m	12.00			$\bar{x}$	11.9492
LSL	11.16	x_{min}	11.80	$\bar{x}$-3s	11.7273
USL	12.84	x_{max}	12.13	$\bar{x}$+3s	12.1711
T	1.68	R	0.33	6s	0.4438
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution		Normal Distribution	
Calculation method		M1 1.4 $\hat{\sigma}$ = S_{tot}	
Potential Capability index	=	C_m	3.79
Critical capability index	=	C_{mk}	3.56

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\Appdata\QW\QWE\Messwert\2022\755949_a2.DFD

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_a	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1K3D	Nom.val.	12,00
Ord. No.	1BD12T2O-A	Serial No.	205495	LSL	11,16
				USL	12,84
Remark	TQ 100% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
205495	1K3D	Nm	11,91	12,00	11,99	11,96	12,05	11,92	11,91	12,09	12,01	11,86
205495	1K3D	Grad	346,00	320,00	337,00	326,00	334,00	318,00	317,00	344,00	337,00	328,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
205495	1K3D	Nm	11,93	11,90	11,89	11,92	12,00	11,96	11,91	11,88	12,08	12,05
205495	1K3D	Grad	309,00	335,00	320,00	322,00	341,00	334,00	315,00	325,00	354,00	364,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
205495	1K3D	Nm	12,06	12,04	11,98	11,92	11,96	12,07	11,81	11,91	11,95	12,13
205495	1K3D	Grad	347,00	359,00	358,00	355,00	315,00	327,00	339,00	361,00	367,00	369,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
205495	1K3D	Nm	12,02	12,08	11,95	12,08	12,07	12,00	11,95	11,96	11,85	11,84
205495	1K3D	Grad	363,00	363,00	349,00	354,00	352,00	363,00	339,00	367,00	335,00	361,00

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
205495	1K3D	Nm	11,86	11,91	11,85	11,91	11,99	11,92	12,04	11,89	11,98	11,89
205495	1K3D	Grad	338,00	354,00	358,00	361,00	363,00	364,00	367,00	360,00	363,00	366,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
205495	1K3D	Nm	11,94	11,98	11,96	12,13	11,98	11,92	11,91	11,89	11,96	11,96
205495	1K3D	Grad	359,00	375,00	378,00	363,00	366,00	357,00	341,00	373,00	400,00	367,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
205495	1K3D	Nm	11,84	11,94	11,87	11,87	11,93	11,99	11,93	12,02	11,95	11,80
205495	1K3D	Grad	352,00	363,00	366,00	358,00	367,00	365,00	374,00	364,00	357,00	375,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
205495	1K3D	Nm	11,82	11,90	11,89	11,96	11,97	12,04	11,90	11,89	11,94	11,87
205495	1K3D	Grad	376,00	347,00	374,00	368,00	375,00	363,00	348,00	365,00	388,00	370,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 10.06.2022

Serial No.	755949_a	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1K3D	Nom.val.	12,00
Ord. No.	1BD12T2O-A	Serial No.	205495	LSL	11,16
				USL	12,84
Remark	TQ 100% soft +/-7% * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 1000/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
205495	1K3D	Nm	12,09	11,91	11,89	11,94	11,96	11,95	11,87	11,97	12,01	12,08
205495	1K3D	Grad	387,00	363,00	361,00	364,00	369,00	338,00	353,00	352,00	349,00	386,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
205495	1K3D	Nm	11,90	11,87	11,90	11,95	11,98	12,04	11,99	11,84	11,90	11,84
205495	1K3D	Grad	363,00	355,00	361,00	348,00	372,00	367,00	368,00	350,00	368,00	355,00

Torque graphs

Machine Capability Study 100 %

Model: **1BD-1B012A-1K3D-1VK3D**
Serial no: **755949**

Angle degree: **360°**
Test torque: **12,0 Nm**



Value no. 1
Graph
Torque / Angle / Speed



Value no. 1
Graph
Torque / Time / Speed



Value no. 100
Graph
Torque / Angle / Speed



Value no. 100
Graph
Torque / Time / Speed

General Specifications

Manufacturer: Apex Tool Group **Tool type:** Fixtured Spindle

Model: 1BD-1B012A-1K3D-1VK3D **Serial no:** 755949

Torque range: **2 Nm to 12 Nm**

Difference evaluation: Reference/Tool at 40° / 60 %

Capability examination

Snugfit value: 2,4 Nm **Torque tolerance ±** 7 %

Target torque: 7,2 Nm Tolerance: 3,98 % ± **1,99 %**

Angle degree: 40° Tolerance: 1,8° ± **0,9°**

Formula derivation: $C_m = \frac{T}{6\,s}$ $T = C_m * 6\,s$

Tool without angle correction

Measurement	Tool data		Control data		Difference	
No.	Torque	Angle	Torque	Angle	Torque	Angle
1	7,41	40,00	7,24	39,25	0,17	0,75
2	7,38	40,00	7,21	39,50	0,17	0,50
3	7,39	40,00	7,22	39,25	0,17	0,75
4	7,38	40,00	7,22	39,50	0,16	0,50
5	7,46	40,00	7,30	39,25	0,16	0,75
6	7,48	40,00	7,31	39,50	0,17	0,50
7	7,40	40,00	7,24	39,25	0,16	0,75
8	7,40	40,00	7,24	39,50	0,16	0,50
9	7,44	40,00	7,27	39,25	0,17	0,75
10	7,46	40,00	7,31	39,50	0,15	0,50
11	7,41	40,00	7,26	39,25	0,15	0,75
12	7,37	40,00	7,25	39,50	0,12	0,50
13	7,41	40,00	7,26	39,50	0,15	0,50
14	7,40	40,00	7,25	39,25	0,15	0,75
15	7,43	40,00	7,28	39,50	0,15	0,50
16	7,41	40,00	7,24	39,25	0,17	0,75
17	7,47	40,00	7,29	39,25	0,18	0,75
18	7,46	40,00	7,31	39,25	0,15	0,75
19	7,48	40,00	7,32	39,25	0,16	0,75
20	7,42	40,00	7,27	39,25	0,15	0,75
21	7,46	40,00	7,29	39,25	0,17	0,75
22	7,41	40,00	7,26	39,50	0,15	0,50
23	7,39	40,00	7,27	39,50	0,12	0,50
24	7,39	40,00	7,25	39,50	0,14	0,50
25	7,42	40,00	7,32	39,75	0,10	0,25
26	7,53	40,00	7,39	39,50	0,14	0,50
27	7,40	40,00	7,34	39,75	0,06	0,25
28	7,42	40,00	7,31	39,50	0,11	0,50
29	7,47	40,00	7,31	39,25	0,16	0,75
30	7,42	40,00	7,25	39,25	0,17	0,75
31	7,42	40,00	7,29	39,25	0,13	0,75
32	7,45	40,00	7,32	39,50	0,13	0,50
33	7,45	40,00	7,32	39,50	0,13	0,50
34	7,41	40,00	7,26	39,25	0,15	0,75
35	7,41	40,00	7,27	39,50	0,14	0,50
36	7,44	40,00	7,33	39,75	0,11	0,25
37	7,38	40,00	7,32	39,50	0,06	0,50
38	7,45	40,00	7,30	39,00	0,15	1,00
39	7,44	40,00	7,29	39,25	0,15	0,75
40	7,47	40,00	7,32	39,25	0,15	0,75
41	7,45	40,00	7,30	39,50	0,15	0,50
42	7,43	40,00	7,31	39,50	0,12	0,50
43	7,46	40,00	7,31	39,25	0,15	0,75
44	7,40	40,00	7,28	39,25	0,12	0,75
45	7,42	40,00	7,28	39,25	0,14	0,75
46	7,44	40,00	7,30	39,25	0,14	0,75
47	7,38	40,00	7,25	39,25	0,13	0,75
48	7,43	40,00	7,30	39,25	0,13	0,75
49	7,43	40,00	7,30	39,50	0,13	0,50
50	7,42	40,00	7,29	39,25	0,13	0,75
51	7,44	40,00	7,32	39,50	0,12	0,50
52	7,44	40,00	7,30	39,50	0,14	0,50
53	7,44	40,00	7,32	39,50	0,12	0,50
54	7,48	40,00	7,34	39,75	0,14	0,25
55	7,43	40,00	7,35	39,50	0,08	0,50
56	7,45	40,00	7,32	39,25	0,13	0,75
57	7,49	40,00	7,33	39,25	0,16	0,75
58	7,47	40,00	7,40	39,75	0,07	0,25
59	7,37	40,00	7,23	39,25	0,14	0,75
60	7,38	40,00	7,23	39,50	0,15	0,50
61	7,34	40,00	7,17	39,25	0,17	0,75
62	7,34	40,00	7,20	39,50	0,14	0,50
63	7,38	40,00	7,23	39,25	0,15	0,75
64	7,34	40,00	7,20	39,50	0,14	0,50
65	7,35	40,00	7,21	39,50	0,14	0,50
66	7,33	40,00	7,22	39,50	0,11	0,50
67	7,30	40,00	7,21	39,50	0,09	0,50
68	7,26	40,00	7,21	39,50	0,05	0,50
69	7,37	40,00	7,25	39,00	0,12	1,00
70	7,37	40,00	7,21	39,25	0,16	0,75
71	7,40	40,00	7,24	39,25	0,16	0,75
72	7,34	40,00	7,18	39,25	0,16	0,75
73	7,34	40,00	7,18	39,25	0,16	0,75
74	7,36	40,00	7,25	39,75	0,11	0,25
75	7,35	40,00	7,23	39,50	0,12	0,50
76	7,34	40,00	7,22	39,50	0,12	0,50
77	7,38	40,00	7,25	39,50	0,13	0,50
78	7,42	40,00	7,28	39,75	0,14	0,25
79	7,35	40,00	7,24	39,75	0,11	0,25
80	7,33	40,00	7,22	39,50	0,11	0,50
81	7,34	40,00	7,22	39,75	0,12	0,25
82	7,32	40,00	7,21	39,50	0,11	0,50
83	7,32	40,00	7,22	39,75	0,10	0,25
84	7,38	40,00	7,28	39,25	0,10	0,75
85	7,35	40,00	7,18	39,25	0,17	0,75
86	7,31	40,00	7,18	39,25	0,13	0,75
87	7,31	40,00	7,25	39,75	0,06	0,25
88	7,38	40,00	7,24	39,25	0,14	0,75
89	7,32	40,00	7,17	39,25	0,15	0,75
90	7,36	40,00	7,30	39,75	0,06	0,25
91	7,35	40,00	7,22	39,25	0,13	0,75
92	7,36	40,00	7,20	39,50	0,16	0,50
93	7,42	40,00	7,27	39,50	0,15	0,50
94	7,32	40,00	7,19	39,50	0,13	0,50
95	7,38	40,00	7,24	39,50	0,14	0,50
96	7,35	40,00	7,25	39,50	0,10	0,50
97	7,29	40,00	7,20	39,25	0,09	0,75
98	7,39	40,00	7,23	39,50	0,16	0,50
99	7,41	40,00	7,24	39,25	0,17	0,75
100	7,36	40,00	7,23	39,50	0,13	0,50
				Standard deviation:	**0,029**	**0,179**

Graphical representation

Model:	**1BD-1B012A-1K3D-1VK3D**	Serial no:	**755949**
Target torque:	**7,20 Nm**	60 % of max. torque	
Angle degree:	**40°**	Tool without angle correction	





Machine Capability Study
Control System

Cleco Production Tools

Plant	ATG Westhausen	Operator Name	Sünder
Date	13.06.2022		

Ord. No.	1BD12T2O-A	Part type	1BD-1B012A-1K3D-1ZB	Contr.item	yes
Serial No.	755949_k	Char.Descr.	VM1698-4	Nom.val. 40,00 5,00	USL 45,00
		Serial No.	1024210	Unit Grad -5,00	LSL 35,00
Char.Type	variable			Tolerance value 12 %	Decimal Pl. 2
Cust.Name	Cleco	Reference System	VM1698-4	Test Electronic	MPRO400GCD-P
Contr.No.	Homologation	Reference Transducer	10 / 1026388	nges.	100

Evaluation from 13.06.2022 08:39:42 to 13.06.2022 08:53:56

Rem. TQ 60% Angle 40° +/-5° * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;







Drawing Values		Collected Values		Statistics	
T_m	40.00			$\bar{x}$	39.4125
LSL	35.00	x_{min}	39.00	$\bar{x}$-3s	38.8755
USL	45.00	x_{max}	39.75	$\bar{x}$+3s	39.9495
T	10.00	R	0.75	6s	1.0740
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1.1.4 $\hat{\sigma} = S_{tot}$
Potential Capability index	=	C_m	9.31
Critical capability index	=	C_{mk}	8.22

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_k	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	VM1698-4	Nom.val.	7,35
Ord. No.	1BD12T2O-A	Serial No.	1024210	LSL	5,73
				USL	9,04
Remark	TQ 60% Angle 40°+/-5°* TQ-Cal.: 12 Nm; Cur- Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
1024210	VM1698-4	Nm	7,24	7,21	7,22	7,22	7,30	7,31	7,24	7,24	7,27	7,31
1024210	VM1698-4	Grad	39,25	39,50	39,25	39,50	39,25	39,50	39,25	39,50	39,25	39,50

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
1024210	VM1698-4	Nm	7,26	7,25	7,26	7,25	7,28	7,24	7,29	7,31	7,32	7,27
1024210	VM1698-4	Grad	39,25	39,50	39,50	39,25	39,50	39,25	39,25	39,25	39,25	39,25

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
1024210	VM1698-4	Nm	7,29	7,26	7,27	7,25	7,32	7,39	7,34	7,31	7,31	7,25
1024210	VM1698-4	Grad	39,25	39,50	39,50	39,50	39,75	39,50	39,75	39,50	39,25	39,25

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
1024210	VM1698-4	Nm	7,29	7,32	7,32	7,26	7,27	7,33	7,32	7,30	7,29	7,32
1024210	VM1698-4	Grad	39,25	39,50	39,50	39,25	39,50	39,75	39,50	39,00	39,25	39,25

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
1024210	VM1698-4	Nm	7,30	7,31	7,31	7,28	7,28	7,30	7,25	7,30	7,30	7,29
1024210	VM1698-4	Grad	39,50	39,50	39,25	39,25	39,25	39,25	39,25	39,25	39,50	39,25

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
1024210	VM1698-4	Nm	7,32	7,30	7,32	7,34	7,35	7,32	7,33	7,40	7,23	7,23
1024210	VM1698-4	Grad	39,50	39,50	39,50	39,75	39,50	39,25	39,25	39,75	39,25	39,50

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
1024210	VM1698-4	Nm	7,17	7,20	7,23	7,20	7,21	7,22	7,21	7,21	7,25	7,21
1024210	VM1698-4	Grad	39,25	39,50	39,25	39,50	39,50	39,50	39,50	39,50	39,00	39,25

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
1024210	VM1698-4	Nm	7,24	7,18	7,18	7,25	7,23	7,22	7,25	7,28	7,24	7,22
1024210	VM1698-4	Grad	39,25	39,25	39,25	39,75	39,50	39,50	39,50	39,75	39,75	39,50

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_k	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	VM1698-4	Nom.val.	7,35
Ord. No.	1BD12T2O-A	Serial No.	1024210	LSL	5,73
				USL	9,04
Remark	TQ 60% Angle 40°+/-5°* TQ-Cal.: 12 Nm; Cur- Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
1024210	VM1698-4	Nm	7,22	7,21	7,22	7,28	7,18	7,18	7,25	7,24	7,17	7,30
1024210	VM1698-4	Grad	39,75	39,50	39,75	39,25	39,25	39,25	39,75	39,25	39,25	39,75

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
1024210	VM1698-4	Nm	7,22	7,20	7,27	7,19	7,24	7,25	7,20	7,23	7,24	7,23
1024210	VM1698-4	Grad	39,25	39,50	39,50	39,50	39,50	39,50	39,25	39,50	39,25	39,50

Machine Capability Study
Tool System

Page 1 / 1

Plant ATG Westhausen		Operator Name Sünder	Date 13.06.2022

Ord. No. 1BD12T2O-A	Part type 1BD-1B012A-1K3D-1ZB				Contr.item yes
Serial No. 755949_k	Char.Descr. 1VK3D	Nom.val.	40,00	5,00	USL 45,00
	Serial No. 198080	Unit	Grad	-5,00	LSL 35,00
Char.Type variable		Tolerance value	12 %		Decimal Pl. 2

Cust.Name Cleco	Reference System VM1698-4	Test Electronic MPRO400GCD-P
Contr.No. Homologation	Reference Transducer 10 / 1026388	nges. 100

Evaluation from 13.06.2022 08:39:43 to 13.06.2022 08:53:57

Rem. TQ 60% Angle 40° +/-5° * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;







Drawing Values		Collected Values		Statistics	
T_m	40.00			$\bar{x}$	40.0000
LSL	35.00	x_{min}	40.00		
USL	45.00	x_{max}	40.00		
T	10.00	R	0.00		
		$n_{<T>}$	100		
		$n_{>USL}$	0		
		$n_{<LSL}$	0		
		n_{eff}	100		
		n_{tot}	100		

--- R = 0 ---

APEX VDI/VDE 2647 V0.1

Apex Tool Group GmbH \\htwe0006\Appdata\QW\QWE\Messwert\2022\755949_k1.DFD

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_k	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1VK3D	Nom.val.	3,77
Ord. No.	1BD12T2O-A	Serial No.	198080	LSL	0,00
				USL	9,04
Remark	TQ 60% Angle 40°+/-5°* TQ-Cal.: 12 Nm; Cur- Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
198080	1VK3D	Nm	7,41	7,38	7,39	7,38	7,46	7,48	7,40	7,40	7,44	7,46
198080	1VK3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
198080	1VK3D	Nm	7,41	7,37	7,41	7,40	7,43	7,41	7,47	7,46	7,48	7,42
198080	1VK3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
198080	1VK3D	Nm	7,46	7,41	7,39	7,39	7,42	7,53	7,40	7,42	7,47	7,42
198080	1VK3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
198080	1VK3D	Nm	7,42	7,45	7,45	7,41	7,41	7,44	7,38	7,45	7,44	7,47
198080	1VK3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
198080	1VK3D	Nm	7,45	7,43	7,46	7,40	7,42	7,44	7,38	7,43	7,43	7,42
198080	1VK3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
198080	1VK3D	Nm	7,44	7,44	7,44	7,48	7,43	7,45	7,49	7,47	7,37	7,38
198080	1VK3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
198080	1VK3D	Nm	7,34	7,34	7,38	7,34	7,35	7,33	7,30	7,26	7,37	7,37
198080	1VK3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
198080	1VK3D	Nm	7,40	7,34	7,34	7,36	7,35	7,34	7,38	7,42	7,35	7,33
198080	1VK3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_k	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1VK3D	Nom.val.	3,77
Ord. No.	1BD12T2O-A	Serial No.	198080	LSL	0,00
				USL	9,04
Remark	TQ 60% Angle 40°+/-5°* TQ-Cal.: 12 Nm; Cur- Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
198080	1VK3D	Nm	7,34	7,32	7,32	7,38	7,35	7,31	7,31	7,38	7,32	7,36
198080	1VK3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
198080	1VK3D	Nm	7,35	7,36	7,42	7,32	7,38	7,35	7,29	7,39	7,41	7,36
198080	1VK3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Machine Capability Study
Tool System

Plant ATG Westhausen		Operator Name Sünder	Date 13.06.2022

Ord. No. 1BD12T2O-A	Part type 1BD-1B012A-1K3D-1ZB				Contr.item yes
Serial No. 755949_k	Char.Descr. 1K3D	Nom.val.	40,00	5,00	USL 45,00
	Serial No. 205495	Unit	Grad	-5,00	LSL 35,00
Char.Type variable		Tolerance value	12 %		Decimal Pl. 2

Cust.Name Cleco	Reference System VM1698-4	Test Electronic MPRO400GCD-P
Contr.No. Homologation	Reference Transducer 10 / 1026388	nges. 100

Evaluation from 13.06.2022 08:39:43 to 13.06.2022 08:53:57

Rem. TQ 60% Angle 40° +/-5° * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;







Drawing Values		Collected Values		Statistics	
T_m	40.00			$\bar{x}$	40.0000
LSL	35.00	x_{min}	40.00		
USL	45.00	x_{max}	40.00		
T	10.00	R	0.00		
		$n_{<T>}$	100		
		$n_{>USL}$	0		
		$n_{<LSL}$	0		
		n_{eff}	100		
		n_{tot}	100		

--- R = 0 ---

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_k	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1K3D	Nom.val.	3,77
Ord. No.	1BD12T2O-A	Serial No.	205495	LSL	0,00
				USL	9,04
Remark	TQ 60% Angle 40°+/-5°* TQ-Cal.: 12 Nm; Cur- Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
205495	1K3D	Nm	7,25	7,20	7,27	7,31	7,40	7,36	7,22	7,32	7,25	7,35
205495	1K3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
205495	1K3D	Nm	7,28	7,26	7,25	7,35	7,33	7,24	7,35	7,32	7,39	7,30
205495	1K3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
205495	1K3D	Nm	7,34	7,25	7,29	7,30	7,41	7,45	7,33	7,31	7,40	7,25
205495	1K3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
205495	1K3D	Nm	7,32	7,38	7,37	7,32	7,27	7,46	7,33	7,36	7,36	7,32
205495	1K3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
205495	1K3D	Nm	7,39	7,33	7,35	7,24	7,33	7,39	7,26	7,31	7,33	7,30
205495	1K3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
205495	1K3D	Nm	7,38	7,35	7,39	7,35	7,41	7,42	7,36	7,50	7,27	7,27
205495	1K3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
205495	1K3D	Nm	7,20	7,20	7,33	7,22	7,17	7,26	7,27	7,23	7,31	7,27
205495	1K3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
205495	1K3D	Nm	7,32	7,20	7,19	7,35	7,30	7,22	7,40	7,40	7,29	7,27
205495	1K3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_k	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1K3D	Nom.val.	3,77
Ord. No.	1BD12T2O-A	Serial No.	205495	LSL	0,00
				USL	9,04
Remark	TQ 60% Angle 40°+/-5°* TQ-Cal.: 12 Nm; Cur- Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
205495	1K3D	Nm	7,20	7,20	7,21	7,34	7,18	7,19	7,30	7,33	7,25	7,36
205495	1K3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
205495	1K3D	Nm	7,24	7,20	7,29	7,23	7,30	7,33	7,16	7,26	7,31	7,28
205495	1K3D	Grad	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00	40,00

Torque graphs

Model:	**1BD-1B012A-1K3D-1VK3D**	Serial no:	**755949**
Target torque:	**7,20 Nm**	60 % of max. torque	
Angle degree:	**40°**	Tool without angle correction	



Value no. 1
Graph
Torque / Angle / Speed



Value no. 1
Graph
Torque / Time / Speed



Value no. 100
Graph
Torque / Angle / Speed



Value no. 100
Graph
Torque / Time / Speed

General Specifications

Manufacturer: Apex Tool Group **Tool type:** Fixtured Spindle

Model: 1BD-1B012A-1K3D-1VK3D **Serial no:** 755949

Torque range: **2 Nm to 12 Nm**

Difference evaluation: Reference/Tool at 180 ° / 80%

Capability examination

Snugfit value: 2,4 Nm **Torque tolerance ±** 7 %

Target torque: 9,6 Nm Tolerance: 4,72 % ± **2,36 %**

Angle degree: 180° Tolerance: 2,5° ± **1,3°**

Formula derivation: $C_m = \frac{T}{6\,s}$ $T = C_m * 6\,s$

Tool without angle correction

Measurement	Tool data		Control data		Difference	
No.	Torque	Angle	Torque	Angle	Torque	Angle
1	9,59	180,00	9,50	178,00	0,09	2,00
2	9,53	180,00	9,45	178,50	0,08	1,50
3	9,56	180,00	9,49	178,75	0,07	1,25
4	9,59	180,00	9,49	178,25	0,10	1,75
5	9,52	180,00	9,45	178,25	0,07	1,75
6	9,54	180,00	9,46	178,25	0,08	1,75
7	9,51	180,00	9,46	178,00	0,05	2,00
8	9,53	180,00	9,47	178,25	0,06	1,75
9	9,53	180,00	9,48	178,50	0,05	1,50
10	9,51	180,00	9,46	178,50	0,05	1,50
11	9,59	180,00	9,50	178,50	0,09	1,50
12	9,50	180,00	9,44	178,50	0,06	1,50
13	9,55	180,00	9,48	178,25	0,07	1,75
14	9,56	180,00	9,47	178,50	0,09	1,50
15	9,52	180,00	9,46	178,25	0,06	1,75
16	9,53	180,00	9,47	178,00	0,06	2,00
17	9,51	180,00	9,44	178,50	0,07	1,50
18	9,49	180,00	9,44	178,50	0,05	1,50
19	9,47	180,00	9,41	178,25	0,06	1,75
20	9,46	180,00	9,40	178,50	0,06	1,50
21	9,48	180,00	9,42	178,50	0,06	1,50
22	9,51	180,00	9,44	178,50	0,07	1,50
23	9,51	180,00	9,45	178,75	0,06	1,25
24	9,43	180,00	9,37	178,00	0,06	2,00
25	9,46	180,00	9,40	178,25	0,06	1,75
26	9,50	180,00	9,44	178,25	0,06	1,75
27	9,47	180,00	9,40	178,25	0,07	1,75
28	9,53	180,00	9,44	178,75	0,09	1,25
29	9,49	180,00	9,43	178,25	0,06	1,75
30	9,41	180,00	9,35	178,00	0,06	2,00
31	9,57	180,00	9,49	178,75	0,08	1,25
32	9,80	180,00	9,61	178,00	0,19	2,00
33	9,66	180,00	9,57	178,25	0,09	1,75
34	9,63	180,00	9,56	178,00	0,07	2,00
35	9,62	180,00	9,56	178,00	0,06	2,00
36	9,56	180,00	9,49	178,25	0,07	1,75
37	9,58	180,00	9,52	178,50	0,06	1,50
38	9,63	180,00	9,55	178,75	0,08	1,25
39	9,83	180,00	9,63	178,00	0,20	2,00
40	9,76	180,00	9,62	178,25	0,14	1,75
41	9,62	180,00	9,55	178,50	0,07	1,50
42	9,61	180,00	9,55	178,75	0,06	1,25
43	9,60	180,00	9,54	178,75	0,06	1,25
44	9,59	180,00	9,53	178,50	0,06	1,50
45	9,59	180,00	9,52	178,75	0,07	1,25
46	9,82	180,00	9,63	178,00	0,19	2,00
47	9,72	180,00	9,63	178,50	0,09	1,50
48	9,53	180,00	9,48	178,00	0,05	2,00
49	9,62	180,00	9,56	178,75	0,06	1,25
50	9,56	180,00	9,48	178,50	0,08	1,50
51	9,77	180,00	9,59	178,25	0,18	1,75
52	9,74	180,00	9,60	178,50	0,14	1,50
53	9,62	180,00	9,54	178,75	0,08	1,25
54	9,57	180,00	9,51	178,25	0,06	1,75
55	9,83	180,00	9,62	178,25	0,21	1,75
56	9,62	180,00	9,52	178,00	0,10	2,00
57	9,78	180,00	9,59	178,25	0,19	1,75
58	9,67	180,00	9,56	178,25	0,11	1,75
59	9,54	180,00	9,48	178,25	0,06	1,75
60	9,54	180,00	9,45	178,50	0,09	1,50
61	9,74	180,00	9,58	177,75	0,16	2,25
62	9,52	180,00	9,47	178,00	0,05	2,00
63	9,58	180,00	9,51	178,25	0,07	1,75
64	9,79	180,00	9,60	178,25	0,19	1,75
65	9,63	180,00	9,54	178,00	0,09	2,00
66	9,75	180,00	9,55	177,75	0,20	2,25
67	9,65	180,00	9,54	178,50	0,11	1,50
68	9,56	180,00	9,49	178,00	0,07	2,00
69	9,56	180,00	9,50	178,50	0,06	1,50
70	9,73	180,00	9,55	178,25	0,18	1,75
71	9,69	180,00	9,58	178,50	0,11	1,50
72	9,54	180,00	9,48	178,25	0,06	1,75
73	9,76	180,00	9,58	178,00	0,18	2,00
74	9,56	180,00	9,49	178,00	0,07	2,00
75	9,50	180,00	9,48	178,75	0,02	1,25
76	9,72	180,00	9,55	178,25	0,17	1,75
77	9,55	180,00	9,49	178,50	0,06	1,50
78	9,51	180,00	9,46	178,25	0,05	1,75
79	9,72	180,00	9,58	178,50	0,14	1,50
80	9,60	180,00	9,51	178,00	0,09	2,00
81	9,54	180,00	9,48	178,25	0,06	1,75
82	9,57	180,00	9,52	178,50	0,05	1,50
83	9,53	180,00	9,45	178,00	0,08	2,00
84	9,61	180,00	9,51	178,50	0,10	1,50
85	9,73	180,00	9,55	178,50	0,18	1,50
86	9,62	180,00	9,54	178,50	0,08	1,50
87	9,56	180,00	9,49	178,50	0,07	1,50
88	9,66	180,00	9,54	178,50	0,12	1,50
89	9,52	180,00	9,45	178,50	0,07	1,50
90	9,72	180,00	9,54	178,25	0,18	1,75
91	9,63	180,00	9,54	178,75	0,09	1,25
92	9,56	180,00	9,48	178,50	0,08	1,50
93	9,75	180,00	9,57	178,50	0,18	1,50
94	9,56	180,00	9,48	178,25	0,08	1,75
95	9,51	180,00	9,45	178,50	0,06	1,50
96	9,72	180,00	9,57	178,75	0,15	1,25
97	9,59	180,00	9,53	178,25	0,06	1,75
98	9,49	180,00	9,44	178,50	0,05	1,50
99	9,55	180,00	9,46	178,25	0,09	1,75
100	9,60	180,00	9,49	178,25	0,11	1,75
				Standard deviation:	**0,045**	**0,250**

Graphical representation

Model:	**1BD-1B012A-1K3D-1VK3D**	Serial no:	**755949**
Target torque:	**9,60 Nm**	80 % of max. torque	
Angle degree:	**180°**	Tool without angle correction	





Machine Capability Study
Control System

Page 1 / 1

Plant	ATG Westhausen	Operator Name	Sünder
Date	13.06.2022		

Ord. No.	1BD12T2O-A	Part type	1BD-1B012A-1K3D-1ZB	Contr.item	yes
Serial No.	755949_l	Char.Descr.	VM1698-4	Nom.val. 180,00 10,00	USL 190,00
		Serial No.	1024210	Unit Grad -10,00	LSL 170,00
Char.Type	variable			Tolerance value 6 %	Decimal Pl. 2
Cust.Name	Cleco	Reference System	VM1698-4	Test Electronic	MPRO400GCD-P
Contr.No.	Homologation	Reference Transducer	10 / 1026388	nges.	100

Evaluation from 13.06.2022 08:58:32 to 13.06.2022 09:14:05

Rem. TQ 80% Angle 180° +/-10° * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;





Drawing Values		Collected Values		Statistics	
T_m	180.00			$\bar{x}$	178.3425
LSL	170.00	x_{min}	177.75	$\bar{x}$-3s	177.5913
USL	190.00	x_{max}	178.75	$\bar{x}$+3s	179.0937
T	20.00	R	1.00	6s	1.5023
		$n_{<T>}$	100	$p_{<T>}$	100.00000 %
		$n_{>USL}$	0	$p_{>USL}$	0.00000%
		$n_{<LSL}$	0	$p_{<LSL}$	0.00000%
		n_{eff}	100		
		n_{tot}	100		

Model distribution			Normal Distribution
Calculation method			M1.1.4 $\hat{\sigma} = s_{tot}$
Potential Capability index	=	C_m	13.31
Critical capability index	=	C_{mk}	11.11

The requirements were met (C_m,C_{mk})

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_I	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	VM1698-4	Nom.val.	9,59
Ord. No.	1BD12T2O-A	Serial No.	1024210	LSL	7,48
				USL	11,80
Remark	TQ 80% Angle 180°+/-10°* TQ-Cal.: 12 Nm; Cu r-Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
1024210	VM1698-4	Nm	9,50	9,45	9,49	9,49	9,45	9,46	9,46	9,47	9,48	9,46
1024210	VM1698-4	Grad	178,00	178,50	178,75	178,25	178,25	178,25	178,00	178,25	178,50	178,50

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
1024210	VM1698-4	Nm	9,50	9,44	9,48	9,47	9,46	9,47	9,44	9,44	9,41	9,40
1024210	VM1698-4	Grad	178,50	178,50	178,25	178,50	178,25	178,00	178,50	178,50	178,25	178,50

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
1024210	VM1698-4	Nm	9,42	9,44	9,45	9,37	9,40	9,44	9,40	9,44	9,43	9,35
1024210	VM1698-4	Grad	178,50	178,50	178,75	178,00	178,25	178,25	178,25	178,75	178,25	178,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
1024210	VM1698-4	Nm	9,49	9,61	9,57	9,56	9,56	9,49	9,52	9,55	9,63	9,62
1024210	VM1698-4	Grad	178,75	178,00	178,25	178,00	178,00	178,25	178,50	178,75	178,00	178,25

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
1024210	VM1698-4	Nm	9,55	9,55	9,54	9,53	9,52	9,63	9,63	9,48	9,56	9,48
1024210	VM1698-4	Grad	178,50	178,75	178,75	178,50	178,75	178,00	178,50	178,00	178,75	178,50

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
1024210	VM1698-4	Nm	9,59	9,60	9,54	9,51	9,62	9,52	9,59	9,56	9,48	9,45
1024210	VM1698-4	Grad	178,25	178,50	178,75	178,25	178,25	178,00	178,25	178,25	178,25	178,50

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
1024210	VM1698-4	Nm	9,58	9,47	9,51	9,60	9,54	9,55	9,54	9,49	9,50	9,55
1024210	VM1698-4	Grad	177,75	178,00	178,25	178,25	178,00	177,75	178,50	178,00	178,50	178,25

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
1024210	VM1698-4	Nm	9,58	9,48	9,58	9,49	9,48	9,55	9,49	9,46	9,58	9,51
1024210	VM1698-4	Grad	178,50	178,25	178,00	178,00	178,75	178,25	178,50	178,25	178,50	178,00

Machine Capability Study
Control System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_I	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	VM1698-4	Nom.val.	9,59
Ord. No.	1BD12T2O-A	Serial No.	1024210	LSL	7,48
				USL	11,80
Remark	TQ 80% Angle 180°+/-10°* TQ-Cal.: 12 Nm; Cu r-Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
1024210	VM1698-4	Nm	9,48	9,52	9,45	9,51	9,55	9,54	9,49	9,54	9,45	9,54
1024210	VM1698-4	Grad	178,25	178,50	178,00	178,50	178,50	178,50	178,50	178,50	178,50	178,25

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
1024210	VM1698-4	Nm	9,54	9,48	9,57	9,48	9,45	9,57	9,53	9,44	9,46	9,49
1024210	VM1698-4	Grad	178,75	178,50	178,50	178,25	178,50	178,75	178,25	178,50	178,25	178,25

Machine Capability Study
Tool System

Plant	ATG Westhausen	Operator Name	Sünder
Date	13.06.2022		

Ord. No.	1BD12T2O-A	Part type	1BD-1B012A-1K3D-1ZB	Contr.item	yes
Serial No.	755949_l	Char.Descr.	1VK3D	Nom.val. 180,00 10,00	USL 190,00
		Serial No.	198080	Unit Grad -10,00	LSL 170,00
Char.Type	variable			Tolerance value 6 %	Decimal Pl. 2
Cust.Name	Cleco	Reference System	VM1698-4	Test Electronic	MPRO400GCD-P
Contr.No.	Homologation	Reference Transducer	10 / 1026388	nges.	100

Evaluation from 13.06.2022 08:58:33 to 13.06.2022 09:14:06

Rem. TQ 80% Angle 180° +/-10° * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;







Drawing Values		Collected Values		Statistics	
T_m	180.00			$\bar{x}$	180.0000
LSL	170.00	x_{min}	180.00		
USL	190.00	x_{max}	180.00		
T	20.00	R	0.00		
		$n_{<T>}$	100		
		$n_{>USL}$	0		
		$n_{<LSL}$	0		
		n_{eff}	100		
		n_{tot}	100		

--- R = 0 ---

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_I	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1VK3D	Nom.val.	4,91
Ord. No.	1BD12T2O-A	Serial No.	198080	LSL	0,00
				USL	11,80
Remark	TQ 80% Angle 180°+/-10°* TQ-Cal.: 12 Nm; Cu r-Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
198080	1VK3D	Nm	9,59	9,53	9,56	9,59	9,52	9,54	9,51	9,53	9,53	9,51
198080	1VK3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
198080	1VK3D	Nm	9,59	9,50	9,55	9,56	9,52	9,53	9,51	9,49	9,47	9,46
198080	1VK3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
198080	1VK3D	Nm	9,48	9,51	9,51	9,43	9,46	9,50	9,47	9,53	9,49	9,41
198080	1VK3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
198080	1VK3D	Nm	9,57	9,80	9,66	9,63	9,62	9,56	9,58	9,63	9,83	9,76
198080	1VK3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
198080	1VK3D	Nm	9,62	9,61	9,60	9,59	9,59	9,82	9,72	9,53	9,62	9,56
198080	1VK3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
198080	1VK3D	Nm	9,77	9,74	9,62	9,57	9,83	9,62	9,78	9,67	9,54	9,54
198080	1VK3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
198080	1VK3D	Nm	9,74	9,52	9,58	9,79	9,63	9,75	9,65	9,56	9,56	9,73
198080	1VK3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
198080	1VK3D	Nm	9,69	9,54	9,76	9,56	9,50	9,72	9,55	9,51	9,72	9,60
198080	1VK3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_I	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1VK3D	Nom.val.	4,91
Ord. No.	1BD12T2O-A	Serial No.	198080	LSL	0,00
				USL	11,80
Remark	TQ 80% Angle 180°+/-10°* TQ-Cal.: 12 Nm; Cu r-Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
198080	1VK3D	Nm	9,54	9,57	9,53	9,61	9,73	9,62	9,56	9,66	9,52	9,72
198080	1VK3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
198080	1VK3D	Nm	9,63	9,56	9,75	9,56	9,51	9,72	9,59	9,49	9,55	9,60
198080	1VK3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Machine Capability Study
Tool System

Plant	ATG Westhausen	Operator Name	Sünder
Date	13.06.2022		

Ord. No.	1BD12T2O-A	Part type	1BD-1B012A-1K3D-1ZB	Contr.item	yes
Serial No.	755949_l	Char.Descr.	1K3D	Nom.val. 180,00 10,00	USL 190,00
		Serial No.	205495	Unit Grad -10,00	LSL 170,00
Char.Type	variable			Tolerance value 6 %	Decimal Pl. 2
Cust.Name	Cleco	Reference System	VM1698-4	Test Electronic	MPRO400GCD-P
Contr.No.	Homologation	Reference Transducer	10 / 1026388	nges.	100

Evaluation from 13.06.2022 08:58:33 to 13.06.2022 09:14:06

Rem. TQ 80% Angle 180° +/-10° * TQ-Cal.: 12 Nm; Cur-Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;







Drawing Values		Collected Values		Statistics	
T_m	180.00			$\bar{x}$	180.0000
LSL	170.00	x_{min}	180.00		
USL	190.00	x_{max}	180.00		
T	20.00	R	0.00		
		$n_{<T>}$	100		
		$n_{>USL}$	0		
		$n_{<LSL}$	0		
		n_{eff}	100		
		n_{tot}	100		

--- R = 0 ---

APEX VDI/VDE 2647 V0.1

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_I	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1K3D	Nom.val.	4,91
Ord. No.	1BD12T2O-A	Serial No.	205495	LSL	0,00
				USL	11,80
Remark	TQ 80% Angle 180°+/-10°* TQ-Cal.: 12 Nm; Cu r-Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;				

Char.No.	Char.Descr.	Unit	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}
205495	1K3D	Nm	9,63	9,50	9,53	9,48	9,47	9,47	9,53	9,51	9,49	9,46
205495	1K3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No.	Char.Descr.	Unit	x_{11}	x_{12}	x_{13}	x_{14}	x_{15}	x_{16}	x_{17}	x_{18}	x_{19}	x_{20}
205495	1K3D	Nm	9,57	9,50	9,49	9,54	9,49	9,50	9,47	9,52	9,55	9,41
205495	1K3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No.	Char.Descr.	Unit	x_{21}	x_{22}	x_{23}	x_{24}	x_{25}	x_{26}	x_{27}	x_{28}	x_{29}	x_{30}
205495	1K3D	Nm	9,41	9,48	9,59	9,42	9,56	9,53	9,50	9,54	9,40	9,41
205495	1K3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No.	Char.Descr.	Unit	x_{31}	x_{32}	x_{33}	x_{34}	x_{35}	x_{36}	x_{37}	x_{38}	x_{39}	x_{40}
205495	1K3D	Nm	9,61	9,66	9,65	9,57	9,63	9,55	9,52	9,67	9,67	9,65
205495	1K3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No.	Char.Descr.	Unit	x_{41}	x_{42}	x_{43}	x_{44}	x_{45}	x_{46}	x_{47}	x_{48}	x_{49}	x_{50}
205495	1K3D	Nm	9,67	9,58	9,55	9,55	9,62	9,71	9,71	9,58	9,64	9,57
205495	1K3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No.	Char.Descr.	Unit	x_{51}	x_{52}	x_{53}	x_{54}	x_{55}	x_{56}	x_{57}	x_{58}	x_{59}	x_{60}
205495	1K3D	Nm	9,66	9,66	9,54	9,53	9,72	9,60	9,69	9,62	9,55	9,55
205495	1K3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No.	Char.Descr.	Unit	x_{61}	x_{62}	x_{63}	x_{64}	x_{65}	x_{66}	x_{67}	x_{68}	x_{69}	x_{70}
205495	1K3D	Nm	9,71	9,46	9,59	9,60	9,58	9,67	9,70	9,60	9,56	9,63
205495	1K3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No.	Char.Descr.	Unit	x_{71}	x_{72}	x_{73}	x_{74}	x_{75}	x_{76}	x_{77}	x_{78}	x_{79}	x_{80}
205495	1K3D	Nm	9,67	9,59	9,61	9,60	9,47	9,67	9,61	9,57	9,56	9,53
205495	1K3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Machine Capability Study
Tool System

Plant	ATG Westhausen		Operator Name	Sünder	Date 13.06.2022

Serial No.	755949_I	Characteristic			
Part type	1BD-1B012A-1K3D-1ZB	Char.Descr.	1K3D	Nom.val.	4,91
Ord. No.	1BD12T2O-A	Serial No.	205495	LSL	0,00
				USL	11,80
Remark	TQ 80% Angle 180°+/-10°* TQ-Cal.: 12 Nm; Cu r-Cal.: 0.8804 Nm/A; Speed: 300/50 rpm;				

Char.No.	Char.Descr.	Unit	x_{81}	x_{82}	x_{83}	x_{84}	x_{85}	x_{86}	x_{87}	x_{88}	x_{89}	x_{90}
205495	1K3D	Nm	9,52	9,53	9,59	9,52	9,66	9,55	9,57	9,68	9,45	9,62
205495	1K3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Char.No.	Char.Descr.	Unit	x_{91}	x_{92}	x_{93}	x_{94}	x_{95}	x_{96}	x_{97}	x_{98}	x_{99}	x_{100}
205495	1K3D	Nm	9,56	9,55	9,61	9,56	9,58	9,61	9,54	9,45	9,50	9,58
205495	1K3D	Grad	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00	180,00

Torque graphs

Model:	**1BD-1B012A-1K3D-1VK3D**	Serial no:	**755949**
Target torque:	**9,60 Nm**	80 % of max. torque	
Angle degree:	**180°**	Tool without angle correction	



Value no. 1
Graph
Torque / Angle / Speed



Value no. 1
Graph
Torque / Time / Speed



Value no. 100
Graph
Torque / Angle / Speed



Value no. 100
Graph
Torque / Time / Speed