Homologation

Document no: 02/22

Fixtured Spindle

Type: **Cleco - 1BD-1B060A-1K2D-1VK2D**

Order no.: **1BD53T2O-A**

This homologation also applies to type(s):

Cleco - 1BD-1B060A-1VK2D
Cleco - 1BDU-1B060A-1K2D-1VK2D
Cleco - 1BDU-1B060A-1VK2D

Cleco - 1BD-1B060A-1K2D-1VK2D

Fixtured Spindle

Order no.: 1BD53T2O-A

Included	*Type*	*Order no.*
	Cleco - 1BD-1B060A-1VK2D	1BD53T1O-A
	Cleco - 1BDU-1B060A-1K2D-1VK2D	1BDU53T2O-A
	Cleco - 1BDU-1B060A-1VK2D	1BDU53T1O-A

Machine type:	Fixtured Spindle
Torque range:	5,3 Nm to 53 Nm
Max speed:	700 rpm
Certified serial nos.:	756027, 756028, 756029

Contents:

Overview C_m/C_{mk} values
General specifications tool and controller
Power Tools Sales & Service Centers
Machine capability study and graphs
Measurement capability test

Apex Tool Group

Fixtured Spindle

C_m / C_{mk} values achieved

According VDI/VDE 2647 February 2013

Accuracy class: 7 %

Tool model	Serial nos.	Test data	30 %		80 %		100 %	
			30° ±5°	360° ±15°	30° ±5°	360° ±15°	30° ±5°	360° ±15°
1BD-1B060A-1K2D-1VK2D		Break time	5 s	5 s	5 s	10 s	5 s	45 s
		Test torque	**19,61 Nm**		**43,46 Nm**		**53,00 Nm**	
		Speed in 1st stage	700 rpm	700 rpm	700 rpm	700 rpm	700 rpm	700 rpm
		Speed in last stage	50 rpm	50 rpm	50 rpm	50 rpm	50 rpm	50 rpm
		Angle start torque	9,81 Nm		21,73 Nm		26,50 Nm	
	756027	C_m	6,81	9,66	17,23	14,36	16,37	18,80
		C_{mk}	6,00	9,60	15,45	14,14	14,96	18,45
	756028	C_m	4,02	3,51	5,36	5,24	4,96	4,10
		C_{mk}	3,80	3,30	5,34	4,83	4,91	3,54
	756029	C_m	4,89	7,76	8,72	9,28	9,50	9,28
		C_{mk}	4,13	7,41	7,51	9,25	8,29	9,10
Min. C_m/C_{mk}		C_m	4,02	3,51	5,36	5,24	4,96	4,10
		C_{mk}	3,80	3,30	5,34	4,83	4,91	3,54

	Target:	≥ 1.67	**Rating**
Capability index	C_m	**3,51**	**OK**
	C_{mk}	**3,30**	**OK**

Tolerances of rotational angle homologation
Measurements without angle correction

Tool model	Serial nos.	Test data	60 % of max. torque		80 % of max. torque	
			40°		**180°**	
1BD-1B060A-1K2D-1VK2D		Break time	5 s		5 s	
		Angle start torque	10,60 Nm		10,60 Nm	
		Test torque	31,80 Nm		42,40 Nm	
		Speed in 1st stage	300 rpm		300 rpm	
		Speed in last stage	50 rpm		50 rpm	
	756027	Torque	±	0,50 %	±	0,47 %
		Angle	±	1,9°	±	3,5°
	756028	Torque	±	2,06 %	±	2,29 %
		Angle	±	2,0°	±	3,2°
	756029	Torque	±	0,86 %	±	1,09 %
		Angle	±	2,3°	±	2,6°

Torque	Target: ±	7 %	Target: ±	7 %
	Actual: ±	2,06 %	Actual: ±	2,29 %
Rating	**OK**		**OK**	

Angle	Target: ±	5°	Target: ±	10°
	Actual: ±	2,3°	Actual: ±	3,5°
Rating	**OK**		**OK**	

Document no: 02/22
Date: 08.02.2022

Test sheet no. 1a

General specifications

Manufacturer:	Apex Tool Group	**Assembly tool type**	Fixtured Spindle
Tool model:	1BD-1B060A-1K2D-1VK2D	**Serial numbers:**	756027, 756028, 756029
Torque range:	5,3 Nm to 53 Nm		

Operating voltage:	380	VDC
Power consumption:	510	W
Weight:	4,74	kg
Control cable length:	15	m
Diameter of control cable:	14	mm
Maximum speed at the first stage:	700	rpm
Maximum speed at the final stage:	700	rpm
Minimum speed at the final stage:	0	rpm
Sound pressure level at maximum speed: (acc. to DIN EN 62841-1:2016-07, DIN EN 62841-2-2:2015-05)	64,9	dB(A)

Temperature of electrical tools:

(After 100 measurements with soft jont at 80% torque)

	start	end
at the angle head:	-	-
on the electric motor:	23 °C	74 °C
on the handle:	-	-

Output type:	Square drive	
Output drive size:	3/8	inches

Test sheet no. 1b

Specifications of controller

Manufacturer:	Apex Tool Group	**Serial number:**	AXABH0001
Controller type:	MPRO400GCD-P	**Software version:**	S168813-1.12.0.61436-Test 03.03.21

Fastening Strategy:	Current shut-off:	Yes
	Torque control:	Yes
	Torque control, angle monitoring:	Yes
	Angle control, torque monitoring:	Yes
	Yield point control:	Yes
	Pre-load control:	No
Options:	Prevailing torque:	Yes
	Angle correction:	No
	Pulsing:	No
	Tighten - loosen - tighten:	Yes
	Tapping screw monitoring:	Yes
	Left-hand rundown:	Yes
	Other procedures:	Yes, see documentation
Angle of rotation resolution:		1 degree
Torque accuracy:		1 %
Programming:	Keyboard:	Yes
	External PC:	Yes
	Text display:	Yes
	Display:	Yes
	LCD display:	No
Printer interface:		Yes
Additional inputs and outputs:		2 Serial RS232 8 Digital in, 8 Digital out (24V) 2 Fieldbus modules 3 USB 2.0
Isolation transformer:		No, galvanic isolated power supply
Network:		2 RJ45 10/100 BaseT Ethernet ports

POWER TOOLS SALES & SERVICE CENTERS

Please note that all locations may not service all products.
Contact the nearest Cleco® Sales & Service Center for the appropriate facility to handle your service requirements.

Sales Center
Service Center

NORTH AMERICA I SOUTH AMERICA

Detroit, Michigan
Apex Tool Group
2630 Superior Court
Auburn Hills, MI 48236
Phone: +1 (248) 393-5644
Fax: +1 (248) 391-6295

Lexington, South Carolina
Apex Tool Group
670 Industrial Drive
Lexington, SC 29072
Phone: +1 (800) 845-5629
Phone: +1 (919) 387-0099
Fax: +1 (803) 358-7681

Canada
Apex Tool Canada, Ltd.
7631 Bath Road
Mississauga, Ontario L4T 3T1
Canada
Phone: (866) 691-6212
Fax: (905) 673-4400

Mexico
Apex Tool Group
Vialidad El Pueblito #103
Parque Industrial Querétaro
Querétaro, QRO 76220
Mexico
Phone: +52 (442) 211 3800
Fax: +52 (800) 685 5560

Brazil
Apex Tool Group
Av. Liberdade, 4055
Zona Industrial Iporanga
Sorocaba, São Paulo
CEP# 18087-170
Brazil
Phone: +55 15 3238 3870
Fax: +55 15 3238 3938

EUROPE I MIDDLE EAST I AFRICA

England
Apex Tool Group GmbH
C/O Spline Gauges
Piccadilly, Tamworth
Staffordshire B78 2ER
United Kingdom
Phone: +44 1827 8727 71
Fax: +44 1827 8741 28

France
Apex Tool Group SAS
25 Avenue Maurice Chevalier - ZI
77330 Ozoir-La-Ferrière
France
Phone: +33 1 64 43 22 00
Fax: +33 1 64 43 17 17

Germany
Apex Tool Group GmbH
Industriestraße 1
73463 Westhausen
Germany
Phone: +49 (0) 73 63 81 0
Fax: +49 (0) 73 63 81 222

Hungary
Apex Tool Group
Hungária Kft.
Platánfa u. 2
9027 Györ
Hungary
Phone: +36 96 66 1383
Fax: +36 96 66 1135

ASIA PACIFIC

Australia
Apex Tool Group
519 Nurigong Street, Albury
NSW 2640
Australia
Phone: +61 2 6058 0300

China
Apex Power Tool Trading
(Shanghai) Co., Ltd.
2nd Floor, Area C
177 Bi Bo Road
Pu Dong New Area, Shanghai
China 201203 P.R.C.
Phone: +86 21 60880320
Fax: +86 21 60880298

India
Apex Power Tool India
Private Limited
Gala No. 1, Plot No. 5
S. No. 234, 235 & 245
Indialand Global
Industrial Park
Taluka-Mulsi, Phase I
Hinjawadi, Pune 411057
Maharashtra, India
Phone: +91 020 66761111

Japan
Apex Tool Group Japan
Korin-Kaikan 5F,
3-6-23 Shibakoen, Minato-Ku,
Tokyo 105-0011, JAPAN
Phone: +81-3-6450-1840
Fax: +81-3-6450-1841

Korea
Apex Tool Group Korea
#1503, Hibrand Living Bldg.,
215 Yangjae-dong,
Seocho-gu, Seoul 137-924,
Korea
Phone: +82-2-2155-0250
Fax: +82-2-2155-0252

Cleco®
Production Tools

© Cleco® is a registered trademark of Apex Brands, Inc.

Apex Tool Group GmbH
Phone: +49 7363 81 0
www.ClecoTools.com
www.ClecoTools.de