

## Highly Productive Modular Assembly System

System brings unmatched Reliability and Durability to your assembly line

## FEATURES

### Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54



## SPECIFICATIONS

### TYPE

2BD-2B110A-2K1D-2ZB

### TORQUE RANGE (Nm)

Min / Max: 11 - 110

### IDLE SPEED (1/min)

890

### FLOAT (mm)

50

### FLOATING ADAPTER





910609

### FLOATING ADAPTER WITH FLANGE HOUSING

S308435

### WEIGHT & DIMENSIONS

Weight 6.5 kg / 14.33 lb  
 Length 481 mm / 18.94 in  
 Side to Center 56 mm / 2.20 in  
 Country of Origin: Germany



Apex Tool Group, LLC

Phone: +1 (800) 845-5629

Phone: +1 (919) 387-0099

Phone: +49 (0)7363 81-0

www.ClecoTools.com / www.ClecoTools.de

## Highly Productive Modular Assembly System

System brings unmatched Reliability and Durability to your assembly line

## FEATURES

### Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54
- Redundant



## SPECIFICATIONS

### TYPE

2BD-2B110A-2/2K1D-2ZB

### TORQUE RANGE (Nm)

Min / Max: 11 - 110

### IDLE SPEED (1/min)

890

### FLOAT (mm)

50

### FLOATING ADAPTER




910609

### FLOATING ADAPTER WITH FLANGE HOUSING

S308435

### WEIGHT & DIMENSIONS

Weight 7.6 kg / 16.76 lb  
 Length 578 mm / 22.76 in  
 Side to Center 56 mm / 2.20 in  
 Country of Origin: Germany



## 2BD110T2S-A

## STRAIGHT ATTACHMENT, TWIN TRANSDUCER

MODEL: BD

SIZE :2

11 - 110 Nm TORQUE


## Highly Productive Modular Assembly System

System brings unmatched Reliability and Durability to your assembly line

## FEATURES

### Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54



## SPECIFICATIONS

### TYPE

2BD-2B110A-2VK1D

### TORQUE RANGE (Nm)

Min / Max: 11 - 110

### IDLE SPEED (1/min)

830

### FLOAT (mm)

50

### FLOATING ADAPTER

910609

### FLOATING ADAPTER WITH FLANGE HOUSING

S308438

### WEIGHT & DIMENSIONS

Weight 8.1 kg / 17.86 lb  
 Length 504 mm / 19.84 in  
 Side to Center 44 mm / 1.73 in  
 Country of Origin: Germany





## 2BD110T10-A

## OFFSET DRIVE SINGLE TRANSDUCER

MODEL: BD

SIZE :2

11 - 110 Nm TORQUE



# Product Specifications



## Highly Productive Modular Assembly System

**System brings unmatched Reliability and Durability to your assembly line**

## FEATURES

## Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54
- Redundant



## SPECIFICATIONS

**TYPE**

2BD-2B110A-2K1D-2VK1D

### TORQUE RANGE (Nm)

Min / Max: 11 - 110

**IDLE SPEED (1/min)**

830

**FLOAT (mm)**

50

## FLOATING ADAPTER

910609

## FLOATING ADAPTER WITH FLANGE HOUSING

S308438

## WEIGHT & DIMENSIONS

Weight	9.2 kg / 20.29 lb
Length	601 mm / 23.66 in
Side to Center	44 mm / 1.73 in
Country of Origin:	Germany



# Product Specifications

## Highly Productive Modular Assembly System

**System brings unmatched Reliability and Durability to your assembly line**

## FEATURES

## Spindle Assembly

- **Drive attachments:** Full complement of modular configurations
- **Motors:** New high precision
- **Transducer:** New digital. Available with single or dual units
- **Protection class:** IP54



## SPECIFICATIONS

**TYPE**

2BD-2B110A-2WK1D

### TORQUE RANGE (Nm)

Min / Max: 11 - 110

**IDLE SPEED (1/min)**

837

**Float (mm)**

25

## FLOATING ADAPTER




—

## FLOATING ADAPTER WITH FLANGE HOUSING

929053

## WEIGHT & DIMENSIONS

Weight	7.6 kg / 16.76 lb
Length	505 mm / 19.88 in
Side to Center	59 mm / 2.32 in
Country of Origin:	Germany



## Highly Productive Modular Assembly System

System brings unmatched Reliability and Durability to your assembly line

## FEATURES

### Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54
- Redundant



## SPECIFICATIONS

### TYPE

2BD-2B110A-2K1D-2WK1D

### TORQUE RANGE (Nm)

Min / Max: 11 - 110

### IDLE SPEED (1/min)

837

### FLOAT (mm)

25

### FLOATING ADAPTER

--

### FLOATING ADAPTER WITH FLANGE HOUSING

929053

### WEIGHT & DIMENSIONS

Weight 8.7 kg / 19.18 lb  
Length 602 mm / 23.70 in  
Side to Center 59 mm / 2.32 in  
Country of Origin: Germany









## 2BD110T2A-A

## ANGLE ATTACHMENT, TWIN TRANSDUCER

MODEL: BD

SIZE :2

11 - 110 Nm TORQUE




## Highly Productive Modular Assembly System

System brings unmatched Reliability and Durability to your assembly line

## FEATURES

### Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54



## SPECIFICATIONS

### TYPE

2BDU-2B110A-2K1D-2ZB

### TORQUE RANGE (Nm)

Min / Max: 11 - 110

### IDLE SPEED (1/min)

890

### FLOAT (mm)

50

### FLOATING ADAPTER

910609

### FLOATING ADAPTER WITH FLANGE HOUSING

S308435

### WEIGHT & DIMENSIONS

Weight 7.5 kg / 16.54 lb  
Length 310 mm / 12.20 in  
Side to Center 56 mm / 2.20 in  
Country of Origin: Germany







## 2BDU110T1S-A

### STRAIGHT DRIVE, REVERSIBLE GEARS, SINGLE TRANSDUCER

MODEL: BD

SIZE :2

11 - 110 Nm TORQUE




## Highly Productive Modular Assembly System

System brings unmatched Reliability and Durability to your assembly line

## FEATURES

### Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54
- Redundant



## SPECIFICATIONS

### TYPE

2BDU-2B110A-2/2K1D-2ZB

### TORQUE RANGE (Nm)

Min / Max: 11 - 110

### IDLE SPEED (1/min)

890

### FLOAT (mm)

50

### FLOATING ADAPTER

910609

### FLOATING ADAPTER WITH FLANGE HOUSING

S308435

### WEIGHT & DIMENSIONS

Weight 8.6 kg / 18.96 lb  
 Length 407 mm / 16.02 in  
 Side to Center 56 mm / 2.20 in  
 Country of Origin: Germany







## 2BDU110T2S-A

### STRAIGHT ATTACHMENT, REVERSIBLE GEARS, TWIN TRANSDUCER

MODEL: BD

SIZE :2

11 - 110 Nm TORQUE






## Highly Productive Modular Assembly System

System brings unmatched Reliability and Durability to your assembly line

## FEATURES

### Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54



## SPECIFICATIONS

### TYPE

2BDU-2B110A-2VK1D

### TORQUE RANGE (Nm)

Min / Max: 11 - 110

### IDLE SPEED (1/min)

830

### FLOAT (mm)

50

### FLOATING ADAPTER

910609

### FLOATING ADAPTER WITH FLANGE HOUSING

S308438

### WEIGHT & DIMENSIONS

Weight 9.1 kg / 20.07 lb  
Length 333 mm / 13.11 in  
Side to Center 44 mm / 1.73 in  
Country of Origin: Germany








## 2BDU110T10-A OFFSET DRIVE, REVERSIBLE GEARS, SINGLE TRANSDUCER

MODEL: BD

SIZE :2

11 - 110 Nm TORQUE




## Highly Productive Modular Assembly System

System brings unmatched Reliability and Durability to your assembly line

## FEATURES

### Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54
- Redundant



## SPECIFICATIONS

### TYPE

2BDU-2B110A-2K1D-2VK1D

### TORQUE RANGE (Nm)

Min / Max: 11 - 110

### IDLE SPEED (1/min)

830

### FLOAT (mm)

50

### FLOATING ADAPTER

910609

### FLOATING ADAPTER WITH FLANGE HOUSING

S308438

### WEIGHT & DIMENSIONS

Weight 10.2 kg / 22.49 lb  
Length 430 mm / 16.93 in  
Side to Center 44 mm / 1.73 in  
Country of Origin: Germany









## 2BDU110T20-A OFFSET ATTACHMENT, REVERSIBLE GEARS, TWIN TRANSDUCER

MODEL: BD

SIZE :2

11 - 110 Nm TORQUE



Apex Tool Group, LLC

Phone: +1 (800) 845-5629

Phone: +1 (919) 387-0099

Phone: +49 (0)7363 81-0

www.ClecoTools.com / www.ClecoTools.de

# Product Specifications


## Highly Productive Modular Assembly System

## System brings unmatched Reliability and Durability to your assembly line

## FEATURES

## Spindle Assembly

- **Drive attachments:** Full complement of modular configurations
- **Motors:** New high precision
- **Transducer:** New digital. Available with single or dual units
- **Protection class:** IP54



## SPECIFICATIONS

## TYPE

2BDU-2B110A-2WK1D

**TORQUE RANGE (Nm)**

Min / Max: 11 - 110

**IDLE SPEED (1/min)**

837

**Float (mm)**

25

## FLOATING ADAPTER







—

## FLOATING ADAPTER WITH FLANGE HOUSING

929053

## WEIGHT & DIMENSIONS

Weight	8.6 kg / 18.96 lb
Length	335 mm / 13.19 in
Side to Center	59 mm / 2.32 in
Country of Origin:	Germany




## Highly Productive Modular Assembly System

System brings unmatched Reliability and Durability to your assembly line

## FEATURES

### Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54
- Redundant



## SPECIFICATIONS

### TYPE

2BDU-2B110A-2K1D-2WK1D

### TORQUE RANGE (Nm)

Min / Max: 11 - 110

### IDLE SPEED (1/min)

837

### FLOAT (mm)

25

### FLOATING ADAPTER

--

### FLOATING ADAPTER WITH FLANGE HOUSING

929053

### WEIGHT & DIMENSIONS

Weight 9.7 kg / 21.39 lb  
Length 432 mm / 17.01 in  
Side to Center 59 mm / 2.32 in  
Country of Origin: Germany









## 2BDU110T2A-A

ANGLE ATTACHEMENT, REVERSIBLE GEARS,  
TWIN TRANSDUCER

MODEL: BD

SIZE :2

11 - 110 Nm TORQUE



# Product Specifications

## Highly Productive Modular Assembly System

**System brings unmatched Reliability and Durability to your assembly line**

## FEATURES

## Spindle Assembly

- **Drive attachments:** Full complement of modular configurations
- **Motors:** New high precision
- **Transducer:** New digital. Available with single or dual units
- **Protection class:** IP54



## SPECIFICATIONS

**TYPE**

2BD-2B200A-2K3D-2ZB

### TORQUE RANGE (Nm)

Min / Max: 20 - 200

**IDLE SPEED (1/min)**

501

**FLOAT (mm)**

50

## FLOATING ADAPTER


910609

## FLOATING ADAPTER WITH FLANGE HOUSING

S308435

## WEIGHT & DIMENSIONS

Weight	6.5 kg / 14.33 lb
Length	481 mm / 18.94 in
Side to Center	56 mm / 2.20 in
Country of Origin:	Germany



## Highly Productive Modular Assembly System

System brings unmatched Reliability and Durability to your assembly line

## FEATURES

### Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54
- Redundant



## SPECIFICATIONS

### TYPE

2BD-2B200A-2/2K3D-2ZB

### TORQUE RANGE (Nm)

Min / Max: 20 - 200

### IDLE SPEED (1/min)

501

### FLOAT (mm)

50

### FLOATING ADAPTER





910609

### FLOATING ADAPTER WITH FLANGE HOUSING

S308435

### WEIGHT & DIMENSIONS

Weight 7.6 kg / 16.76 lb  
Length 578 mm / 22.76 in  
Side to Center 56 mm / 2.20 in  
Country of Origin: Germany



## 2BD200T2S-A

## STRAIGHT ATTACHMENT TWIN TRANSDUCER

MODEL: BD

SIZE :2

20 - 200 Nm TORQUE

# Product Specifications


## Highly Productive Modular Assembly System

**System brings unmatched Reliability and Durability to your assembly line**

## FEATURES

## Spindle Assembly

- **Drive attachments:** Full complement of modular configurations
- **Motors:** New high precision
- **Transducer:** New digital. Available with single or dual units
- **Protection class:** IP54



## SPECIFICATIONS

**TYPE**

2BD-2B200A-2VK3D

### TORQUE RANGE (Nm)

Min / Max: 20 - 200

**IDLE SPEED (1/min)**

468

**FLOAT (mm)**

50

## FLOATING ADAPTER

910609

## FLOATING ADAPTER WITH FLANGE HOUSING

S308438

## WEIGHT & DIMENSIONS

Weight	8.1 kg / 17.86 lb
Length	504 mm / 19.84 in
Side to Center	44 mm / 1.73 in
Country of Origin:	Germany




## 2BD200T10-A

### OFFSET DRIVE SINGLE TRANSDUCER

MODEL: BD

SIZE :2

20 - 200 Nm TORQUE



## Highly Productive Modular Assembly System

System brings unmatched Reliability and Durability to your assembly line

## FEATURES

### Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54
- Redundant



## SPECIFICATIONS

### TYPE

2BD-2B200A-2K3D-2VK3D

### TORQUE RANGE (Nm)

Min / Max: 20 - 200

### IDLE SPEED (1/min)

468

### FLOAT (mm)

50

### FLOATING ADAPTER

910609

### FLOATING ADAPTER WITH FLANGE HOUSING

S308438

### WEIGHT & DIMENSIONS

Weight 9.2 kg / 20.29 lb  
Length 601 mm / 23.66 in  
Side to Center 44 mm / 1.73 in  
Country of Origin: Germany




## 2BD200T20-A

## OFFSET ATTACHMENT, TWIN TRANSDUCER

MODEL: BD

SIZE :2

20 - 200 Nm TORQUE





# Product Specifications


## Highly Productive Modular Assembly System

**System brings unmatched Reliability and Durability to your assembly line**

## FEATURES

## Spindle Assembly

- **Drive attachments:** Full complement of modular configurations
- **Motors:** New high precision
- **Transducer:** New digital. Available with single or dual units
- **Protection class:** IP54



## SPECIFICATIONS

**TYPE**

2BD-2B200A-2WK3D

### TORQUE RANGE (Nm)

Min / Max: 20 - 200

**IDLE SPEED (1/min)**

472

**FLOAT (mm)**

25

## FLOATING ADAPTER




—

## FLOATING ADAPTER WITH FLANGE HOUSING

929053

## WEIGHT & DIMENSIONS

Weight	7.6 kg / 16.76 lb
Length	505 mm / 19.88 in
Side to Center	59 mm / 2.32 in
Country of Origin:	Germany



**Apex Tool Group, LLC**

Phone: +1 (800) 845-5629

Phone: +1 (919) 387-0099

Phone: +49 (0)7363 81-0

www.ClecoTools.com / www.ClecoTools.de

# Product Specifications




## Highly Productive Modular Assembly System

**System brings unmatched Reliability  
and Durability to your assembly line**

## FEATURES

## Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54
- Redundant



## SPECIFICATIONS

**TYPE**

2BD-2B200A-2K3D-2WK3D

### TORQUE RANGE (Nm)

Min / Max: 20 - 200

**IDLE SPEED (1/min)**

472

**FLOAT (mm)**

25

## FLOATING ADAPTER

—

## FLOATING ADAPTER WITH FLANGE HOUSING

929053

## WEIGHT & DIMENSIONS

Weight	8.7 kg / 19.18 lb
Length	602 mm / 23.70 in
Side to Center	59 mm / 2.32 in
Country of Origin:	Germany




## Highly Productive Modular Assembly System

System brings unmatched Reliability and Durability to your assembly line

## FEATURES

### Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54



## SPECIFICATIONS

### TYPE

2BDU-2B200A-2K3D-2ZB

### TORQUE RANGE (Nm)

Min / Max: 20 - 200

### IDLE SPEED (1/min)

501

### FLOAT (mm)

50

### FLOATING ADAPTER

910609

### FLOATING ADAPTER WITH FLANGE HOUSING

S308435

### WEIGHT & DIMENSIONS

Weight 7.5 kg / 16.54 lb  
 Length 310 mm / 12.20 in  
 Side to Center 56 mm / 2.20 in  
 Country of Origin: Germany







## 2BDU200T1S-A

STRAIGHT DRIVE, REVERSIBLE GEARS,  
SINGLE TRANSDUCER

MODEL: BD

SIZE :2

20 - 200 Nm TORQUE




## Highly Productive Modular Assembly System

System brings unmatched Reliability and Durability to your assembly line

## FEATURES

### Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54
- Redundant



## SPECIFICATIONS

### TYPE

2BDU-2B200A-2/2K3D-2ZB

### TORQUE RANGE (Nm)

Min / Max: 20 - 200

### IDLE SPEED (1/min)

501

### FLOAT (mm)

50

### FLOATING ADAPTER

910609

### FLOATING ADAPTER WITH FLANGE HOUSING

S308435

### WEIGHT & DIMENSIONS

Weight 8.6 kg / 18.96 lb  
Length 407 mm / 16.02 in  
Side to Center 56 mm / 2.20 in  
Country of Origin: Germany







## 2BDU200T2S-A

**STRAIGHT ATTACHMENT, REVERSIBLE GEARS, TWIN TRANSDUCER**

MODEL: BD

SIZE :2

20 - 200 Nm TORQUE



Apex Tool Group, LLC

Phone: +1 (800) 845-5629

Phone: +1 (919) 387-0099

Phone: +49 (0)7363 81-0

www.ClecoTools.com / www.ClecoTools.de


## Highly Productive Modular Assembly System

System brings unmatched Reliability and Durability to your assembly line

## FEATURES

### Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54



## SPECIFICATIONS

### TYPE

2BDU-2B200A-2VK3D

### TORQUE RANGE (Nm)

Min / Max: 20 - 200

### IDLE SPEED (1/min)

468

### FLOAT (mm)

50

### FLOATING ADAPTER

910609

### FLOATING ADAPTER WITH FLANGE HOUSING

S308438

### WEIGHT & DIMENSIONS

Weight 9.1 kg / 20.07 lb  
 Length 333 mm / 13.11 in  
 Side to Center 44 mm / 1.73 in  
 Country of Origin: Germany









## 2BDU200T10-A

OFFSET DRIVE, REVERSIBLE GEARS,  
SINGLE TRANSDUCER

MODEL: BD

SIZE :2

20 - 200 Nm TORQUE



# Product Specifications





## Highly Productive Modular Assembly System

**System brings unmatched Reliability and Durability to your assembly line**

## FEATURES

## Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54
- Redundant



## SPECIFICATIONS

**TYPE**

2BDU-2B200A-2K3D-2VK3D

### TORQUE RANGE (Nm)

Min / Max: 20 - 200

**IDLE SPEED (1/min)**

468

**FLOAT (mm)**

50

## FLOATING ADAPTER

910609

## FLOATING ADAPTER WITH FLANGE HOUSING

S308438

## WEIGHT & DIMENSIONS

Weight 10.2 kg / 22.49 lb

Length 430 mm / 16.93 in

Side to Center 44 mm / 1.73 in

Country of Origin: Germany




## Highly Productive Modular Assembly System

System brings unmatched Reliability and Durability to your assembly line

## FEATURES

### Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54



## SPECIFICATIONS

### TYPE

2BDU-2B200A-2WK3D

### TORQUE RANGE (Nm)

Min / Max: 20 - 200

### IDLE SPEED (1/min)

472

### FLOAT (mm)

25

### FLOATING ADAPTER

--

### FLOATING ADAPTER WITH FLANGE HOUSING

929053

### WEIGHT & DIMENSIONS

Weight 8.6 kg / 18.96 lb  
Length 335 mm / 13.19 in  
Side to Center 59 mm / 2.32 in  
Country of Origin: Germany






## 2BDU200T1A-A

### ANGLE DRIVE, REVERSIBLE GEARS, SINGLE TRANSDUCER

MODEL: BD

SIZE :2

20 - 200 Nm TORQUE




## Highly Productive Modular Assembly System

System brings unmatched Reliability and Durability to your assembly line

## FEATURES

### Spindle Assembly

- Drive attachments: Full complement of modular configurations
- Motors: New high precision
- Transducer: New digital. Available with single or dual units
- Protection class: IP54
- Redundant



## SPECIFICATIONS

### TYPE

2BDU-2B200A-2K3D-2WK3D

### TORQUE RANGE (Nm)

Min / Max: 20 - 200

### IDLE SPEED (1/min)

472

### FLOAT (mm)

25

### FLOATING ADAPTER

--

### FLOATING ADAPTER WITH FLANGE HOUSING

929053

### WEIGHT & DIMENSIONS

Weight 9.7 kg / 21.39 lb  
Length 432 mm / 17.01 in  
Side to Center 59 mm / 2.32 in  
Country of Origin: Germany



## 2BDU200T2A-A

### ANGLE ATTACHMENT, REVERSIBLE GEARS, TWIN TRANSDUCER

MODEL: BD

SIZE :2

20 - 200 Nm TORQUE

